

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

Well # 5

WATER WELL REPORT

RECEIVED

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WASCO

STATE OF OREGON

MAY 28 1978

48/2E-9bc

(Please type or print)

WATER RESOURCES DEPT.

SALEM, OREGON

003571

(Do not write above this line)

(1) OWNER:

Name IRL DAVIS JR.
Address Box 41 ID, Tygh Valley, OR. 97063

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Cable Dug
Driven Jetted Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

Threaded Welded
8" Diam. from +3 ft. to 73 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom? DRILLER
Yield: 62 gal./min. with 0 ft. drawdown after 3 hrs.
" AIR LIFT PUMP " " " "
" " " " " " "
Baller test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement grout
Well sealed from land surface to 73' ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 35 sacks
How was cement grout placed?
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County WASCO Driller's well number XXXXX 78-07
SW 1/4 NW 1/4 Section 9 T.4S R. 12 E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 104 ft.
Static level 198 ft. below land surface. Date 1 May 78
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8"
Depth drilled 505 ft. Depth of completed well 500 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Clay & Sandstone Brn	0	30	
Boulder & Cobble	30	35	
Gravel & Sand	35	67	
Basalt, grey, hard WB@ 104	67	171	
Basalt, brown, hard	171	197	
Conglomerates, fractures WB	197	273	198
Clay, Brown	273	278	
Cinder W/clay red WB	278	318	
Basalt, grey, hard	318	377	
Cinder, red, med-hard	377	415	
Sandstone, brown med. WB	415	505	198

RECEIVED

MAR 28 2008

WATER RESOURCES DEPT
SALEM, OREGON

Work started 17 Apr. 1978 Completed 3 May 1978
Date well drilling machine moved off of well 3 May 1978

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] William Lee Date 19 MAY, 1978
(Drilling Machine Operator)

Drilling Machine Operator's License No. 700

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Marinelli Drilling Co.
(Person, firm or corporation) (Type or print)

Address P.O. Box 571, Lake Oswego, OR. 97034

[Signed] James P. Marinelli
(Water Well Contractor)

Contractor's License No. 672 Date 19 MAY, 1978

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED APR 15 1970

RECEIVED APR 20 1970

Well #2

4/12-4dc

STATE ENGINEER SALEM, OREGON 5181 STATE ENGINEER SALEM, OREGON

(1) OWNER:

Name Irl Davis Address Tygh Valley, Oregon 003560

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon []

(3) TYPE OF WELL:

Rotary [] Cable [x] Dug []

(4) PROPOSED USE (check):

Domestic [x] Industrial [] Municipal [] Irrigation [] Test Well [] Other []

CASING INSTALLED:

0" Diam. from 0 ft. to 440 ft. Gage .250

(6) PERFORATIONS:

Perforated? [x] Yes [] No. Factory Perforated. Size of perforations 1/4 in. by 3/8 in. 1080 perforations from 380 ft. to 440 ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No. Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 310 ft. below land surface Date 3/24/70 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level. Was a pump test made? [x] Yes [] No. Yield: 60 gal./min. with ft. drawdown after hrs. Air Test. Baller test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m. Date. Temperature of water Was a chemical analysis made? [] Yes [x] No

(10) CONSTRUCTION:

Well seal—Material used Cement Grout Depth of seal 21' Diameter of well bore to bottom of seal 10 in. Were any loose strata cemented off? [] Yes [x] No Depth. Was a drive shoe used? [] Yes [x] No Did any strata contain unusable water? [] Yes [x] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Wasco Driller's well number Two SW 1/4 SE 1/4 Section 4 T. 4S R. 12 E W.M. Bearing and distance from section or subdivision corner 408' N, 1410' W Sec 4 co/comm 3,4,9,10

(12) WELL LOG:

Diameter of well below casing Depth drilled 440 ft. Depth of completed well 440 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include Soil, Brown Loam; Clay, Brown; Basalt, Brown; Gravel, Coarse, cemented; Basalt, black; Clay, brown; Gravel, coarse, Br. clay; Clay, Br., Gravel, fine; Basalt, brown, broken; Basalt, gravel, Blk., coa; Basalt, blk.

RECEIVED

MAR 28 2008

WATER RESOURCES DEPT SALEM, OREGON

Work started March 18, 1970 Completed March 24, 1970

Date well drilling machine moved off of well March 25, 1970

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Don Parry, Jr. Date 3/25/1970 (Drilling Machine Operator)

Drilling Machine Operator's License No. 640

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME PROJECT: Corporation (Person, firm or corporation) (Type or print)

Address One South Second, Walla, Walla, Wn.

[Signed] Gary Hisey, Jr. (Water Well Contractor)

Contractor's License No. 527 Date April 13, 1970

(USE ADDITIONAL SHEETS IF NECESSARY)

T 10585

copy checked in error

#2