NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER WELL REPORT

State Well No

25/2E-1 bd

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF OREGON Do not write above this li

ELAC 03965 Perna No.

AUG: 91977				_
(1) OWNER: VATER RESOURCES DEPT.	(10) LOCATION OF WELL:			
	County Clackamas Driller's well number			
Address 15301 S. E. Sunnyside Rivers	SE 1/4 NW 1/4 Section 1 T. 2 S R. 2 E.		E. w.:	<u>M.</u>
Clackamas, Oregon 97015	Bearing and distance from section or subdivisi	on corner		-
(2) TYPE OF WORK (check):				_
New Well Deepening Reconditioning Abandon				_
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 190 f			ft.
Rotary Driven Domestic Dindustrial Municipal	Static level 100 ft. below land	surface. Da	te 8/4/77	
Cable Jetted And Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per squar			
ASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well	below casing	0	
8-5/8 Diam from plus 1 ft. to 810 ft. Gage 250	Depth drilled 310 ft. Depth of completed well 310			ft.
	Formation: Describe color, texture, grain size and show thickness and nature of each stratu			
A TREOD A MICONG	with at least one entry for each change of forms	tion. Report	each change	In
Type of perforator used Type of perforator used Torch	position of Static Water Level and indicate prin			_
0/40	Silty brown clay	Prom 0	To SWL	_
Size of perforations 8/16 in. by 12 in. 400 perforations from 190 ft. to 290 ft.	Brown cemented gravel-occ.	1 .	LO	
	boulders	10	50	- ·
perforations fromft. toft.	Cemented boulders		90	- ·
perforations fromft. toft.	Red & brown basalt-occ. soft		1720	
(7) SCREENS: Well screen installed? Tyes Z No	streak	90 10	00	_
Manufacturer's Name	Hard gray-black & gray-brown			_
TypeModel No.	basalt	100 13	30	
Diam. Slot size Set from ft. to ft.	Cemented gravel w/brown clay-	100 0	· 2 5	
Diam. Slot size Set from ft. to ft.	occ. clean streaks	130 28		_ 19
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Brown clay w/boulders Hard brown clay	290 30 300 33	10	_
Was a pump test made? Yes No If yes, by whom?	hard brown clay	000 o,	10	
right 250 gal./min. with 180 ft. drawdown after 2 hrs.				
200 100	e e e e e			_
100 60				
20 20				
				_
Artesian flow g.p.m. ature of water Depth artesian flow encounteredft.	Work started 7/26/77 19 Complet	ed 8/4/7	77 19	_
	Date well drilling machine moved off of well	8/4/7		_
(9) CONSTRUCTION: Well seal—Material used Coment grout & 2% ge1	Drilling Machine Operator's Certification			_
Well sealed from land surface 160	This well was constructed under my	direct a	upervisio	n.
Diameter of well bore to bottom of seal	This well was constructed under my Materials used and information reported best knowledge and belief.	above are	e true to n	ny
Diameter of well bore below seal	- UATELLI F	×/1	5/77	
Number of sacks of cement used in well seal 20 sacks	(Drilling Michine Operator)	Date		••••
How was cement grout placed? Grout placed by lowering fluid level to 100' on 0. D. of casing	Drilling Machine Operator's License No.	520		<u></u>
and filling to ground level with grout	Water Well Contractor's Certification:			
	This well was drilled under my jurisd true to the best of my knowledge and be	lief.	this report	is
Was a drive shoe used? Yes No Plugs Size; location ft. Did any strata contain unusable water? Yes No	Name A. M. Jannsen Drilling Co. (Person, firm or corporation) (Type or print)			
Type of water? depth of stratRECEIVED	Address 21078 S. V. Tualatin Val	ley Hwy	. Aloha.	Or.
Method of sealing strata off	(Signed Steen Dille Kenny			
Was well gravel packed? [] Yes & No Size of grapel: 1	(Water Well Contractor)			
Gravel placed fromft. toft.	Contractor's License No. 79 Date	8/5/77	19	••••
WITTO DECOURS				_