



NOTICE TO WATER WELL CONTRACTOR: The original and first copy of this report are to be filed with the

RECEIVED AUG 30 1971

WATER WELL REPORT

4443 MAR 11 1973 G5621

State Well No. 6/2W-26db

STATE ENGINEER, SALEM, OREGON (Please type or print) SALEM, OREGON (Do not write above this line)

State Permit No.

(1) OWNER:

Name M. T. Ray Address 8127 Nutmeg Street NE Salem, Ore.

(2) TYPE OF WORK (check):

New Well [X] Deepening [ ] Reconditioning [ ] Abandon [ ] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [ ] Driven [ ] Cable [X] Jetted [ ] Dug [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [X] Industrial [ ] Municipal [ ] Irrigation [X] Test Well [ ] Other [ ]

CASING INSTALLED:

8" Diam. from top ft. to 180 ft. Gage 250

PERFORATIONS:

Type of perforator used Mills Size of perforations 3/8 in. by 2 in. 200 perforations from 130 ft. to 180 ft.

(7) SCREENS:

Well screen installed? [ ] Yes [X] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Was a pump test made? [X] Yes [ ] No If yes, by whom? Driller Yield: 100 gal./min. with 35 ft. drawdown after 5 1/2 hrs. 150 " 50 " 5 1/2 " 180 " 55 " 5 1/2 "

(9) CONSTRUCTION:

Well seal—Material used Cement and Puddle Clay Well sealed from land surface to 20 ft. Diameter of well bore to bottom of seal 10 in. Diameter of well bore below seal 8 in. Number of sacks of cement used in well seal 6 sacks Number of sacks of bentonite used in well seal Brand name of bentonite Number of pounds of bentonite per 100 gallons of water Was a drive shoe used? [X] Yes [ ] No Plugs Size: location Did any strata contain unusable water? [ ] Yes [X] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [ ] Yes [X] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Marion Driller's well number 1572 1/4 Section 26 T.6S R.2W W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 120 ft. Static level 65 ft. below land surface. Date 8-26-71 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing Depth drilled 180 ft. Depth of completed well 180 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include Top Soil, Brown silty clay, Brown clay, Blue Clay, Sticky blue sandy clay, Brown sand stone, Cemented clay and gravel, Brown sand and gravel, Brown gravel (water), Tight sand and gravel with blue clay, Black sand and gravel with clay, Brown sand and gravel.

RECEIVED

OCT 31 2008

WATER RESOURCES DEPT SALEM, OREGON

Work started Aug. 16, 1971 Completed Aug. 27, 1971 Date well drilling machine moved off of well Aug. 27, 1971

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Dallas L. Peas (Drilling Machine Operator) Date 8-27-71, 19

Drilling Machine Operator's License No. 752

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name WILLAMETTE DRILLING COMPANY (Person, firm or corporation) (Type or print)

Address 7641 35th Ave. NE Salem, Oregon 97303

[Signed] Emil O. Beier (Water Well Contractor)

Contractor's License No. 2 Date 8-27-71, 19

WELL # 1