



NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

RECEIVED AUG 9 - 1971

WATER WELL REPORT

MULT 921 G5614

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from date of well completion.

STATE ENGINEER SALEM OREGON

STATE OF OREGON (Please type or print)

State Well No. W/1-202 db State Permit No.

(1) OWNER:

Name COLUMBIA EDWATE GOLF AND COUNTRY Club County MULT Address 2137 NE MARINE DRIVE PORTLAND ORE 97211

(10) LOCATION OF WELL:

Driller's well number 5281 Section 2 T. 1N R. 1E W.M. Bearing and distance from section or subdivision corner

(2) TYPE OF WORK (check):

New Well [X] Deepening [ ] Reconditioning [ ] Abandon [ ] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [ ] Cable [X] Dug [ ] Driven [ ] Jetted [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [ ] Industrial [ ] Municipal [ ] Irrigation [X] Test Well [ ] Other [ ]

CASING INSTALLED:

12" Diam. from 0 ft. to 135 ft. Gage 330 16" Diam. from 0 ft. to 35 ft. Gage 1312

(11) WATER LEVEL: Completed well.

Depth at which water was first found 110 ft. Static level 1 ft. below land surface. Date 7/19/71 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing Depth drilled 135 ft. Depth of completed well 135 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include GRAVEL FILL, SILT AND SAND, BLUE CLAY, FINE SANDY SILT, PACKED SAND AND SILT, WATER BEARING GRAVEL, CLAY AND GRAVEL.

(6) PERFORATIONS:

Perforated? [X] Yes [ ] No. Type of perforator used STAR Size of perforations 2 1/8 in. by 1 1/4 in. 480 perforations from 119 ft. to 131 ft.

(7) SCREENS:

Well screen installed? [ ] Yes [X] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [X] Yes [ ] No. If yes, by whom? STRASSER Yield: 1080 gal./min. with 3 1/4 ft. drawdown after 4 hrs.

(9) CONSTRUCTION:

Well seal-Material used CEMENT GROUT Well sealed from land surface to 35 ft. Diameter of well bore to bottom of seal 16 in. Diameter of well bore below seal 12 in. Number of sacks of cement used in well seal 27 sacks

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] DATE Smith Date AUG 4, 1971 (Drilling Machine Operator) Drilling Machine Operator's License No. 175

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name R.J. STRASSER DRILLING Co (Person, firm or corporation) (Type or print) Address 8110 SE SUNSET LANE PORTLAND ORE [Signed] Robert J. Strasser (Water Well Contractor) Contractor's License No. 10 Date JULY 26, 1971

RECEIVED

FEB 23 2009

WATER RESOURCES DEPT SALEM, OREGON

Work started JUNE 11 1971 Completed JULY 23 1971 Date well drilling machine moved off of well JULY 23 1971

