STATE OF OREGON WATER WELL REPORT (as required by ORS 537.765)

OCT 24 1994

(as required by ORS 537.765) PLEASE TYPE	or PRINT IN INK
(1) OWNER:	(10) LOCATION OF WELL by legal description:
Name CM LIFETISEIC	County Matific Sw. All of Section 33 of
Address RT2 857 357-8	Township (Township is North or South) Range (Range is East or West) WM.
City M. 1 Tim Free WTER State ORGAN	Tax Lot Lot Block Subdivision
(2) TYPE OF WORK (check): 97%	MAILING ADDRESS OF WELL (or nearest address) County Road
New Well	The state of the s
If abandonment, describe material and procedure in Item 12.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL of COMPLETED WELL:
Rotary Air Driven Domestic Industrial Municipal	Depth at which water was first found 68
Rotary Mud Dug Irrigation Thermal: Withdrawal Reinjection	Static level 50 ft. below land surface. Date 9-7-9
_ Other: _	Artesian pressure lbs. per square inch. Date
Cable Bored Piezometric Grounding Test	(12) WELL LOG: Diameter of well below casing 10"
(5) CASING INSTALLED: Steel Plastic Welded D	Depth drilled /42 Diameter of well below casing
10 +1 20	Formation: Describe color, texture, grain size and structure of materials; and show thickness
	and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal
ft. Gauge	water-bearing strata.
LINER INSTALLED: Steel Plastic	MATERIAL D. C.
Threaded Welded D	MATERIAL From To SWL
Diam. from AOL ft. to 180 ft. Gauge SX40	Bin 80,1 + Grave 1 0 2
(6) PERFORATIONS: Perforated? ✓ Yes □ No Line L	Tansit Builders 2 12
Size of perforations in. by in.	LOOSE Gravel Brusilt 12 16
6.72 perforations from 120 ft. to 182 ft.	Bru S. IT Comensed Gravel 16 22
perforations fromft. toft.	Tow SIT Computed Grave 1 22 68
perforations from ft. to ft.	Brown Silt Comented Grave 68 128 50
	Grey comented Graves
(7) SCREENS: Well screen installed? Yes No	Clean unter Barring 128 180 50
Manufacturer's Name	Breeze S'IT LOOSO GROVE 180 192 50
Type	
Diam Slot Size Set from ft. to ft.	
Diam Slot Size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered	
(6) WELL 1ES1S: below static level	DESCRIPTION OF THE PROPERTY OF
Was a pump test made? Yes No If yes, by whom?	RECEIVED
Yield: gal./min. with ft. drawdown after hrs.	
• • •	FEB 1 2 2009
Air test 300 gal./min. with drill stem at 180 ft. 2 hrs.	
Bailer test gal./min. with ft. drawdown after hrs.	WATER RESOURCES DEPT
Artesian flow g.p.m.	SALEM, OREGON
Temperature of water 54/ Depth artesian flow encountered	
(O) CONCERNICATION:	Date work started 8-30-94 /completed 9-9-94
(9) CONSTRUCTION: Special standards: Yes □ No 🕱 Well seal—Material used	Date well drilling machine moved off of well 9-7 1994
	(unbonded) Water Well Constructor Certification (if applicable):
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used and
	information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	ro: - n
Amount of sealing material	[Signed], 19
How was cement grout placed?	(bonded) Water Well Constructor Certification;
	Bond Issued by: AetVA
li	(number) (Surety Company Name)
Was pump installed? Depth ft.	On behalf of (type or print name of Water Well Constructor)
Was a drive shoe used? XYes No Plugs Size: location ft.	· · · ·
Did any strata contain unusable water? Yes No	This well was drilled under my jurisdiction and this report is true to the
Type of Water? depth of strata	best of my knowledge and belief:
Method of sealing strata off	(Signed) (Vater Well Constructor)
Was well gravel packed? Yes No Size of gravel:	(Dated) 9-7-94
Gravel placed from ft. to ft.	

NOTICE TO WATER WELL CONSTRUCTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

SP*46866-6999