are to be filed with the

WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF OREGENE CE VE Date Well No. S. (Please type or print) DEC 15 1977

(Do not write above this line) DEC 151977 State Permit No.

SEAT WE CARD 12-19-17

. 2	6	6	ج	
-2	L)		

	WATER RESOURCES DEPT.				
(1) OWNER:	(10) LOCATRON RECHELL:				
Name John Stacey	County Uma+'//a Driller's well number				
Address R+#2 Box /2	1/13 0 31/ 57/				
milton-tree water or 97862					
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner				
New Well Deepening . Reconditioning . Abandon .					
If abandonment, describe material and procedure in Item 12.	(11) WATER TEVEL, Completed well				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well. Depth at which water was first found ? Ø ft.				
Rotary Driven Domestic Industrial Municipal Domestic Industrial	Static level 3/ ft. below land surface. Date				
Cable	Artesian pressure Ibs. per square inch. Date				
CASING INSTALLED: Threaded Welded &	(12) WELL LOG: Diameter of well below casing				
8 " Diam. from + tt to 65/2tt. Gage 0.250	, and the same of				
ft. to ft. Gage					
"Dlam, from	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated.				
PERFORATIONS: Perforated? [] Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.				
Type of perforator used	MATERIAL From To SWL				
Size of perforations in. by in.	Soil Boulders 06				
perforations fromft. toft.	Beulderes + Gravel 6 44				
perforations from	Carnery, Grovel 44 71				
-	Clay + Gravel 71 84				
perforations fromft. toft.	Gement Gravel 84 124				
(7) SCREENS: Well screen installed? Yes No	5000 550000 1211 128				
Manufacturer's Name	Basalt Brown 128 140				
Type Model No.	Cinder Brown 140 149				
Diam. Slot size Set from ft. to ft.	Bosolt. Gray 149 158				
Diam Slot size	GINDLE BROWN 158 172				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	BECEIVED				
Was a pump test made? Yes No If yes, by whom? 547772	MAY 10 8 2009				
A	MAR 0.5 2009				
Yield: 96 gal./min. with 8/ ft. drawdown after 2 hrs.					
***	WATER RESOURCES DEPT				
# # # # # # # # # # # # # # # # # # #	1				
Bailer test gal./min. with ft. drawdown after hra.	SALEN, OREGON				
Artesian flow g.p.m.					
erature of water 5 (Depth artesian flow encountered ft.	Work started /4-27 19 2 Completed //-/0 - 1977				
(9) CONSTRUCTION:	Date well drilling machine moved off of well //-//- 1977				
Well seal-Material used Benton: te Sturay	Drilling Machine Operator's Certification:				
Well sealed from land surface to 20 ft.	This well was constructed under my direct supervision.				
Diameter of well bore to bottom of seal & in.	Materials used and information reported above are true to my best knowledge and belief.				
Diameter of well bore below, seal					
Number of sacks of the used in well seal	[Signed] Chargestalt Title Operator)				
How was cement grout placed?	Drilling Machine Operator's License No. 22				
A STATE OF THE STA	Water Well Contractor's Certification:				
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.				
Was a drive shoe used? Yes No Plugs Size: location ft.	Name C. W. Suzzzers Well DRilling				
Did any strata contain unusable water? Yes No Type of water? depth of strata	(Person, the or corporation) (Type or print) Address P + 3 Boy 143-1-171 17. 08				
Method of sealing strata off					
Was well gravel packed? [Yes B'No Size of gravel:	[Signed] (Water Well Contractor)				
Gravel placed from	Contractor's License No. 57.5 Date //-/0- , 1927				
(IISE ADDITIONAL SUPPLS IP NECESSARY)					