	L REPORTE CEIVED OREGON AUG2 1976 tate Well No.			
STATE ENGINEER, SALEM, OREGON MIN 2	OREGON AUG 2 1976 tate Well No.	25	2/,,	11:-21
STATE ENGINEER, SALEM, OREGON With Within 30 days from the date of well completion. (Do not write all	or print) NATER RESOURCES DEFINITION SALEM, OREGON CRO	m C	1 14 1 4	1618
(1) OWNER:	(10) LOCATION OF WELL:			
Name Charles Tompkins	County Lake Driller's well m	mber	1	
Address Fort Rock, Oregon 97735		R 14	E	W.M.
and the state of t	Bearing and distance from section or subdivisi		132	2 ft.
(2) TYPE OF WORK (check):	south, 1318 ft. W from t	he N	cor	mer.
New Well M Deepening   Reconditioning   Abandon				
If shandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	33		
Rotary Driven Domestic Dindustrial Municipal	Static level 30 ft. below land a	urface. I	Date F 12	i <del>v</del> 20
Box   Boxed   Irrigation   Test Well   Other	Artesian pressure ————————————————————————————————————	e inch. I	Date	
(5) CASING INSTALLED: Threaded   Welded E	(12) WELL LOG: Diameter of well i	elow cas	ng 1	2 in.
2 ID Diam from 0 n to 128 n Gego 1 in.	Depth drilled 366 ft. Depth of compl	eted well	366	·· fL
ft. toft. Gage	Formation: Describe color, texture, grain size a			
Diam. from # Gage	and show thickness and nature of each stratus with at least one entry for each change of forms	n and aq	uifer pe	netrated,
(6) PERFORATIONS: Perforated?   Yes M. No.	position of Static Water Level and indicate prin	cipal wate	er-bearis	ng strata.
Type of perforator used	MATERIAL	From	To	swi.
Size of perforations in. by in.	Top Soil	0	3	
perforations fromft. toft.	Cemented Gravel	3	16	
perforations fromft. toft.	Diatomaceous Earth	16	32	
perforations from ft. to ft.	Black sand, small gravel	32	-33	
(7) SCREENS: Well screen installed?   Yes  No	Water Estimated 5 gph.	~-		<del>-33</del> -
Manufacturer's Name	Black sand, Blue Clay	33	54	
Type Model No.	Rlack sand	54	68	
Dism. Slot size Set from 11. to 15.	Small amount of Add Wat		-06	33
Dism. Slot size Set from 1 to 1	Hard Blue Clay	68.	70	
(8) WELL TESTS: Drawdown is amount water level is	Black Sand	70	84	
NOMELECT DETOM RESIDE TEACT	Hard Blue Clay	84	96	
Was a pump test made? Dives I No It yes, by whom fart Reed  at: 1300 gal/min with 10 r. drawdown after 17 hrs.	Black Sand & more water Hard Red & Yellow Clay	96	104	
id: 1300 gal./min. with 10 ft. drawdown after 17 hrs.	Small amount ofgravel a	130	<del>190</del>	
And the state of t	wat the water (additional water	tor		
The second section of the second section is a second section of the second section of the second section secti	Clay	150		
Baller test gal./min. with ft. drawdown after hrs.	Black Sand	310	350	
terian flow g.p.m.	Small Brown Gravel 444	350	366 L	32
Temperature of water 5 0 Depth artesian flow encountered ft.	Work started May 20 1976 Complete	<u>d July</u>	<del>7 20</del>	<sup>19</sup> 76
(9) CONSTRUCTION:	Date well drilling machine moved off of well	uly ?	20	1976
Well seel-Material used Coment	Drilling Machine Operator's Certification:			
Well sealed from land surface to 20	This well was constructed under my Materials used and information reported			
Diameter of well bore to bottom of seal16	best knowledge and belief.			
Diameter of well bore below sealin.	[Signed]	Dațè		., 49
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No			
Number of sacks of bentonite used in well seal				
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:			
of water lbs./100 gals.	This well was drilled under my jurisdi true to the best of my knowledge and beli		i this r	eport is
Was a drive shoe used?   Yes   No Plugs Size: location ft.	Name		٠.	٠
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	(12)	o or petr	at)
Type of water? Alkall depth of strata 1 Pt.	Address			
Method of scaling strata off CC.50 C.	[Signed] Charles Jamphy		wner	•
Was well gravel packed? The Ro Size of the Color of the C	(Water Well Control			
Gravel placed from ft. to ft.	Contractor's License No Date J1	L <b>y2</b>	8	., 1976
AU 2 DP ZOUJAL SH	EETS IF NECESSARY)		SP	*45456-119

NOTICE TO WATER WELL CONTRACTOR The original and first copy	RECEIVED				
of this report are to be WATER WE	1111 1 1001 75 1311 2 3CD				
STATE OF OREGON STATE ENGINEER, SALEM, OREGON Sile  (Please type or print ATER RESOURCES DEPT.  within 30 days from the date of well completion.  (Do not write above this line) SALEM, OREGON  C# 52623					
within 30 days from the date of well completion. (Do not write a					
at wen completion. (Do not write a	FROM C# 5262				
(1) OWNER:	(10) LOCATION OF WELL:				
Name Charles tompking	County LAKE Diffler's well number				
Address Fart ROCK OREGAN SWYN	4/SE 4 NE 4 Section 37 T. 25 R. 14E. W.				
	Bearing and distance from section or subdivision corner				
(2) TYPE OF WORK (check):	1322 ft. S. and 1378 ft W. from the				
New Well A Despening   Reconditioning   Abandon	Coknew of Sect 34				
If abandonment, describe material and procedure in Item 13.	(11) WATER LEVEL: Completed well.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 3.0 4+.				
Rotary Driven Domestic Dindustrial Municipal D	Static level 30 ft. below land surface. Date				
Cable Bored D britgation M Test Well D Other D	.Artesian pressure Ibs. per square inch. Date				
CEL CACTUC VATORIAT I TOD.	(9/4)				
(5) CASING INSTALLED: Threaded   Welded   Welded	(12) WELL LOG: Diameter of well below casing				
12 Diam. from Q ft to 87 ft Gage Acid	Depth drilled 300 ft. Depth of completed well 300 f				
8 " Diam from 80 st to 8// st Gage 14/16-	-Formation: Describe color, texture, grain size and structure of materials and show thickness and nature of each stratum and aquifer penetrated				
	with at least one entry for each change of formation. Report each change t				
(6) PERFORATIONS: Perforated? [] Yes [2] No.	position of Static Water Level and indicate principal water-bearing strate				
Type of perferator used	MATERIAL From To SWL				
Size of perforations in. by in.	top soil				
perforations from ti_ to ft.	Small Brown Pen Grave! 4 /4				
perforations from ft. to ft.	ivellaw clay 14 30				
perforations fromft. toft.	Black Sand with water 30 75 30				
(7) SCREENS: Well screen installed? Thes R No	(Estimate 100 7.0.4.)				
Manufacturer's Name	Soft Black Rock - Probably 75 90 30				
Type Model No	Sand stone)				
Diam. Slot size Set from ft. to ft.	Black Sand Callitions water 90 200 30				
The state of the s	HARD Blue Clay 200 237 30				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	400SC Grey Sand 237 262 30				
Was a pump test made? ☐ Yes 🎒 No If yes, by whom?	Brown & Grey CLAY 262 300 30				
: gal/min, with ft. drawdown after hrs.	Some Black Cinders at 7854h				
	top with vulber vactor to 12 iv casing.				
Beller test gal./min. with it. drawdown after hrs.	top with rubber parker to 12.14 casing.				
gian flow g.p.m.	7				
Temperature of water - Depth artesian flow encounteredft.	Wark started July 10 19 77 Completed may 7 198				
(9) CONSTRUCTION:	Date well drilling machine moved off of well June 15 199				
- L	Drilling Machine Operator's Certification:				
Well seal-Material used SchneatT	This well was constructed under my direct supervision				
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.				
Diameter of well bore below seal _125 in.	[Signed] Date, 19				
Number of sacks of coment used in well seal sacks	(Drilling Machine Operator) Drilling Machine Operator's License No.				
Number of sacks of bentonite used in well seal sacks	Tarming Machine Operator's Internet No.				
Brand name of bentonite  Number of pounds of bentonite per 100 sallons	Water Well Contractor's Certification:				
0 mater   100 gale	This well was drilled under my jurisdiction and this report is				
War's drive shoe used? If Yes   No Plus Size: location fi.	true to the best of my knowledge and belief.  Name Charles Tom PKANS				
Did any strata contain unusable water? Yes 🗆 No	(Person, firm or corporation) (Type or print)				
Type of water? ALKAL; depth of strate 25 to 80 ft.	Address				
Method of sealing strata off Casing	[Signed] Charles Tomahin				
Was well gravel packed? □ Yes D'No Size of gravel;	(Water Well Chitrafter)				
Gravel placed from ft. to	Contractor's License No. Date June 29, 1921				
KEUGI Mahonai, se	ERTS IF NECESSARY) . SP-4566-11				

1.4

Pake 429 State Well No. 205/15E-224 WATER RESOURCES DEPARTMENTSEP 7 1978 STATE OF OBEGON SALEM, OREGON 97310

Within 30 days from the day eTER RESOURCES DEPT write above this line)

SALEM, OREGON State Permit No. ... (1) OWNER: (10) LOCATION OF WELL: Theodore Tight Driller's well number County Star Route Fort Rock, Oregon 14 N.W. 14 Section 22 T. 26 5 R. 15 E Bearing and distance from section or subdivision corner TYPE OF WORK (check): Deepening [ Reconditioning Abandon [ If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found 61 Rotary Driven 🗆 ft. below land surface. Date 8-11-78 Domestic 🔲 Industrial 🔲 Municipal 🗍 Static level Cable Jetted 🔲 Irrigation Test Well Other Artesian pressure lbs. per square inch. Date CASING INSTALLED: Threaded | Welded (12) WELL LOG: Diameter of well below casing .. " Diam from + 1 tt to 104 tt Gage , 250 Depth drilled 262 ft. Depth of completed well Formation: Describe color, texture, grain size and structure of materials: " Diam. from ..... .. ft. to ..... and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. PERFORATIONS: Perforated? | Yes | No. Type of perforator used MATERIAL From Brown 3 Sandy Size of perforations in. by Brown 3 Clay 61 .... perforations from ..... 67  $\omega B$ Sanc Brown ... perforations from ..... 98 Brown \_ perforations from ..... 104 Pumic Green+ White wB (7) SCREENS: Well screen installed? | Yes | No Basalt Hard Grev 104 w.B. Manufacturer's Name Lava Cinders Brown W.B with Clay Streaks ... Set from ..... Drawdown is amount water level is lowered below static level (8) WELL TESTS: Was a pump test made? Yes WNo If yes, by whom? Yield: gal./min. with ft. drawdown after hrs. a" hole from te test 1110 gal./min. with 18ft. drawdown after 4 Artesian flow g.p.m. 8-7 8-11 1978 perature of water Depth artesian flow encountered .. Work started 19 78 Completed Date well drilling machine moved off of well (9) CONSTRUCTION: Grout Drilling Machine Operator's Certification: Well seal-Material used ...... This well was constructed under my direct supervision. Materials used and information reported above are true to my Well sealed from land surface to ..... best knowledge and belief [Signed] State Date 8-17, 19.78 Number of sacks of cement used in well seal ..... How was cement grout placed? Gravity Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name West Coast Drilling ( Was a drive shoe used? 🗆 Yes 🗷 No Plugs ............. Size: location ...... (Type or print) (Person, firm or corporation) Did any strata contain unusable water? 

Yes No depth of strate Type of water? Method of sealing strata off Was well gravel packed? Tyes No. Size of gravel: Q (Water Well Contractor's License No. 519... Date ..... Gravel placed from ......ft. to ... SALEM OREGON

NOTICE TO WATER WELL CONTRACTO
The original and first copy of this speci

are to be filed with the

## **LAKE 51879**

STATE OF OREGON
WATER SUPPLY WELL REPORT
(as required by OR\$ 537.765)

WELL LD. # L	
	187901

antifections for compacting this report are on the last page of this form.		
(1) LAND OWNER Name CON CONFORMATION	(9) LOCATION OF WELL (legal description)	
Name Hall La France	(9) LOCATION OF WELL (legal description)	
Address STON CONTROL	Tax Lot 6 8 CC	
City (Callelle Seaso - Zip 7772)	Township North Page 150	
(4) THE OR HADDE	Section 1/4 C 1/4	
(2) TYPE OF WORK New Well		
☐ Deepening ☐ Alteration (repair/recondition) ☐ Abandonment ☐ Conversion	Lat (degrees or decimal)	
(3) DRILL METHOD	Long (degrees or decipual)	
Rotary Air Rotary Mud Cable Auger Cable Mud	Street Address of Well (or nearest address) SCLTL (c, ice in	
Other	alver 10 KC CC 17735	
- Valet		
(4) PROPOSED USE	(10) STATIC WATER LEVEL	
Domestic Community Industrial Integration	n. below land surface.	
☐ Thermal ☐ Injection ☐ Livestock ☐ Other	ft. below hand surface. Date	
(5) BORE HOLE CONSTRUCTION Special Construction: Yes No	Artesian pressure lb. per square inch Date	
Depth of Completed Well 7 t.	(11) WATER BEARING ZONES > 20	
Explosives used: Yes No Type Amount	Depth at which water was first found	
BORE HOLE SEAL	Freque To Estimated Flow Rate SWL	
Diameter From To Muterial From To Sacks or Pounds	From Estimated Flow Rate SWL	
26" 0 70 Comed C 16 H		
19 521 12 134		
How was seal placed: Method	(12) WELL LOG Ground Elevation	
Other		
Backfill placed from ft. Material	Material From To SWL	
Gravel placed from ft. to ft. Size of gravel	1 00 1 00 10 mm	
	Carrie Car Hora Too Tura	
6) CASING/LINER	1000 1000 CROX CO 140 160	
Casing: 14   C   74c   Super Stepl Plantic Welded Threaded	16. 116. 16136 1686 1635 1886	
	17000	
	MODE BUTTON SECTIONS	
	Contact of the second	
Liner:	100 100 100 100 100 100 100 100 100 100	
	The contract of the contract o	
Drive Shoe used   Inside   Qutside   None	6 Cery + cr 6 10 9 9 9 100	
Final location of shoe(s) CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC	200 + MACK CIACL 460 460	
WW 1000000 01 31000(0)	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
7) PERFORATIONS/SCREENS	मिलदा लालर हराला गर रहे।	
Perforations Method		
Screens Type Material	Date Started 7-70-C Completed 6.22-06	
From To Slot Number Diameter Tele/pipe Casing Liner	Dez statut Compace	
From To Slot Number Diameter Tele/pipe Casing Liner Size Size	(unbonded) Water Well Constructor Certification	
	I certify that the work I performed on the construction, deepming, alteration, or	
	abandonment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to	
	the best of my knowledge and belief.	
	///	
	WWC Number Date	
8) WELL TESTS: Minimum testing time is 1 hour	1 1 minutes	
Pump Bailer Air Flowing Artesian	Signed	
	(bonded) Water Well Constructor Certification	
Yield gal/min Dramdown Drill stem at Time	I accept responsibility for the construction, deepening, alteration, or	
	abandonment work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water	
AFAEN/EN		
emperature of water Depth Artesian Flow Found	supply well construction standards. This report is true to the best of my knowledge	
•	and belief.	
'as a water analysis done? Yes By whom		
and the Company which they be colored in the control of the colored in the colore		
Salty Muddy Odor RECE VEGER RESOURCES DEPT	Signed	
epth of strata; RECEIVEMEN RESOURCES DETV		
SALEM, UNGOVA		

## WATER SUPPLY WELL REPORT (as required by ORS 537.765)



WELL I.D. #L START CARD#

Actor serious for comparing the report are an the last page of this form.		
(1) LAND OWNER Name Well Number	(9) LOCATION OF WELL (legal description)	
Addres 580 N Central		
CITY COOLLEGE State CK Zip 97423		
	Section North Nort	
(2) TYPE OF WORK New Well  Deepening Alteration (repair/recondition) Abandamment Conversion	Lat	
Conversion	Long or (degrees or decimal)	
(3) DRILL METHOD	Servet Address of Well (or pearset address) \$0/86 Cerster in	
□ Rotary Air □ Rotary Mud □ Cable □ Auger □ Cable Mud	Silver Address of Wall (of Descript address)	
(4) PROPOSED USE	(10) STATIC WATER LEVEL	
☐ Domestic ☐ Community ☐ Industrial ☐ Brigation ☐ Thermal ☐ Injection ☐ Livestock ☐ Other	3 A ft. below lead surface. Date 7-20-06	
Therman Timlection Titrespect Titrespect	ft. below land surface. Date	
(5) BORE HOLE CONSTRUCTION Special Construction: Yes No Depth of Completed Well	Artesian pressure lb. per square inch Date	
Depth of Completed Well ft. Explosives used: Yes No Type Amount	(11) WATER BEARING ZONES > 20	
BORE HOLE SEAL	Depth at which water was first found	
Diameter From To Material From To, Sacks or Pounds	To Retinated Flow Rate SWL	
36" 0 70 COMUNT 0 70 FT		
12" 70 557 12 1324		
How was seal placed: Method	(12) WELL LOG Ground Elevation	
Backfill placed from ft. to ft. Material		
Gravel placed from ft. to ft. Size of gravel	Grey Claus From L. To SWL	
· · · · · · · · · · · · · · · · · · ·	CT 108 CIGIC 10 10C	
(6) CASING/LINER	COSE SCIENCING TOO 140	
Diameter From To Gauge Steel Flastic Welded Threaded Oasing:   V   D   745   1/4   D   D	2044 CICLE 1662 2004, 16-5, 180	
Casing: 14	17 AVEL SKILL ST. SMIT 200 360	
	017 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	
Line:	1 4 700 (1666) 380 900	
	13 CC 2 2 CC 1 1 30 410	
Drive Shoe used   Inside   Outside   None First Inserting of shorts   PUSH   CASUS   OOW   G' w Zook	ROLLEMAN CKILL 440 460	
Final location of shoo(s) PUSH CUSH OOUN G W/200"	>0++ 13/0CK CKTO, APC 480	
(7) PERFORATIONS/SCREENS	101 + 01716 11108 480 310 1100 3101 BOSAN 510 537 -	
Perforations Method		
Scroens Type Material	Date Started 7-20-0 Completed 8-22-06	
From To Slot Number Diameter Tele/pipe Casing Liner	(unbonded) Water Well Constructor Certification	
T	I certify that the work I performed on the construction, despening, alteration, or	
	abundamment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to	
	the best of my brandedge and belief	
	WWC Number Dete	
(8) WELL TESTS: Minimum testing time is 1 bour		
Pump Bailer Air Flowing Artesian	Signed	
Relation Drawdown Drill stem at Time	(bondes) Water Well Coastructor Certification	
	I accept responsibility for the construction, deeptaing, alteration, or shandonment work performed on this well during the construction dates reported	
11400 galler nun	above. All work performed during this time is to compliance with Oregon water	
Temperature of protes Depth Artesian Flow Found	supply well construction standards. This report is true to the best of my knowledge and belief.	
Did and straid contain water not suitable frances with 1 3 3 30 butle	WWC Number Date	
[Up] _ M /MII ALAWED SECOMOCER DEF	Signed	
WATER RESOURCES SETT AUG 2 1- SETTE OFFE		

## RON'S OIL COMPANY

== 580 North Central

Coquille. Oregon 97423 (541) 396-557)

The following people were drilling machine operators during the construction of this well.

JUL 18 2007

Date

Date

Wusne E Hand Dwayne Hand

Date

RECEIVED

DEC 1 9 2007

WATER RESOURCES DEPT SALEM OREGON

RECEIVED

AUG 2 7 2009

**WATER RESOURCES DEPT** SALEM, OREGON