## WATER WELL REPORT ✓ STATE OF OREGON

# RECEIVED

JUL 21 1981

State Well No. 365/2F-22C

WATER RESOURCES DEP' state Permit No. ..... SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:	
Name Kenneth Allison	County Klamath Driller's well	numbon
Address 2028 Reclamation		R. 12 E W.M.
City Klamath Falls State OR 97601	Tax Lot # Lot Blk	
	Address at well location:	Subdivision
(2) TYPE OF WORK (check):	Address at well location:	
New Well ☑ Deepening □ Reconditioning □ Abandon □	(14) WA CORD Y DYDY C	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	142 ft.
		and surface. Date 7-7-81
Rotary Air XI Driven	Artesian pressure lbs. pe	er square inch. Date
☐ Bored ☐ Thermal: Withdrawal ☐ Reinjection ☐		casing 12* & 8"
(5) CASING INSTALLED: Steel 🔯 Plastic 🗆		completed well 597 ft.
Threaded  Welded	Formation: Describe color, texture, grain size and stru	
12" Diam from +1 ft to 277 ft Gauge .250	thickness and nature of each stratum and aquifer pene for each change of formation. Report each change in	
	and indicate principal water-bearing strata.	TOTAL OF COURT WATER LEVEL
LINER INSTALLED:	MATERIAL	From To SWL
	Sandy Top Soil	0 1
		1 19
(6) PERFORATIONS: Perforated? ☐ Yes ☒ No	Pumice & Gravel	19 36
Type of perforator used	Brown Clay	
Size of perforations in. by in.	Blue Clay	36 41 41 50
	Yellow Clay & Pumice	
perforations from ft. to ft. to ft.	Brown Sandstone	
perforations from ft. to ft.	White Pumice	59 70
	Brown Clay	70 76
	Green Clay	76 81
Manufacturer's Name	Dicker Dank	81 82
Type Model No	Blue Clay	82 139
	Black Cinder Rock	139 141
Diam. Slot Size Set from ft. to ft.  Drawdown is amount water level is lowered	Blue Shale	141 142
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Blue Clay with Streaks of -	142 168 23'
Was a pump test made? KI Yes Do If yes, by whom? Valley Pump	White Pumice	168 210
d: 1500 gal/min. with 33 ft. drawdown after 1 hrs.	Blue Clay	TOO \$10
garrante. with j it diawdown after 1 ins.	Brown Clay with Streaks of ~	210 200 221
Air test gal/min, with drill stem at ft. hrs.	Brown Sand	210 222 23'
Bailer test gal/min, with ft. drawdown after hrs.	Blue Clay with Streaks of -	000 001 001
	Black Sand	222 234 23'
perature of water 56 Depth artesian flow encountered	Continued On Another Sheet	~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~
	Work started 6-8 19 81 Complete	ed 7-7 1981
(9) CONSTRUCTION: Special standards: Yes \( \subseteq \) No \( \subseteq \)	Date well drilling machine moved off of well	7-7 1981
Well seal—Material used Cement & 5% Bentonite	Drilling Machine Operator's Certification:	
Well sealed from land surface to	This well was constructed under my direct s	
Diameter of well bore to bottom of seal	and information reported above are true to my b	
Diameter of well bore below sealin.	[Signed] Stephen. A. Aughes.	Date . 1.7, 19
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No	1171
How was coment grout placed? Pumped from bottom of	Water Well Control to the Control	
casing up to the ground surface.	Water Well Contractor's Certification:	cond this new to to
370 - 370 -	This well was drilled under my jurisdiction the best of my knowledge and belief.	and this report is true to
Was pump installed?NO	Name Norm Sevey Well Drilling,	Inc.
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	(Person, firm or corporation)	(Type or print)
Did any strata contain unusable water?	Address 800 Old Midland Rd, Klam	ath Falls, OR 97
Type of Water? depth of strata	[Signed] Konn & luce	
Method of sealing strata off	(Water Well Contract	or)
Was well gravel packed? ☐ Yes ☒ No Size of gravel:	Configurator's License No. 498Date	7-9-81 , 19 81
Gravel placed from ft. to ft.	<u></u>	

11029

NOTICE TO WATER WELL CONTRACTOR.

The original and first copy of this report WAR 1 1 2010 are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion. SP\*12658-690

### WATER WELL REPORT ... STATE OF OREGON

## RECEIVED

JUL 2 1 1981

State Well No. 365/12E-22C

WATER RESOURCES DEPTtate Permit No. SALEM, OREGON (1) OWNER Continued from page 1 (10) LOCATION OF WELL: Name Kenneth Allison County Klamath Driller's well number Address 2028 Reclamation 4 Section 22 т. 36S 4 SW W.M. Klamath Falls. State OR 97601 Tax Lot # Subdivision Address at well location: (2) TYPE OF WORK (check): New Well □ Reconditioning [ Abandon 🗆 (11) WATER LEVEL: Completed well. If abandonment, describe material and procedure in Item 12. Depth at which water was first found (3) TYPE OF WELL: (4) PROPOSED USE (check): Static level ft. below land surface. Date Rotary Air 🛘 Driven Domestic · □ Municipal □ Industrial Artesian pressure lbs. per square inch. Date Dug Irrigation Test Well Other Bored Thermal: Withdrawal Reinjection Diameter of well below casing 12" & 8" (12) WELL LOG: Depth drilled ft. Depth of completed well (5) CASING INSTALLED: Steel Plastic Formation: Describe color, texture, grain size and structure of materials; and show Threaded Welded thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. LINER INSTALLED: MATERIAL From To SWL Blue Clay 234 259 Blue Clay with Streaks of (6) PERFORATIONS: Perforated? Yes No 259 269 Black Sand Type of perforator used 269 Coarse Brown Sand 271 Size of perforations in. by in. Red Shale 271 274 ...... perforations from ...... ft. to ...... ft. 274 Sandy Brown Clay ..... perforations from ..... ft. to ...... ft. 279 285 Red Lava Rock perforations from ...... ft. to..... ft. <u>Black Lava Rock</u> 285 288 23 (7) SCREENS: Well screen installed? ☐ Yes ☐ No 288 Brown Lava Rock 300 23 Manufacturer's Name ..... Brown Sand Rock 300 312 312 Red Lava Rock 390 231 Diam. Slot Size ...... Set from ..... ft. to ..... ft. Brown Lava Rock 390 413 231 Slot Size ........ Set from ...... ft. to ..... ft. Black Lava Rock 413 597 23 Drawdown is amount water level is lowered (8) WELL TESTS: below static level Well is 12" to 373' then s a pump test made? 🗆 Yes 🗀 No If yes, by whom? is 8" from 373' to 597' ft, drawdown after gal./min. with hrs. Air test gal./min. with drill stem at hrs. gal./min. with ft. drawdown after hrs. Bailer test sian flow perature of water Depth artesian flow encountered ...... 19 81 19 81 Work started Completed Date well drilling machine moved off of well 1981 (9) CONSTRUCTION: Special standards: Yes 

No Well seal—Material used Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used Diameter of well bore to bottom of seal .....in Number of sacks of cement used in well seal Drilling Machine Operator's License No. 1171 How was cement grout placed? Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Was pump installed? ...... Type , ......... HP ......... Depth ....... ft. Name Norm Sevey Well Drilling, Inc.
(Person, firm or corporation) (Type or print) Was a drive shoe used? ☐ Yes ☐ No Plugs ..... Size: location ...... ft. 800 Old Midland Rd. Klamath Falls, OR 97601 Did any strata contain unusable water? 

Yes 

No depth of strata Type of Water? Method of sealing strata off Contractor's License No. 408 Date 7-9 , 19.81 Was well gravel packed? 

Yes 

No Size of gravel: .....

Gravel placed from ...... ft. to .....ft.

## STATE OF OREGON WATER WELL REPORT

KLAM 10447

LEF-e--Levidus

365/12E/28aa

(as required by ORS 53	37,765)	IVIAT	- 0 100m. (S	TARĮ CARD) #				
(1) OWNER: Name Terry L. H	Well Nu	mber: 2	(9) LOCATION	OF WELL by le	gal de	escript	tion:	, .
Address P. O. Box 8			County	Latitude1	2 F	Longitud	le	
City Beatty		Zip 97621	County Klama Township 36 Section 28	N.or S, Range 1	NE		_E or W.	WM.
(2) TYPE OF WOR		-	Tay Lat 100	Lot Block	,	Subd	linicion	
New Well Deeper		Abandon	Street Address of W	ell (or nearest address) M Beatty, OR	P 39	нід	nway	
(3) DRILL METHO		;,						
Rotary Air Rotar			(10) STATIC W	ATÉR LEVEL: below land surface. =	:	Date	4, 1, 9	92
(4) PROPOSED US	SE:		1	lb. per squ	are inch.	Date		
	unity Industrial <b>X</b> Irri		(11) WATER B	EARING ZONE	S:			
(5) BORE HOLE C			Depth at which water was	first found40 _£	t			
Special Construction approval	Yes No Depth of Comp	leted Well 267 ft.	From	To		nated Flow		SWL
Yes No	Yes No Depth of Comp		40	75		0 gp		26
Explosives used $\Box$	Type Amount		79	182		Ø gp		26
HOLE Diameter From To	SEAL Material From To	Amount sacks or pounds	182	267	200	Ø gp	m	23
16   0 180 C	Material From To Cement& 0 18	103sks						
	Bent.	1/2 sk	(12) WELL LO	G: Ground elevati	on <u>42</u>	50		-
10 180 267				Material		From	To	swL
			Sandy Top S	Soil		Ø	1	
How was seal placed: Method	□ A □ B 🙀 C □ D	E		ravel & Pum	ice	1	9	
Other			White Pumi	ce		9	56	26
-	ft. to ft. Material					56_	65	
	ft. to ftSize of grayel			ce		65_		26
(6) CASING/LÎNE		Welded Threaded		<u>y</u>		75	79	
Casing: 12 1 1	To Gauge Steel Plastic	₩eided Inreaded	White Pumic	stone		79 82	82 182	26 26
				vn Lava Roc	k	182	205	
			Broken Blac			205	267	1
Liner:								
Final location of shoe(s) _ NO								
(7) PERFORATIO								
Perforations	Method	35			DE	^F!	(F)	
	Type Materi							
Slot	Tele/pipe				E S A	0 1 1	חזקל	
From To size	Number Diameter size	Casing Liner			N.4	711	2010	
	-			\WA	क्षार है	FRGH0	CES DE	DT
				VV		M. OF		<u>er" I</u>
				e e e	- C/344	121, V/3".	CON	
			Date started 4-1-9	2 Com	pleted 4	-7-9	2	
			(unbonded) Water V					
(8) WELL TESTS:	Minimum testing time is	s 1 hour Flowing	I certify that the	e work I performed o	n the co	nstructi		
Pump 🗆 Ba	iler 🗆 Air	Artesian	abandonment of this standards. Materials u					
Yield gal/min Drawd	lown Drill stem at	Time	knowledge and belief.		•			5
1700	130'	1 hr.	Signed Tonlan	4 R Hughe	W n	WC Nu late 4	mber	2
			3 57			<u> </u>		
			(bonded) Water Well I accept responsi	I Constructor Certi: bility for the construc			or aband	donment
Temperature of water 51 F	Depth Artesian Flo	w round	work performed on the	is well during the cons	struction	dates re	ported a	bove. all
Was a water analysis done?  Did any strata contain water no	ot suitable for intended use?	Too little	work performed duri construction standard					
	or Colored Cother		belief.	011			mber 77	_
Depth of strata:			Signed Stepl	ren K. Hugh	ne D	ate	4-16	-92
	WATER RESOURCES DEPART	MENT SECO	ND COPY - CONSTRUCTO	OR THIRD CO	PY - CUS	TOMER		98\& D4086

#### WELL TEST REPORT

Location of Well	85 Bec	of Hagers	place Bea	tty. Oregon
Inside Diameter .	12"		Depth	
Feet	of	Inch Casing.	Driller	Sevey Well Drilling
130 Feet	of 10	Inch Column c	and 3	. Stage 12 Inch Bowls.
Test Done By	Lee C	ampbell	· ·	
			7-1	and the street of the state of
	87 Ft.	DRAWDOWN	12:00PM	Clear
1700	130 Ft.		1:00BM	
	125 Ft.   105 Ft.		2:00PM 3:00PM	
1400	89 Ft.		3130PM	
1100	81 Ft.		4100FM	
	•		), the ma	tal Test
			4 111. 10	
				数据
				RECEIVE
				Tage V
			.,.	MAR 1 1 20
			$\hat{A}$	WATER RESOURCE
			1. [	SALEM, ORSO
		, •		TEMPERATURE
Static Water Level A	After Rump Test			
·				
VEWITIND;	***************************************			The Field to the first of the f
	*************************			The state of the s
REMARKS:				