

**WATER WELL REPORT
STATE OF OREGON**

#5 should be 10"

7393
MARI-MARI

RECEIVED

JUN 21 2007

State Well No. 752w-20ad

State Permit No. 2253

WATER RESOURCES DEPT
SALEM, OREGON

(1) OWNER:

Name Dan Stauffer
Address 1660 Hamdon Lane N.E.
City Salem Oregon State Or.

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Air Driven Domestic Industrial Municipal
Rotary Mud Dig Irrigation Test Well Other
Cable Bored Thermal Withdrawal Reinjection

(4) PROPOSED USE (check):

CASING INSTALLED: Steel Plastic
Threaded Welded
" Diam. from +1 ft. to 1.75 ft. Gauge 2.50
" Diam. from ft. to ft. Gauge

LINER INSTALLED:

(6) PERFORATIONS:

Perforated? Yes No
Type of perforator used Perf Hawk
Size of perforations 3/8 in. by 1 1/2 in.
3521 perforations from 1.00 ft. to 1.55 ft.
1326 perforations from 1.55 ft. to 1.73 ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot Size Set from ft. to ft.
Diam. Slot Size Set from ft. to ft.

WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
old: gal./min. with ft. drawdown after hrs.
"
test 400 gal./min. with drill stem at 175 ft. 2 1/2 hrs.
pump test gal./min. with ft. drawdown after hrs.
testian flow g.p.m.
temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Special standards: Yes No
Well seal—Material used Cement
Well sealed from land surface to 26 ft.
Diameter of well bore to bottom of seal 1.5 in.
Diameter of well bore below seal 1.0 in.
Number of sacks of cement used in well seal 23 sacks
How was cement grout placed? Pressure
.....
Was pump installed? No Yes Type HP Depth ft.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of Water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Marion Driller's well number S-1
SE 1/4 NE 1/4 Section 20 T. 7S R. 2W W.M.
Tax Lot # Lot Blk Subdivision
Address at well location: 1660 Hamdon Lane

(11) WATER LEVEL: Completed well.

Depth at which water was first found 49 ft.
Static level 26 ft. below land surface. Date 10-3-80
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 10
Depth drilled 177 ft. Depth of completed well 177 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Soil brn	0	2	
Clay med brn	2	26	
Clay med grey	26	44	
Sand blk gravel med brn	44	62	
Clay med blue	62	73	
Gravel med-lge sand brn	73	160	
Gravel lge lite sand br	160	177	

RECORDED

OCT 13 1980

WATER RESOURCES DEPT
SALEM, OREGON

Work started 9-29-80 19 Completed 10-3 19 80
Date well drilling machine moved off of well 10-3 19 80

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
(Signed) Byron B. Stadel Date 10-9, 1980.
(Drilling Machine Operator)

Drilling Machine Operator's License No. 1371

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name West Coast Drilling Co. Inc.
(Person, firm or corporation) (Type or print)
Address 220 Academy St. Mt. Angel Or.

(Signed) Charles E. Stadel
(Water Well Contractor)

Contractor's License No. 519 Date 10-9, 1980

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

SP-12655-000

WELL FOR G-10248