

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

RECEIVED WATER WELL REPORT JUL 17 1967 STATE OF OREGON (Please type or print) STATE ENGINEER SALEM, OREGON

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

KLAM 436

State Well No. 24/9-30 State Permit No.

(1) OWNER:

Name CRESCENT WATER ASSOC. Address P.O. BOX 123 CRESCENT ORE

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven [] Cable [X] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [X] Irrigation [] Test Well [] Other []

CASING INSTALLED:

10" Diam. from 0 ft. to 110 ft. Gage 250

PERFORATIONS:

Perforated? [] Yes [X] No

Type of perforator used

Table with columns: Size of perforations, in. by, in. Rows for perforations from 0 to 110 ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No

Manufacturer's Name, Type, Model No., Diam., Slot size, Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 312 ft. below land surface Date 5/15/67

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [X] Yes [] No If yes, by whom? Klamath Falls Pump Yield: 350 gal./min. with 20 ft. drawdown after 24 hrs.

Ball test 20 gal./min. with 20 ft. drawdown after 4 hrs.

Artesian flow g.p.m. Date

Temperature of water 43 Was a chemical analysis made? [X] Yes [] No

(10) CONSTRUCTION:

Well seal—Material used BENTONITE & CEMENT

Depth of seal 43 ft.

Diameter of well bore to bottom of seal 14 in.

Were any loose strata cemented off? [X] Yes [] No Depth 120 to 140

Was a drive shoe used? [X] Yes [] No

Did any strata contain unusable water? [] Yes [X] No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? [] Yes [X] No Size of gravel:

Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County KLAMOTH Driller's well number 1/4 Section 20 T. 24S R. 9 E.W.M.

Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 10 in.

Depth drilled 334 ft. Depth of completed well 334 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows: Volcanic ash & gumise, Grey Basalt Boulders, Black Cinders, Red Cinders & Broken Rock, Grey Basalt Rock, Broken grey Rock, Grey Basalt Rock, Brown Rock, Brown Rock with Crayons, Black Cinder Rock.

RECEIVED

JUL 20 2007

WATER RESOURCES DEPT SALEM, OREGON

Work started 1/14 1966 Completed 6/10 1967

Date well drilling machine moved off of well 6/14 1967

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] KENNETH MATHERS Date 7/11, 1967 (Drilling Machine Operator)

Drilling Machine Operator's License No. 245

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME MATHERS & SON (Person, firm or corporation) (Type or print)

Address P.O. Box 288 BEND OREGON

[Signed] Kenneth Mathers (Water Well Contractor)

Contractor's License No. 263 Date 7/11, 1967

RECEIVED OVER THE COUNTER

(USE ADDITIONAL SHEETS IF NECESSARY)