# Water Right Conditions Tracking Slip

Groundwater/Hydrology Section

FIIF## 6-17560
FILE # # 6-17560 ROUTED TO: Water Rights
TOWNSHIP/ RANGE-SECTION: 125/5W-12
CONDITIONS ATTACHED?: [4] yes [] no
REMARKS OR FURTHER INSTRUCTIONS:
Reviewer: J. Hackett

# WATER RESOURCES DEPARTMENT

MEM	10							Ju	ly 3	<u>l</u> ,	200/12	
TO:			cation (									
FRO	M:	GW: J. Hackett (Reviewer's Name)										
SUBJ	ECT:				terfere		luation					
	_YES _NO YES	The so	ource of	approp	riation i	s within	or abo	ve a Sce	nic Wa	terway		
	_11.0	Use th	e Sceni	c Water	way cor	ndition (	Conditi	on 7J)				
	interfe calcula Per OI interfe the De that th	rence wated into	with surferences 835, the with surferent is unable.	ace wat e is dist Ground ace wat nable to e will n	er that c ributed d Water er that c o find the	ontribut below. Section ontribut at ther bly red	is unal tes to a s e is a pruce the	Scenic V ble to ca scenic w reponde surface	ulate growante waterwayerance of water water water water mic water	ground y; there of evide flows	water	
Calcula calcula informin Exerci Watery	ted, per cong Water se of the	rcentage in riteria in Rights the is permited the follower.	of consum 390.835, at the De t is calc owing an	nptive use do not fit partment ulated t mounts	e by mont. Il in the to is unable o reduce	able but c to make e month	heck the a Prepon ly flows	"unable" derance o s in	If interfe option a of Eviden e consu	bove, thu ce finding	s g. Scenic	
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	

# PUBLIC INTEREST REVIEW FOR GROUND WATER APPLICATIONS

TO:		Wate	r Rights S	ection			DateJuly 31, 2012						
FROM	:	Grou	nd Water/	Hydrology	Section _	J. Hacl				_			
OAR 69 welfare,	IC INTI 90-310-1 safety at	ERES' 30 (1) nd heal	F PRESU The Depart th as descr	ibed in ORS	GROUN resume that 537.525. D	Sup  DWATE  t a proposit  Department	<b>R</b> ed ground staff revie	water use will ew ground water the proposed	ensure the	ons under OA	of the pub AR 690-31	0-140	
								id agency poli					
<b>A.</b> <u>GE</u> I	N <u>ERAL</u>	INFO	<u> PRMATIO</u>	<u>ON</u> : A	pplicant's N	lame:	WK&K L	Land, Ltd.		_ County:_	Benton		
A1.	Applica	ınt(s) se	eek(s) <u>0.7</u>		n <u>l</u>			Willamette Quad Map: <u>Ri</u>					
A2. A3.	Propose Well an	ed use_ id aquif	Ind er data (att	ustrial		Seas	sonality: _	Year-Roun	d				
Well	Logid Applicant's Well #		Propos	Proposed Aquifer*		osed (cfs)	Location (T/R-S QQ 12S/5W-12 SE	-Q)	Location, metes and bound 2250' N, 1200' E fr NW co 1400'E fr SW cor S 12		cor S 36		
3 4					-								
5 * Alluviu	ım, CRB,	Bedroc	k										
Well	Well Elev ft msl 218	First Water ft bls 22	ft ble	SWL Date 8/23/1991	Well Depth (ft) 35	Scal Interval (ft) 0-18	Casing Intervals (ft) +1 to 33	Liner Intervals (ft)	Perforation Or Scree (ft) 22.5-33.	ns Yield (gpm)	Draw Down (fi)	Test Type B	
	Commo		for proposed	d wells.									
A5. ⊠	manage (Not all Comme	ment o basin ents: <u>T</u>	rules contai ne applican	ater hydrauli in such provi	sions.) luces from a	an unconfi	rface water ned aquife	rules relative t r ☑ are, or ☐ r and is located	are not, a	activated by t	his applica	ation.	
A6. 🗌	Name o	of admi	nistrative a	rea:				tap(s) an aquif					

Version: 08/15/2003

Date: July 31, 2012 Page 2

# B. GROUND WATER AVAILABILITY CONSIDERATIONS, OAR 690-310-130, 400-010, 410-0070

	ed upon available data, I have determined that ground water* for the proposed use:	
a.	is over appropriated, ⊠ is not over appropriated, or □ cannot be determined to be period of the proposed use. * This finding is limited to the ground water portion of the determination as prescribed in OAR 690-310-130;	
b.	<b>will not</b> or <b>□</b> will likely be available in the amounts requested without injury to prior is limited to the ground water portion of the injury determination as prescribed in OAR	
c.	will not or will likely to be available within the capacity of the ground water reso	urce; or
d.	will, if properly conditioned, avoid injury to existing ground water rights or to the grain.  The permit should contain condition #(s) _7B,7C  ii The permit should be conditioned as indicated in item 2 below.  The permit should contain special condition(s) as indicated in item 3 below;	round water resource:
a.	Condition to allow ground water production from no deeper than	ft. below land surface;
b.	Condition to allow ground water production from no shallower than	ft. below land surface;
c.	Condition to allow ground water production only from the water reservoir between approximately ft. and ft. below land	ground
	water reservoir between approximately it. and it. below faile	i surface,
Cw		
GIC	und water availability remarks:	
The	applicant's well is completed in Holocene floodplain deposits of the Willamette River. The regrained and highly permeable. Locally, the floodplain deposits are 20-30 feet thick. Apperained alluvial sediments underlies the floodplain sediments.	ese deposits are generally
The	applicant's well is completed in Holocene floodplain deposits of the Willamette River. The grained and highly permeable. Locally, the floodplain deposits are 20-30 feet thick. App	ese deposits are generally
The	applicant's well is completed in Holocene floodplain deposits of the Willamette River. The grained and highly permeable. Locally, the floodplain deposits are 20-30 feet thick. App	ese deposits are generally
The	applicant's well is completed in Holocene floodplain deposits of the Willamette River. The grained and highly permeable. Locally, the floodplain deposits are 20-30 feet thick. App	ese deposits are generally
The	applicant's well is completed in Holocene floodplain deposits of the Willamette River. The grained and highly permeable. Locally, the floodplain deposits are 20-30 feet thick. App	ese deposits are generally
The	applicant's well is completed in Holocene floodplain deposits of the Willamette River. The grained and highly permeable. Locally, the floodplain deposits are 20-30 feet thick. App	ese deposits are generally
The	applicant's well is completed in Holocene floodplain deposits of the Willamette River. The grained and highly permeable. Locally, the floodplain deposits are 20-30 feet thick. App	ese deposits are generally
The	applicant's well is completed in Holocene floodplain deposits of the Willamette River. The grained and highly permeable. Locally, the floodplain deposits are 20-30 feet thick. App	ese deposits are generally

#### C. GROUND WATER/SURFACE WATER CONSIDERATIONS, OAR 690-09-040

C1. **690-09-040 (1):** Evaluation of aquifer confinement:

Well	Aquifer or Proposed Aquifer	Confined	Unconfined
1	alluvium		
	or aquifer confinement evaluation: The applicant's well produce on fining units.	ces from coarse-grained sec	diments that are not overlain

C2. **690-09-040 (2) (3):** Evaluation of distance to, and hydraulic connection with, surface water sources. All wells located a horizontal distance less than ¼ mile from a surface water source that produce water from an unconfined aquifer shall be assumed to be hydraulically connected to the surface water source. Include in this table any streams located beyond one mile that are evaluated for PSI.

Well	SW #	Surface Water Name	GW Elev ft msl	SW Elev ft msl	Distance (ft)	Hydraulically Connected? YES NO ASSUMED	Potential for Subst. Interfer. Assumed? YES NO
1	1	Willamette River	200	200	1000		
1	2	East Channel Willamette River	200	200	4700		
					_		

Basis for aquifer hydraulic connection evaluation: Water levels in the alluvial aquifer are coincident with the elevations of
nearby stream reaches. This indicates a hydraulic connection between the groundwater and surface water systems.

Water Availability Basin the well(s) are located within: 30200321: WILLAMETTE R > COLUMBIA R - AB PERIWINKLE CR AT GAGE 14174

C3a. 690-09-040 (4): Evaluation of stream impacts for each well that has been determined or assumed to be hydraulically connected and less than 1 mile from a surface water source. Limit evaluation to instream rights and minimum stream flows that are pertinent to that surface water source, and not lower SW sources to which the stream under evaluation is tributary. Compare the requested rate against the 1% of 80% natural flow for the pertinent Water Availability Basin (WAB). If Q is not distributed by well, use full rate for each well. Any checked box indicates the well is assumed to have the potential to cause PSI.

Well	SW #	Well < ½ mile?	Qw > 5 cfs?	Instream Water Right ID	Instream Water Right Q (cfs)	Qw > 1% ISWR?	80% Natural Flow (cfs)	Qw > 1% of 80% Natural Flow?	Interference @ 30 days (%)	Potential for Subst. Interfer. Assumed?
1	1	$\boxtimes$		MF184A	1750		2540		>25%	<u> </u>
1	2			N/A			2540		<25%	
				_						

Version: 08/15/2003

Date: July 31, 2012

C3b. 690-09-040 (4): Evaluation of stream impacts by total appropriation for all wells determined or assumed to be hydraulically connected and less than 1 mile from a surface water source. Complete only if Q is distributed among wells. Otherwise same evaluation and limitations apply as in C3a above.

C variation at	a minitations	appij as	<u> </u>	<u> </u>					
SW #		Qw > 5 cfs?	Instream Water Right ID	Instream Water Right Q (cfs)	Qw > 1% ISWR?	80% Natural Flow (cfs)	Qw > 1% of 80% Natural Flow?	Interference @ 30 days (%)	Potential for Subst. Interfer. Assumed?

Comments: Modeling in similar circumstances suggests that due to the proximity of the applicant's well to the Willamette River, and because the well produces from a highly permeable aquifer, pumping impacts to the Willamette River will be > 25% of the pumping rate after 30 days of pumping.

Modeling in similar circumstances also suggests that because the East Channel of the Willamette River is likely to contain some fine-grained sediments, pumping impacts to it will be < 25% of the pumping rate after 30 days of pumping.

C4a. 690-09-040 (5): Estimated impacts on hydraulically connected surface water sources greater than one mile as a percentage of the proposed pumping rate. Limit evaluation to the effects that will occur up to one year after pumping begins. This table encompasses the considerations required by 09-040 (5)(a), (b), (c) and (d), which are not included on this form. Use additional sheets if calculated flows from more than one WAB are required.

Non-Di	stributed	Wells											
Well	SW#	Jan	Feb	Mar_	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
		%	%	%	%	%	%	%	%	%	%	%	9/
Well Q	as CFS												
Interfere	ence CFS												
Distrib	uted Well	<u> </u>											
Well	SW#	Jan	Feb	Mar	Apr	May	Jun	<u>Ju</u> l	Aug	Sep	Oct	Nov	Dec
		%	-%	%	%	%	%	-%	%	%	%	%	9/
Well Q	as CFS												
Interfere	ence CFS												
		%	%	%	%	%	%	%	%	%	%	%	9/
Well Q	as CFS												
Interfere	ence CFS												
		%	%	%	%	%	%	%	%	%	%	%	9/
Well Q	as CFS												
Interfere	enee CFS			_									
		%	%	%	%	%	%	%	%	%	%	%	9/
Well Q	as CFS												
Interfere	ence CFS									_			
		%	%	%	%	%	%	<del>%</del>	%	%	%	%	9,
Well Q	as CFS			_									
Interfere	ence CFS												
		%	%	%	%	%	%	%	%	%	%	%	9/
Well Q	as CFS												
Interfere	ence CFS									_			
										_			
	tal Interf.		_	_									
(B) = 80	% Nat. Q					_							
(C) = 1	% Nat. Q												

Application G-17560 Date: July 31, 2012 Page 5

(E) = (A / B) x 100 % % % % % % % % % % % % % % % % % %	
CFS; (D) = highlight the checkmark for each month where (A) is greater than (C); (E) = total interference divided by 80% flow as perc	
	mtage.
C4b. 690-09-040 (5) (b) The potential to impair or detrimentally affect the public interest is to be determined by Rights Section.	the Water
Rights Section.	
OF The second conditions of the conference of th	
C5. If properly conditioned, the surface water source(s) can be adequately protected from interference, and/or ground under this permit can be regulated if it is found to substantially interfere with surface water:	water use
i. The permit should contain condition #(s)	;
ii. The permit should contain special condition(s) as indicated in "Remarks" below;	
C6. SW / GW Remarks and Conditions	
	_
References Used:	
References Used:	
References Used:  Conlon, T.D., Wozniak, K.C., Woodcock, D., Herrera, N.B., Fisher, B.J., Morgan, D.S., Lee, K.K., and Hinkle, S.R., Ground-water hydrology of the Willamette Basin, Oregon: U.S. Geological Survey Scientific Investigations Report 20	005, 05-5168.
Conlon, T.D., Wozniak, K.C., Woodcock, D., Herrera, N.B., Fisher, B.J., Morgan, D.S., Lee, K.K., and Hinkle, S.R.,	005 <u>,</u> 05-5168.
Conlon, T.D., Wozniak, K.C., Woodcock, D., Herrera, N.B., Fisher, B.J., Morgan, D.S., Lee, K.K., and Hinkle, S.R., Ground-water hydrology of the Willamette Basin, Oregon: U.S. Geological Survey Scientific Investigations Report 20 Gannett, M. W. and Caldwell, R.R., 1998, Geologic framework of the Willamette lowland aquifer system, Oregon and	05-5168. fer system,

Version: 08/15/2003

Application G-17560

6

Date: July 31, 2012

D	WEIT	CONSTRUCTION.	OAR 690-200

D1.	Well #:	Logid:
D2.	a.	VELL does not meet current well construction standards based upon:  review of the well log; field inspection by
D3.	a.	permits the loss of artesian head;
D4.	THE W	VELL construction deficiency is described as follows:
D5. D6.		WELL  a. was, or was not constructed according to the standards in effect at the time of original construction or most recent modification.  b. I don't know if it met standards at the time of construction.  to the Enforcement Section. I recommend withholding issuance of the permit until evidence of well reconstruction with the Department and approved by the Enforcement Section and the Ground Water Section.
THI	S SECTION	ON TO BE COMPLETED BY ENFORCEMENT PERSONNEL
D7.		onstruction deficiency has been corrected by the following actions:
		(Enforcement Section Signature), 200
D8.	☐ Route	to Water Rights Section (attach well reconstruction logs to this page).

#### Water Availability Tables

# WILLAMETTE R > COLUMBIA R - AB PERIWINKLE CR AT GAGE 14174 WILLAMETTE BASIN

Water Availability as of 7/31/2012

Watershed ID #: 30200321

Date: 7/31/2012

Exceedance Level:

Time: 2:10 PM

#### Water Availability Calculation

Monthly Streamflows in Cubic Feet per Second Storage at 50% Exceedance in Acre-Feet

Month	Natural Stream Flow	Consumptive Uses and Storages	Expected Stream Flow	Reserved Stream Flow	Instream Flow Requirement	Net Water Available
JAN	10,100.00	1,330.00	8,770.00	0.00	1,750.00	7,020.00
FEB	11,600.00	4,240.00	7,360.00	0.00	1,750.00	5,610.00
MAR	11,000.00	4,520.00	6,480.00	0.00	1,750.00	4,730.00
APR	9,760.00	4,220.00	5,540.00	0.00	1,750.00	3,790.00
MAY	8,430.00	2,490.00	5,940.00	0.00	1,750.00	4,190.00
JUN	5,360.00	790.00	4,570.00	0.00	1,750.00	2,820.00
JUL	3,270.00	592.00	2,680.00	0.00	1,750.00	928.00
AUG	2,560.00	540.00	2,020.00	0.00	1,750.00	270.00
SEP	2,540.00	460.00	2,080.00	0.00	1,750.00	330.00
OCT	2,860.00	230.00	2,630.00	0.00	1,750.00	880.00
NOV	4,170.00	314.00	3,860.00	0.00	1,750.00	2,110.00
DEC	8,150.00	336.00	7,810.00	0.00	1,750.00	6,060.00
ANN	7,460,000.00	1,200,000.00	6,260,000.00	0.00	1,270,000.00	5,000,000.00

### Detailed Report of Instream Flow Requirements

Instream Flow Requirements in Cubic Feet per Second

Application #	Status	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
MF184A	APPLICATIO N	1,750.00	1,750.00	1,750.00	1,750.00	1,750.00	1,750.00	1,750.00	1,750.00	1,750.00	1,750.00	1,750.00	1,750.00
Maximum	45 / 50	1,750.00	1,750.00	1,750.00	1,750.00	1,750.00	1,750.00	1,750.00	1,750.00	1,750.00	1,750.00	1,750.00	1,750.00

Date: July 31, 2012

