

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

State Well No.

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

(Do not write above this line)

State Permit No.

(1) OWNER:

Name George Hoffman
Address Prine, Oregon

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven []
Cable [x] Jetted []
Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal []
Irrigation [x] Test Well [] Other []

(5) CASING INSTALLED:

8" Diam. from 0 ft. to 140 ft. Gage 290
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? [] Yes [x] No

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [x] Yes [] No If yes, by whom? SELF

Yield: 200 gal./min. with 50 ft. drawdown after 3 hrs.

Baller test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m.

Temperature of water 52 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used CEMENT

Well sealed from land surface to 20 ft.

Diameter of well bore to bottom of seal 10 in.

Diameter of well bore below seal 8 in.

Number of sacks of cement used in well seal 8 sacks

Number of sacks of bentonite used in well seal sacks

Brand name of bentonite

Number of pounds of bentonite per 100 gallons

of water lbs./100 gals.

Was a drive shoe used? [x] Yes [] No Plugs Size: location ft.

Did any strata contain unusable water? [] Yes [x] No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? [] Yes [x] No Size of gravel

Gravel placed from ft. to

(10) LOCATION OF WELL:

County Harney Driller's well number
W 1/4 NE 1/4 Section 74 T. 26S.R. 31E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 30 ft.
Static level 22.5 ft. below land surface. Date 8/13/76
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8"
Depth drilled 180 ft. Depth of completed well 150 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include Top Soil, Clay - yellow, Fine sand, Clay and silt, Clay - blue, Clay - brown, Coarse sand and gravel.

RECEIVED

AUG 20 2006

WATER RESOURCES DEPT SALEM, OREGON

Work started 4/13 1976 Completed 6/11 1976
Date well drilling machine moved off of well 6/11 1976

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] John D. Rossberg Date 8/23, 1976
(Drilling Machine Operator)

Drilling Machine Operator's License No. 269

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Rossberg, Son (Person, firm or corporation) (Type or print)

Address CRANE DRIVE

[Signed] John D. Rossberg (Water Well Contractor)

Contractor's License No. 272 Date 8/23, 1976

RECEIVED

SEP 14 2006

WATER RESOURCES DEPT SALEM, OREGON