# WATER RESOURCES DEPARTMENT **MEMO** Application G- 17630 TO: FROM: SUBJECT: Scenic Waterway Interference Evaluation The source of appropriation is within or above a Scenic Waterway NO YES Use the Scenic Waterway condition (Condition 7J) NO Per ORS 390.835, the Ground Water Section is able to calculate ground water interference with surface water that contributes to a Scenic Waterway. The calculated interference is distributed below. Per ORS 390.835, the Ground Water Section is unable to calculate ground water interference with surface water that contributes to a scenic waterway; therefore, the Department is unable to find that there is a preponderance of evidence that the proposed use will measurably reduce the surface water flows necessary to maintain the free-flowing character of a scenic waterway. DISTRIBUTION OF INTERFERENCE Calculate the percentage of consumptive use by month and fill in the table below. If interference cannot be

calculated, per criteria in 390.835, do not fill in the table but check the "unable" option above, thus informing Water Rights that the Department is unable to make a Preponderance of Evidence finding.

Exercise of this permit is calculated to reduce monthly flows in Waterway by the following amounts expressed as a proportion of the consumptive use by which surface water flow is reduced.

Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov ·	Dec
						9					

### PUBLIC INTEREST REVIEW FOR GROUNDWATER APPLICATIONS

TO:	Water Rights Section						Date <u>July 30, 2013</u>						
FROM		Grou	ındwater S	Section		J. Hac	kett						
I KOWI	•	Orot	mawater 5								1000		
SUBJE	CT:	Appl	ication G-	17630		Su	persedes	review of					
						,	•	review of			Date of Re	iew(s)	
OAR 69 welfare, to determ the pres	90-310-1 safety as mine who umption	30 (1) nd hea ether th	The Depart Ith as descr ne presumpt a. This revi	ribed in ORS tion is establi ew is based	resume that 537.525. D shed. OAR upon avail	a propose epartment 690-310- able infor	ed ground staff revi 140 allow mation a	water use will ew ground wat s the proposed nd agency policervative Baptic	er applications use be mo	tions undified ace at	under OA l or condi the time	R 690-3 tioned to	10-140 meet
A1.													Racin
AI.	Аррпса	111(5) 5	cck(s) <u>0.4</u>	CIS HOI		well(s) in the <u>Willamette</u> B							
						subbasin Quad Map: Sweet Home							
A2. A3.								March 1 – nark proposed					
Well	Logic	i	Applicant Well #	's Propose	ed Aquifer*	Proposed Rate(cfs)			Location (T/R-S QQ-Q)		Location, metes and bounds, 2250' N, 1200' E fr NW cor S		
1	LINN 12	125	1	В	Bedrock		0.4		13S/IE-2 SE-NE		385'N, 595'W fr E1/4 cor S 2		
2	LINN 55	655	2	В	edrock	0.4		13S/1E-2 SE	-NE	1370'N, 195'W fr E1/4 cor S 2			or S 2
3 4													
5													
* Alluviı	ım, CRB,	Bedroc	k										
Well	Well Elev	First Wate	<sub>r</sub> SWL	SWL	Well Depth	Seal Interval	Casing Intervals	Liner	Perforat Or Scre		Well Yield	Draw Down	Test
	ft msl	ft bls	l ft ble	Date	(ft)	(ft)	(ft)	(ft)	(ft)		(gpm)	(ft)	Туре
2	1700 1750	70 80	71	08/28/2003	285 660	0-28	0-119 +1-159	0-285	60-28 80-13		35 40	26	P P
	1750	80	14	08/21/2003	600	0-60	+1-139	_	80-13	3	40		P
Use data	from app	lication	for proposed	d wells.									
A4.	Comme	ents:											
A5. 🛚	Provisions of the Willamette  Basin rules relative to the development, classification and/or management of ground water hydraulically connected to surface water are, or are not, activated by this application. (Not all basin rules contain such provisions.)  Comments: The applicant's wells are not located within 1/4 mile of the nearest surface water source, so the pertinent basin rules do not apply.												
A6. 🗌	Name o	f admi	nistrative a	rea:				tap(s) an aquif		_	_		

### B. GROUND WATER AVAILABILITY CONSIDERATIONS, OAR 690-310-130, 400-010, 410-0070

B1. Based upon available data, I have determined that ground water* for the proposed use:									
	a.	is over appropriated, is not over appropriated, or is cannot be determined to be over appropriated during any period of the proposed use. * This finding is limited to the ground water portion of the over-appropriation determination as prescribed in OAR 690-310-130;							
	b.	will not or will likely be available in the amounts requested without injury to prior water rights. * This finding is limited to the ground water portion of the injury determination as prescribed in OAR 690-310-130;							
	c.	will not or will likely to be available within the capacity of the ground water resource; or							
	d.	will, if properly conditioned, avoid injury to existing ground water rights or to the ground water resource:  i. The permit should contain condition #(s) 7B, 7C  ii. The permit should be conditioned as indicated in item 2 below.  iii. The permit should contain special condition(s) as indicated in item 3 below;							
B2.	a.	Condition to allow ground water production from no deeper than ft. below land surface;							
	b.	Condition to allow ground water production from no shallower than ft. below land surface;							
	c.	Condition to allow ground water production only from the ground water reservoir between approximately ft. and ft. below land surface;							
	d.	<ul> <li>Well reconstruction is necessary to accomplish one or more of the above conditions. The problems that are likely to occur with this use and without reconstructing are cited below. Without reconstruction, I recommend withholding issuance of the permit until evidence of well reconstruction is filed with the Department and approved by the Ground Water Section.</li> <li>Describe injury —as related to water availability—that is likely to occur without well reconstruction (interference w/ senior water rights, not within the capacity of the resource, etc):</li> </ul>							
В3.	Gro	ound water availability remarks:							
	rock	e applicant's wells are located in an area that contains several hundred feet of low-yield Early Western Cascades volcanic ks. The applicant's wells produce water from fractures within these low-yield volcanic rocks. The low-yield aquifer tem is characterized by large amounts of drawdown and production rates typically less than 50 gpm.							
		water-level data is available to assess the stability of the groundwater system. This suggests the need for long-term nitoring.							
	_								
	-								
	-								

#### C. GROUND WATER/SURFACE WATER CONSIDERATIONS, OAR 690-09-040

C1. 690-09-040 (1): Evaluation of aquifer confinement:

Well	Aquifer or Proposed Aquifer	Confined	Unconfined
1	Low-yield bedrock (Western Cascades volcanics)	$\boxtimes$	
2	Low-yield bedrock (Western Cascades volcanics)		

Basis for aquifer confinement evaluation: Water levels in nearby wells are above the level of water-bearing zones. This suggests the aquifer is confined which is consistent with general knowledge about the low-yield bedrock aquifer system.

C2. **690-09-040** (2) (3): Evaluation of distance to, and hydraulic connection with, surface water sources. All wells located a horizontal distance less than ¼ mile from a surface water source that produce water from an unconfined aquifer shall be assumed to be hydraulically connected to the surface water source. Include in this table any streams located beyond one mile that are evaluated for PSI.

Well	SW #	Surface Water Name	GW Elev ft msl	SW Elev ft msl	Distance (ft)	Hydraulically Connected? YES NO ASSUMED	Potentia Subst. Int Assum YES	terfer.
1	1	Cedar Creek	1630	2080- 1180	2050			×
2	1	Cedar Creek	1630	2080- 1180	1375			
1	. 2	Fall Creek	1670	1840- 1360	3300			⊠
2	2	Fall Creek	1670	1840- 1360	4050			⊠
					_			
								$\dashv$

Basis for aquifer hydraulic connection evaluation: Water level elevations in the applicant's wells are above the elevations of local reaches of Cedar and Fall Creeks. This indicates groundwater flows toward local streams and suggests hydraulic connection.

Water Availability Basin the well(s) are located within: 123: MCDOWELL CR > S SANTIAM R - AT MOUTH

C3a. 690-09-040 (4): Evaluation of stream impacts for each well that has been determined or assumed to be hydraulically connected and less than 1 mile from a surface water source. Limit evaluation to instream rights and minimum stream flows that are pertinent to that surface water source, and not lower SW sources to which the stream under evaluation is tributary. Compare the requested rate against the 1% of 80% natural flow for the pertinent Water Availability Basin (WAB). If Q is not distributed by well, use full rate for each well. Any checked box indicates the well is assumed to have the potential to cause PSI.

Well	SW #	Well < 1/4 mile?	Qw > 5 cfs?	Instream Water Right ID	Instream Water Right Q (cfs)	Qw > 1% ISWR?	80% Natural Flow (cfs)	Qw > 1% of 80% Natural Flow?	Interference @ 30 days (%)	Potential for Subst. Interfer. Assumed?
1	1			n/a	n/a		4.87	$\square$	<25%	$\boxtimes$
2	1			n/a	n/a		4.87	$\square$	<25%	$\boxtimes$
1	2			n/a	n/a		4.87	$\boxtimes$	<25%	
2	2			n/a	n/a		4.87	$\boxtimes$	<25%	$\boxtimes$
									-	

C3b. 690-09-040 (4): Evaluation of stream impacts by total appropriation for all wells determined or assumed to be hydraulically connected and less than 1 mile from a surface water source. Complete only if Q is distributed among wells. Otherwise same evaluation and limitations apply as in C3a above.

SW #	Qw > 5 cfs?	Instream Water Right ID	Instream Water Right Q (cfs)	Qw > 1% ISWR?	80% Natural Flow (cfs)	Qw > 1% of 80% Natural Flow?	Interference @ 30 days (%)	Potential for Subst. Interfer. Assumed?

Comments: No model is readily available to estimate impacts to streams by the pumping of a well in a fractured system. However, because of the low permeability and porosity of the Western Cascades volcanics aquifer system, pumping impacts are likely to be localized to a relatively small area around the wells. Therefore, impacts to Cedar and Fall Creeks are likely to be less than 25% of the pumping rate after 30 days of pumping.

C4a. **690-09-040** (5): Estimated impacts on hydraulically connected surface water sources greater than one mile as a percentage of the proposed pumping rate. Limit evaluation to the effects that will occur up to one year after pumping begins. This table encompasses the considerations required by 09-040 (5)(a), (b), (c) and (d), which are not included on this form. Use additional sheets if calculated flows from more than one WAB are required.

Well Q as CFS         %         <	Oct	Nov	Dec %
Well Q as CFS	%		%
Interference CFS			
Distributed Wells			
	Oct	Nov	Dec
% % % % % % % % % %	%	%	%
Well Q as CFS			
Interference CFS			
% % % % % % % % % %	%	%	%
Well Q as CFS			
Interference CFS			
% % % % % % % %	%	%	%
Well Q as CFS			
Interference CFS			
%         %	%	%	%
Well Q as CFS			
Interference CFS			
%         %	%	%	%
Well Q as CFS			
Interference CFS			
%         %	%	%	%
Well Q as CFS			
Interference CFS			
(A) = Total Interf.			
(B) = 80 % Nat. Q			
(C) = 1 % Nat. Q			
(D) = (A) > (C)			
(E) = (A / B) x 100 % % % % % % % % % %	%	%	%

(A) = total interference as CFS; (B) = WAB calculated natural flow at 80% exceed. as CFS; (C) = 1% of calculated natural flow at 80% exceed. as CFS; (D) = highlight the checkmark for each month where (A) is greater than (C); (E) = total interference divided by 80% flow as percentage.

	690-09-040 (5) (b) The potential to impair or detrimentally affect the public interest is to be determined by the Rights Section.
	If properly conditioned, the surface water source(s) can be adequately protected from interference, and/or ground wat under this permit can be regulated if it is found to substantially interfere with surface water:  i.   The permit should contain condition #(s)
	ii. The permit should contain condition #(s)  The permit should contain special condition(s) as indicated in "Remarks" below;
SV	W / GW Remarks and Conditions
_	
_	
_	
Re	eferences Used:
<u>Cc</u>	eferences Used:  onlon, T.D., Wozniak, K.C., Woodcock, D., Herrera, N.B., Fisher, B.J., Morgan, D.S., Lee, K.K., and Hinkle, S.R., 2005, round-water hydrology of the Willamette Basin, Oregon: U.S. Geological Survey Scientific Investigations Report 2005-5
Co Gr Ga	onlon, T.D., Wozniak, K.C., Woodcock, D., Herrera, N.B., Fisher, B.J., Morgan, D.S., Lee, K.K., and Hinkle, S.R., 2005,
Co Gr Ga U.	onlon, T.D., Wozniak, K.C., Woodcock, D., Herrera, N.B., Fisher, B.J., Morgan, D.S., Lee, K.K., and Hinkle, S.R., 2005, cound-water hydrology of the Willamette Basin, Oregon: U.S. Geological Survey Scientific Investigations Report 2005-5 annett, M.W. and Caldwell, R., 1998, Geologic framework of the Willamette Lowland aquifer system, Oregon and Washi

Page

5

Application G-17630

Application G-17630 Date: July 30, 2013 Page

### D. <u>WELL CONSTRUCTION, OAR 690-200</u>

D1.	Well #:	Logid:
D2.	a.	ELL does not appear to meet current well construction standards based upon: review of the well log; field inspection by
D3.		ELL construction deficiency or other comment is described as follows:
D4. [	Route to	o the Well Construction and Compliance Section for a review of existing well construction.

6

### Water Availability Tables

## Water Availability Analysis Detailed Reports

# MCDOWELL CR > S SANTIAM R - AT MOUTH WILLAMETTE BASIN

Water Availability as of 7/30/2013

Watershed ID #: 123

Exceedance Level:

80% ▼

Time: 7:05 AM

Date: 7/30/2013

#### Water Availability Calculation

Monthly Streamflow in Cubic Feet per Second Annual Volume at 50% Exceedance in Acre-Feet

Month	Natural Stream Flow	Consumptive Uses and Storages	Expected Stream Flow	Reserved Stream Flow	Instream Flow Requirement	Net Water Available
JAN	83.30	0.05	83.20	0.00	45.00	38.20
FEB	82.20	0.05	82.20	0.00	45.00	37.20
MAR	59.90	0.02	59.90	0.00	45.00	14.90
APR	34.30	0.05	34.20	0.00	45.00	-10.80
MAY	30.00	0.25	29.80	0.00	45.00	-15.20
JUN	26.00	0.49	25.50	Ď.00	15.00	10.50
JUL	12.30	0.85	11.50	0.00	8.00	3.45
AUG	5.56	0.68	4.88	0.00	3.00	1.88
SEP	4.88	0.34	4.54	0.00	3.00	1.54
OCT	4.87	0.04	4.83	0.00	20.00	-15.20
NOV	31.00	0.03	31.00	0.00	45.00	-14.00
DEC	56.60	0.04	56.60	0.00	45.00	11.60
ANN	47,400.00	176.00	47,200.00	0.00	21,900.00	25,900.00

### Well Location Map

