# Water Right Conditions Tracking Slip

Groundwater/Hydrology Section

Reviewer: J. Hackett

# WATER RESOURCES DEPARTMENT **MEMO** Application G- 17727 TO: FROM: SUBJECT: Scenic Waterway Interference Evaluation YES The source of appropriation is within or above a Scenic Waterway YES Use the Scenic Waterway condition (Condition 7J) Per ORS 390.835, the Ground Water Section is able to calculate ground water interference with surface water that contributes to a Scenic Waterway. The calculated interference is distributed below. Per ORS 390.835, the Ground Water Section is **unable** to calculate ground water interference with surface water that contributes to a scenic waterway; therefore,

# the Department is unable to find that there is a preponderance of evidence that the proposed use will measurably reduce the surface water flows necessary to maintain the free-flowing character of a scenic waterway.

#### DISTRIBUTION OF INTERFERENCE

Calculate the percentage of consumptive use by month and fill in the table below. If interference cannot be calculated, per criteria in 390.835, do not fill in the table but check the "unable" option above, thus informing Water Rights that the Department is unable to make a Preponderance of Evidence finding.

Exercise of this permit is calculated to reduce monthly flows in \_\_\_\_\_Scenic Waterway by the following amounts expressed as a proportion of the consumptive use by which surface water flow is reduced.

Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec

# PUBLIC INTEREST REVIEW FOR GROUNDWATER APPLICATIONS

TO:		Wate	r Rights S	ection				Date	e Novem	ber 5, 20	13	
FROM	:	Grou	ndwater S	ection		J. Hac	<u>kett</u>					
						Davi	awar'e Mama					
SUBJE	CT:	Appl	ication G-	17727		Suj	persedes re	view of		Data of Da		
										Date of Re	view(s)	
OAR 69 welfare, to deteri	90-310-1 safety a mine who	<b>30</b> (1) <i>and heal</i> ether th	The Depart th as descr e presumpt	<i>ibed in ORS</i> ion is establ	resume that 537.525. D ished. OAR	a propose epartment 690-310-	ed groundwa staff review 140 allows t	v ground wate he proposed	ensure the preser applications use be modified icies in place a	under OA d or cond	R 690-3 itioned to	10-140 meet
A. <u>GE</u> l	NERAL	INFO	<u>PRMATIO</u>	<u>ON</u> : A	pplicant's N	lame:	Jerry Lasel	lle		County:_	Clackar	nas
Al.	Applica	ınt(s) se	eek(s) <u>0.3</u>	34 cfs froi	m2							
						subb		•	anby			
A2. A3.									etober 1 wells as such		gid):	
Well	Logic	d	Applicant Well #	's Propos	ed Aquifer*	Prop Rate		Location (T/R-S QQ-		ation, mete 0' N, 1200'		
1	CLAC 50	0982	1	al	luvium	0.3		3S/1E-24 SE-		50' N, 2271'		
2	Propos	ed	2	al	luvium	0.3	34	3S/1E-25 NE-	-NW 5	50° S, 2271'	E fr SW co	r <u>S</u> 24
3 4						-						
5						-						
* Alluvit	ım, CRB,	Bedrocl	k	·					·			
	Well	First			Well	Seal	Casing	Liner	Perforations	Well	Draw	
Well	Elev	Water	SWL	SWL	Depth	Interval	Intervals	Intervals	Or Screens	Yield	Down	Test
	ft msl	ft bls	ft bls	Date	(ft)	(ft)	(ft)	(ft)	(ft)	(gpm)	(ft)	Туре
2**	240	89	137	9/8/1996	190	0-21	+1-125	115-190	130-190	50		A
2**	230									+		
Lise data	from ann	lication	for proposed	l wells								
A4.	Comme	ents: _*	* The appli	icant did not					nation for this intended aquif			
A5. 🛛	manage (Not all	ment of basin r ents: <u>Th</u>	ules contai ne applican	ater hydrauli n such provi t's wells pro	cally conne sions.) duce from a	cted to sur confined	rface water aquifer, so	$\square$ are, $or$	o the developn are not, acti	vated by t	his applic	eation.
A6. 🗌	Comme	# of admir ents:	nistrative ar	rea:,	,,	,	, ta	p(s) an aquife	er limited by a	n administ	rative res	striction.

Version: 07/26/2013

Date: November 5, 2013

2

# B. GROUND WATER AVAILABILITY CONSIDERATIONS, OAR 690-310-130, 400-010, 410-0070

	ed upon available data, I have determined that ground water* for the proposed use:		
a.	is over appropriated, is <b>not</b> over appropriated, or cannot be determined to be period of the proposed use. * This finding is limited to the ground water portion of determination as prescribed in OAR 690-310-130;		
b.	will not or will likely be available in the amounts requested without injury to pr is limited to the ground water portion of the injury determination as prescribed in OA		
c.	will not or will likely to be available within the capacity of the ground water res	source; or	
d.	will, if properly conditioned, avoid injury to existing ground water rights or to the  i. The permit should contain condition #(s) _7B,7C	ground water res	ource:
	<ul> <li>ii.  The permit should be conditioned as indicated in item 2 below.</li> <li>iii.  The permit should contain special condition(s) as indicated in item 3 below</li> </ul>	;	
a.	Condition to allow ground water production from no deeper than	ft. below land	surface;
b.	Condition to allow ground water production from no shallower than	ft. below land	surface;
c.	★ Condition to allow ground water production only from the alluvial water reservoir between approximately ft. and ft. below law	nd surface;	ground
d.	Well reconstruction is necessary to accomplish one or more of the above conditions to occur with this use and without reconstructing are eited below. Without reconstruction issuance of the permit until evidence of well reconstruction is filed with the Departm Ground Water Section.	action, I recomme	nd withholdir
	Describe injury —as related to water availability— that is likely to occur without well r		
	<b>Describe injury</b> —as related to water availability— that is likely to occur without well resenior water rights, not within the capacity of the resource, etc):		
Gro			
The and wate appr	senior water rights, not within the capacity of the resource, etc):	nts that encase thin thin sand and grav nearby alluvial we	n beds of san vel beds. The
The and water approximately two No 1	und water availability remarks:  applicant's wells are located in an area that contains mostly fine grained alluvial sedimen gravels from land surface to a depth of 400-600 feet. Wells in the area produce from the ter-bearing zones are not likely to have extensive lateral continuity. The median yield for not example to example the possibility that the applicant may not be able to obtain wells.  ocal data is available to evaluate water-level trends over time in this area. This indicates a	nts that encase thin thin sand and grav nearby alluvial we ain the requested	n beds of sand vel beds. These ells is 150 gpm fron
The and water approximately two No 1	und water availability remarks:  applicant's wells are located in an area that contains mostly fine grained alluvial sedimen gravels from land surface to a depth of 400-600 feet. Wells in the area produce from the ter-bearing zones are not likely to have extensive lateral continuity. The median yield for moximately 35 gpm. This suggests the possibility that the applicant may not be able to obtawells.	nts that encase thin thin sand and grav nearby alluvial we ain the requested	n beds of san vel beds. The ells is 150 gpm fron
The and water approximately two No 1	und water availability remarks:  applicant's wells are located in an area that contains mostly fine grained alluvial sedimen gravels from land surface to a depth of 400-600 feet. Wells in the area produce from the ter-bearing zones are not likely to have extensive lateral continuity. The median yield for not example to example the possibility that the applicant may not be able to obtain wells.  ocal data is available to evaluate water-level trends over time in this area. This indicates a	nts that encase thin thin sand and grav nearby alluvial we ain the requested	n beds of san vel beds. The ells is 150 gpm fror
The and water approximately two No 1	und water availability remarks:  applicant's wells are located in an area that contains mostly fine grained alluvial sedimen gravels from land surface to a depth of 400-600 feet. Wells in the area produce from the ter-bearing zones are not likely to have extensive lateral continuity. The median yield for not example to example the possibility that the applicant may not be able to obtain wells.  ocal data is available to evaluate water-level trends over time in this area. This indicates a	nts that encase thin thin sand and grav nearby alluvial we ain the requested	n beds of sam vel beds. The ells is 150 gpm fror
The and water approximately two No 1	und water availability remarks:  applicant's wells are located in an area that contains mostly fine grained alluvial sedimen gravels from land surface to a depth of 400-600 feet. Wells in the area produce from the ter-bearing zones are not likely to have extensive lateral continuity. The median yield for not example to example the possibility that the applicant may not be able to obtain wells.  ocal data is available to evaluate water-level trends over time in this area. This indicates a	nts that encase thin thin sand and grav nearby alluvial we ain the requested	n beds of sam vel beds. The ells is 150 gpm fror
The and water approximately two No 1	und water availability remarks:  applicant's wells are located in an area that contains mostly fine grained alluvial sedimen gravels from land surface to a depth of 400-600 feet. Wells in the area produce from the ter-bearing zones are not likely to have extensive lateral continuity. The median yield for not example to example the possibility that the applicant may not be able to obtain wells.  ocal data is available to evaluate water-level trends over time in this area. This indicates a	nts that encase thin thin sand and grav nearby alluvial we ain the requested	n beds of sam vel beds. The ells is 150 gpm fror
The and water approximately two No 1	und water availability remarks:  applicant's wells are located in an area that contains mostly fine grained alluvial sedimen gravels from land surface to a depth of 400-600 feet. Wells in the area produce from the ter-bearing zones are not likely to have extensive lateral continuity. The median yield for not example to example the possibility that the applicant may not be able to obtain wells.  ocal data is available to evaluate water-level trends over time in this area. This indicates a	nts that encase thin thin sand and grav nearby alluvial we ain the requested	n beds of sam vel beds. The ells is 150 gpm fror

3

Date: November 5, 2013

## C. GROUND WATER/SURFACE WATER CONSIDERATIONS, OAR 690-09-040

C1. **690-09-040** (1): Evaluation of aquifer confinement:

Well	Aquifer or Proposed Aquifer	Confined	Unconfined
1	alluvium	$\boxtimes$	
2	alluvium	$\boxtimes$	

Basis for aquifer confinement evaluation: Nearby well logs show a thick sequence of silts and clays which encase a few thin sand and gravel beds that produce water to wells. This suggests that the productive water-bearing zones are likely to be confined.

C2. 690-09-040 (2) (3): Evaluation of distance to, and hydraulic connection with, surface water sources. All wells located a horizontal distance less than 1/4 mile from a surface water source that produce water from an unconfined aquifer shall be assumed to be hydraulically connected to the surface water source. Include in this table any streams located beyond one mile that are evaluated for PSI.

Well	SW #	Surface Water Name	GW Elev ft msl	SW Elev ft msl	Distance (ft)	Hydraulically Connected? YES NO ASSUMED	Potentia Subst. Int Assume YES	terfer.
1	1	Parrott Creek	150	80-130	3300			$\boxtimes$
2	1	Parrott Creek	150	80-130	3000			$\boxtimes$
1	2	Unnamed trib. to Parrott Creek	150	130-250	1650			
2	2	Unnamed trib. to Parrott Creek	150	130-250	1500			$\boxtimes$

Basis for aquifer hydraulic connection evaluation: The perennial nature of Parrott Creek and its local tributary indicate a component of groundwater discharge that sustains surface water flows. Also, heads in nearby wells are coincident with or above the elevation of local streams. These facts indicate that the alluvial groundwater system is hydraulically connected to local streams. However, the high proportion of clay and silt in the alluvial sediments should reduce the efficiency of the connection.

Water Availability Basin the well(s) are located within: 181: Willamette R > Columbia R - At Mouth

C3a. 690-09-040 (4): Evaluation of stream impacts for each well that has been determined or assumed to be hydraulically connected and less than 1 mile from a surface water source. Limit evaluation to instream rights and minimum stream flows that are pertinent to that surface water source, and not lower SW sources to which the stream under evaluation is tributary. Compare the requested rate against the 1% of 80% natural flow for the pertinent Water Availability Basin (WAB). If Q is not distributed by well, use full rate for each well. Any checked box indicates the well is assumed to have the potential to cause PSI.

Well	SW #	Well < 1/4 mile?	Qw > 5 cfs?	Instream Water Right ID	Instream Water Right Q (cfs)	Qw> 1% ISWR?	80% Natural Flow (cfs)	Qw > 1% of 80% Natural Flow?	Interference @ 30 days (%)	Potential for Subst. Interfer. Assumed?
1	1			n/a			4890.00		<<25%	
2	1			n/a			4890.00		<<25%	
1	2			n/a			4890.00		<<25%	
2	2			n/a			4890.00		<<25%	

Application G-17727

Date: November 5, 2013

Page

4

C3b. **690-09-040 (4):** Evaluation of stream impacts by total appropriation for all wells determined or assumed to be hydraulically connected and less than 1 mile from a surface water source. Complete only if Q is distributed among wells. Otherwise same evaluation and limitations apply as in C3a above.

SW #	Qw > 5 cfs?	Instream Water Right ID	Instream Water Right Q (cfs)	Qw > 1% ISWR?	80% Natural Flow (cfs)	Qw > 1% of 80% Natural Flow?	Interference @ 30 days (%)	Potential for Subst. Interfer. Assumed?

Comments: Because of uncertainty regarding the spatial distribution and occurrence of productive water-bearing zones, a model was not used to estimate the interference at 30 days. However, nearby well logs indicate that productive water-bearing zones are generally thin beds of sand and gravel that are encased in a thick sequence of silt and clays. These water-bearing zones are not likely to have extensive lateral continuity. Therefore, any given productive zone is likely to be vertically separated from nearby streams by many feet of clay or silt over most stream reaches. Models run in similar scenarios indicate impacts that are much less than 25% after 30 days.

C4a. **690-09-040 (5):** Estimated impacts on **hydraulically connected surface water sources greater than one mile** as a percentage of the proposed pumping rate. Limit evaluation to the effects that will occur up to one year after pumping begins. This table encompasses the considerations required by 09-040 (5)(a), (b), (c) and (d), which are not included on this form. Use additional sheets if calculated flows from more than one WAB are required.

Non-D	istributed	Wells											
Well	SW#	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oet	Nov	Dec
		%	%	%	%	%	%	%	%	%	%	%	%
Well (	as CFS												
Interfei	ence CFS												
D: 4 'I	4. 1337.11												
Well	outed Well SW#	s Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
wen	3W#				Apr					% %	%	%	%
W . II .	) CUC	%	%	%	%	%	%	%	%	%	%	%	76
	Q us CFS												
mener	ence CFS		~				67	er e	eri .	Cr.	CT.	CT.	67
111 11 4	CIFIC	%	%	%	%	%	%	%	%	%	%	%	%
	Q as CFS												
Interfei	ence CFS												
		%	%	%	%	%	%	%	%	%	%	%	%
	) as CFS												
Interfei	ence CFS												
		%	%	%	%	%	%	%	%	%	%	%	%
	) as CFS												
Interfer	ence CFS												
		%	%	%	%	%	%	%	%	%	%	%	%
Well (	) as CFS												
Interfer	ence CFS												
		%	%	%	%	%	%	%	%	%	%	%	%
Well (	Q as CFS												
Interfer	ence CFS												
(A) = T	otal Interf.												
	% Nat. Q												
	% Nat. Q												
											_		
(D) =	(A) > (C)												
$(\mathbf{E}) = (\mathbf{A}$	/B) x 100	%	%	%	%	%	%	%	%	%	%	%	%

Application G-17727 5 Date: November 5, 2013 Page (A) = total interference as CFS; (B) = WAB calculated natural flow at 80% exceed. as CFS; (C) = 1% of calculated natural flow at 80% exceed. as CFS; (D) = highlight the checkmark for each month where (A) is greater than (C); (E) = total interference divided by 80% flow as percentage. 690-09-040 (5) (b) The potential to impair or detrimentally affect the public interest is to be determined by the Water C4b. Rights Section. C5. If properly conditioned, the surface water source(s) can be adequately protected from interference, and/or ground water use under this permit can be regulated if it is found to substantially interfere with surface water: i. The permit should contain condition #(s) ii. The permit should contain special condition(s) as indicated in "Remarks" below; C6. SW / GW Remarks and Conditions\_\_\_\_\_\_ References Used: Leonard, A.R. and Collins, C.A., 1983, Ground water in the northern part of Clackamas County, Oregon: Oregon Water Resources Department Ground Water Report No. 29. Trimble, D.E., 1963, Geology of Portland, Oregon and Adjacent Areas: U.S. Geological Survey Bulletin 1119.

Application G-17727 Date: November 5, 2013 Page 6

# D. WELL CONSTRUCTION, OAR 690-200

D1.	Well #:	Logid:	
D2.	a.	ELL does not appear to meet current well construction standards based upon: review of the well log; field inspection by	;
D3.	THE W	ELL construction deficiency or other comment is described as follows:	
D4.	Route t	to the Well Construction and Compliance Section for a review of existing well construction.	

Date: November 5, 2013

#### Water Availability Tables

## WILLAMETTE R > COLUMBIA R - AT MOUTH WILLAMETTE BASIN

Water Availability as of 11/5/2013

Watershed ID #: 181 (Map)

Exceedance Level:

80%

Time: 4:28 PM

Date: 11/5/2013

### Water Availability Calculation

Monthly Streamflow in Cubic Feet per Second Annual Volume at 50% Exceedance in Acre-Feet

Month I	Natural Stream Flow	Consumptive Uses and Storages	Expected Stream Flow	Reserved Stream Flow	Instream Flow Requirement	Net Water Available
JAN	27,500.00	2,770.00	24,700.00	0.00	1,500.00	23,200.00
FEB	30,000.00	8,040.00	22,000.00	0.00	1,500.00	20,500.00
MAR	28,500.00	7,600.00	20,900.00	0.00	1,500.00	19,400.00
APR	25,400.00	7,210.00	18,200.00	0.00	1,500.00	16,700.00
MAY	20,700.00	4,460.00	16,200.00	0.00	1,500.00	14,700.00
JUN	11,000.00	2,430.00	8,570.00	0.00	1,500.00	7,070.00
JUL	6,280.00	2,370.00	3,910.00	0.00	1,500.00	2,410.00
AUG	4,890.00	2,130.00	2,760.00	0.00	1,500.00	1,260.00
SEP	4,930.00	1,760.00	3,170.00	0.00	1,500.00	1,670.00
OCT	5,990.00	736.00	5,250.00	0.00	1,500.00	3,750.00
NOV	12,700.00	1,030.00	11,700.00	0.00	1,500.00	10,200.00
DEC	24,800.00	1,420.00	23,400.00	0.00	1,500.00	21,900.00
ANN	19,700,000.00	2,510,000.00	17,200,000.00	0.00	1,090,000.00	16,100,000.00

### **Detailed Report of Instream Flow Requirements**

Instream Flow Requirements in Cubic Feet per Second

Applicatio n #	Status	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
MF181A	APPLICATI ON	00	00	00	00	00	00	00	00	00	00	00	00
Maximum	E I	1,500. 00											

8

### Well Location Map

