PUBLIC INTEREST REVIEW FOR GROUNDWATER APPLICATIONS

TO:		Water Rights Section						Da	ite	Decei	<u>nber 22</u>	, 2015	
FROM	[:	Grou	ndwater S	ection		J. Hackett							
SUBJI	JBJECT: Application G- <u>18134</u>					Reviewer's Name Supersedes review of Date of Review(s)							
PUBL OAR 6 welfare to deten the pres	PUBLIC INTEREST PRESUMPTION; GROUNDWATER OAR 690-310-130 (1) <i>The Department shall presume that a proposed groundwater use will ensure the preservation of the public welfare, safety and health as described in ORS 537.525.</i> Department staff review groundwater applications under OAR 690-310-140 to determine whether the presumption is established. OAR 690-310-140 allows the proposed use be modified or conditioned to meet the presumption criteria. This review is based upon available information and agency policies in place at the time of evaluation .												
A. <u>GENERAL INFORMATION</u> : Applicant's Name: <u>Michael & Kristen Kruse</u> County: <u>Union</u>													
A1.	Applica	nt(s) se	ek(s) <u>1.9</u>	8 cfs from	n <u>1</u>	well((s) in the	Grande	Ronde				_Basin,
						subb	asin						
A2.	Propose	ed use _	Irr	igation		Seas	sonality:	March 1 –	<u>October</u>	31			
A3.	Well an	d aquif	er data (att	ach and nu	mber logs f	or existin	ıg wells; 1	nark propose	ed wells as	s such	under log	gid):	
Well	Logic	1	Applicant Well #	's Propos	ed Aquifer*	Proposed Rate(cfs)		Location (T/R-S QQ-Q)		Location, metes and bound 2250' N, 1200' E fr NW co		nds, e.g. cor S 36	
1 2	UNIO 50	833	1]	Basalt	1.9	98	1S/39E-29 NW-NW		84'S, 708' E fr NW cor S 29		S 29	
3													
5													
* Alluvi	um, CRB,	Bedroc	k				·						
Well	Well Elev ft msl	First Water ft bls	SWL ft bls	SWL Date	Well Depth (ft)	Seal Interval	Casing Interval	s Liner Intervals	Perfora Or Sci	ations reens	Well Yield	Draw Down (ft)	Test Type
1	2743	231	-37	6/11/2001	1924	0-483	+2 - 1924*	*	224 -	1924	1700	0	Р
Use data	a from app	lication	for proposed	t wells.									
A4.	Commo above la	ents: * and sur	* <u>Well log</u> face to 483	provides con feet below l	flicting info and surface	ormation r (bls) in S	egarding ection 6, a	depth of casin and perforated	<u>g. The log</u> l casing fr	<u>g indica</u> om 224	tes casing to 1924	g from 2 feet bls i	<u>feet</u> n
	Section	7.											
A5. 🛛	Provis manage	ions of ment o	the <u>Grand</u> f groundwa	le Ronde ater hydraulio	cally conned	cted to sur	Basin	rules relative $\begin{bmatrix} r & r \\ r & m \end{bmatrix}$ are, or	to the dev are no	velopm t , activa	ent, class ated by th	ification	and/or ation.
	(Not all Comme	basin 1 nts:	ules contai	n such provi	sions.)								
A6. 🗌	 Well(s) #,,,,, tap(s) an aquifer limited by an administrative restriction. Name of administrative area:, comments: 												

B. GROUNDWATER AVAILABILITY CONSIDERATIONS, OAR 690-310-130, 400-010, 410-0070

- B1. **Based upon available data**, I have determined that <u>groundwater</u>* for the proposed use:
 - a. **is** over appropriated, **is not** over appropriated, *or* **is cannot be determined to be** over appropriated during any period of the proposed use. * This finding is limited to the groundwater portion of the over-appropriation determination as prescribed in OAR 690-310-130;
 - b. **will not** *or* **will** likely be available in the amounts requested without injury to prior water rights. * This finding is limited to the groundwater portion of the injury determination as prescribed in OAR 690-310-130;
 - c. **will not** *or* **will** likely to be available within the capacity of the groundwater resource; or
 - d. **will, if properly conditioned**, avoid injury to existing groundwater rights or to the groundwater resource:
 - i. The permit should contain condition #(s) 7N; Lagre water-use reporting
 - ii. The permit should be conditioned as indicated in item 2 below.
 - iii. The permit should contain special condition(s) as indicated in item 3 below;
- B2. a. Condition to allow groundwater production from no deeper than ______ ft. below land surface;
 - b. Condition to allow groundwater production from no shallower than ______ ft. below land surface;
 - c. Condition to allow groundwater production only from the groundwater reservoir between approximately ft. and ft. below land surface;
 - d. Well reconstruction is necessary to accomplish one or more of the above conditions. The problems that are likely to occur with this use and without reconstructing are cited below. Without reconstruction, I recommend withholding issuance of the permit until evidence of well reconstruction is filed with the Department and approved by the Groundwater Section.

Describe injury –as related to water availability– that is likely to occur without well reconstruction (interference w/ senior water rights, not within the capacity of the resource, etc):

B3. Groundwater availability remarks: The applicant's well is located in the fault bounded depression that is the Grande Ronde Valley. The valley is a pull-apart basin bounded on the east and west by major fault zones (Hampton and Brown, 1964). Down-to-the-west normal faults have dropped the bedrock surface approximately 1000 feet from an elevation of 3300 feet above mean sea level (amsl) in the eastern uplands bordering the basin to 2280 feet amsl in the valley. The area around the applicant's well is underlain by fine to coarse grained fluvial and pluvial sediments from land surface to a depth of about 500 feet. The uppermost bedrock unit, the Powder River Volcanics (PRV), have a total thickness of 500 feet and extend to a depth of 1000 feet below land surface. Beneath the PRV, basalt flows of the Columbia River Basalt Group (CRBG) extend to a depth of several thousand feet.

Within the CRBG, most water occurs in confined aquifers that occupy thin rubble zones (interflow zones) at the contacts between lava flows. The interiors of the basalt flows generally have low porosity and permeability and act as confining beds. This geometry generally produces a stack of thin aquifers (interflow zones) separated by thick confining beds (flow interiors). The low permeability of the basalt flow interiors probably limits the natural vertical connection between overlying aquifers. Drill cuttings analysis (Ferns et. al, 2010) indicates that the applicant's well produces from water-bearing zones of the Grande Ronde Basalt Formation of the CRBG. Production from water-bearing zones in Grande Ronde Basalt aquifers in nearby wells ranges from 50 to 3200 gallons per minute (gpm) with a median production of 1700 gpm.

Water levels in nearby Grande Ronde Basalt wells show conflicting trends over time (see attached hydrographs). Water levels in well UNIO 156 declined approximately 40 feet between 1950 and 2001, however water levels have stabilized since 2001. Water levels in other nearby wells show no obvious signs of declines. Because CRBG aquifers are prone to overdraft and water levels appear to have declined somewhat in at least one nearby well, the permit should contain condition 7N (long-term water level measurements) and the large water-use reporting condition.

C. GROUNDWATER/SURFACE WATER CONSIDERATIONS, OAR 690-09-040

C1. 690-09-040 (1): Evaluation of aquifer confinement:

Well	Aquifer or Proposed Aquifer	Confined	Unconfined
1	Basalt	\boxtimes	

Basis for aquifer confinement evaluation: <u>Water level rose well above the depth at which it was encountered</u>. This indicates confined conditions.

C2. **690-09-040** (2) (3): Evaluation of distance to, and hydraulic connection with, surface water sources. All wells located a horizontal distance less than ¹/₄ mile from a surface water source that produce water from an unconfined aquifer shall be assumed to be hydraulically connected to the surface water source. Include in this table any streams located beyond one mile that are evaluated for PSI.

Well	SW #	Surface Water Name	GW Elev ft msl	SW Elev ft msl	Distance (ft)	Hydraulically Connected? YES NO ASSUMED	Potential for Subst. Interfer. Assumed? YES NO
1	1	Grande Ronde River	2798	2690	3350		

Basis for aquifer hydraulic connection evaluation: Water-bearing zones in the applicant's well are several hundred feet below the elevation of the Grande Ronde River. This suggests the well is not locally hydraulically connected to the river.

Water Availability Basin the well(s) are located within: <u>30810407: GRANDE RONDE R > SNAKE R – AB WILLOW CR</u>

C3a. **690-09-040** (4): Evaluation of stream impacts for <u>each well</u> that has been determined or assumed to be **hydraulically connected and less than 1 mile** from a surface water source. Limit evaluation to instream rights and minimum stream flows that are pertinent to that surface water source, and not lower SW sources to which the stream under evaluation is tributary. Compare the requested rate against the 1% of 80% *natural* flow for the pertinent Water Availability Basin (WAB). If Q is not distributed by well, use full rate for each well. Any checked 🖾 box indicates the well is assumed to have the potential to cause PSI.

Well	SW #	Well < ¼ mile?	Qw > 5 cfs?	Instream Water Right ID	Instream Water Right Q (cfs)	Qw > 1% ISWR?	80% Natural Flow (cfs)	Qw > 1% of 80% Natural Flow?	Interference @ 30 days (%)	Potential for Subst. Interfer. Assumed?

C3b. **690-09-040** (4): Evaluation of stream impacts by total appropriation for all wells determined or assumed to be hydraulically connected and less than 1 mile from a surface water source. Complete only if Q is distributed among wells. Otherwise same evaluation and limitations apply as in C3a above.

SW #	Qw 5 cfs	> Instream > Water ? Right ID	Instream Water Right Q (cfs)	Qw > 1% ISWR?	80% Natural Flow (cfs)	Qw > 1% of 80% Natural Flow?	Interference @ 30 days (%)	Potential for Subst. Interfer. Assumed?
Comments: _								

C4a. **690-09-040 (5):** Estimated impacts on **hydraulically connected surface water sources greater than one mile** as a percentage of the proposed pumping rate. Limit evaluation to the effects that will occur up to one year after pumping begins. This table encompasses the considerations required by 09-040 (5)(a), (b), (c) and (d), which are not included on this form. Use additional sheets if calculated flows from more than one WAB are required.

Non-Di	stributed	Wells											
Well	SW#	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
		%	%	%	%	%	%	%	%	%	%	%	%
Well Q	as CFS												
Interfere	ence CFS												
Dictrib	utod Woll	c											
Well	SW#	Ian	Feb	Mar	Anr	May	Iun	Iul	Δ 11σ	Sen	Oct	Nov	Dec
VV CH	5111	9/a	%	0/a	0%	%	0/a	0/a	11ug %	%	%	0/a	%
Well O	as CES	70	70	70	70	70	70	70	70	70	70	70	70
Interfere	ence CFS												
		0/0	0/0	0/0	0/0	9/0	0/0	0/0	0/0	0/0	0/0	0/0	0/0
Well O	as CFS	/0	/0	/0	/0	/0	/0	/0	/0	/0	/0	/0	/0
Interfere	ence CFS												
		%	%	%	%	%	%	%	%	%	%	%	%
Well Q	as CFS												
Interfere	ence CFS												
		%	%	%	%	%	%	%	%	%	%	%	%
Well Q	as CFS												
Interfere	ence CFS												
		%	%	%	%	%	%	%	%	%	%	%	%
Well Q	as CFS												
Interfere	ence CFS												
		%	%	%	%	%	%	%	%	%	%	%	%
Well Q	as CFS												
Interfere	ence CFS												
$(\mathbf{A}) = \mathbf{T}0$	tai Interf.												
(B) = 80	% Nat. Q												
(C) = 1	% Nat. Q												
(D) = (\mathbf{A}) > (C)	\sim	$\overline{\checkmark}$	\checkmark	$\overline{\checkmark}$	\checkmark	$\overline{\checkmark}$	$\overline{\checkmark}$	$\overline{\checkmark}$	$\overline{\checkmark}$	$\overline{\checkmark}$		~
(E) = (A	/ B) x 100	%	%	%	%	%	%	%	%	%	%	%	%

(A) = total	interference as CFS; (B) = WAB calculated natural flow at 80% exceed. as CFS	; (C) = 1% of calculated natural flow at 80% exceed. as
CFS; (D)	= highlight the checkmark for each month where (A) is greater than (C); $(E) = tc$	otal interference divided by 80% flow as percentage.

-	
-	
-	
-	
-	
-	
-	
_	
_	
-	
).	690-09-040 (5) (b) The potential to impair or detrimentally affect the public interest is to be determined by the Wa Rights Section.
	If properly conditioned , the surface water source(s) can be adequately protected from interference, and/or groundwater us under this permit can be regulated if it is found to substantially interfere with surface water: i. The permit should contain condition #(s)
	ii. The permit should contain special condition(s) as indicated in "Remarks" below;
SV	V / GW Remarks and Conditions:
SV	V / GW Remarks and Conditions:
SV	V / GW Remarks and Conditions:
SV	V / GW Remarks and Conditions:
SV	V / GW Remarks and Conditions:
SV	V / GW Remarks and Conditions:
SV	V / GW Remarks and Conditions:
sv	V / GW Remarks and Conditions:
sv	V / GW Remarks and Conditions:
sv	V / GW Remarks and Conditions:
sv	V / GW Remarks and Conditions:
sv	V / GW Remarks and Conditions:
sv 	V / GW Remarks and Conditions:
sv 	V / GW Remarks and Conditions:
SV	V / GW Remarks and Conditions:
SV	V / GW Remarks and Conditions:
SV	V / GW Remarks and Conditions:
SV	V / GW Remarks and Conditions:
SV	V / GW Remarks and Conditions:

D. WELL CONSTRUCTION, OAR 690-200

D1.	Well #:	Logid:
D2.	THE WELL does not appear to meet a. review of the well log; b. field inspection by	current well construction standards based upon: ; ;
D3.	THE WELL construction deficiency o	or other comment is described as follows:

D4.

Route to the Well Construction and Compliance Section for a review of existing well construction.

7

Well Location Map



Water-Level Trends in Nearby Wells



