Water Right Conditions Tracking Slip

Groundwater/Hydrology Section

FILE # # G-17215

ROUTED TO: Water Rights

TOWNSHIP/
RANGE-SECTION: 35S/2W-sec 13

CONDITIONS ATTACHED?: Myes [] no

REMARKS OR FURTHER INSTRUCTIONS:

Condition 7B, 7N, 7J and see page 7

Reviewer: GERALD H. GRONDIN

WATER RESOURCES DEPARTMENT

MEN	40							8	June	,	200_9_
TO:		Appli	ication	G 172	115						
FRO SUB.	M: JECT:		W: GERALD H. GRONDIN (Reviewer's Name) cenic Waterway Interference Evaluation								
	_YES	The so	ource of	f approp	riation	is within	n or abo	ve a Sce	enic Wa	terway	
	_YES _NO	Use the Scenic Waterway condition (Condition 7J)									
X	Per Of interfect the Detat that the	RS 390. erence wated into	with surferference 835, the with surferent is unosed us	ace wat e is dist e Ground ace wat nable to	er that or ributed d Water er that or find the	contributed below. Section contributed there bly red	tes to a is unal tes to a se is a pruce the	ble to cascenic v	Waterwa alculate vaterwa erance	ground y; there of evide flows	water
Calcula calcula informi Exerci Water	te the per ted, per c ng Water se of th way by	ON OF recentage of riteria in Rights the is permited the followater flower flow	of consum 390.835, at the De t is calc owing a	nptive use do not fit epartment culated t mounts	e by mont ll in the to is unable o reduce	able but c to make e month	heck the a Prepor ly flows	"unable" iderance s in R	option a of Eviden	bove, thu ce findin	s g. Scenic
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec

PUBLIC INTEREST REVIEW FOR GROUND WATER APPLICATIONS

TO:		Water Rights Section Date 8 June 2009												
FROM	:	Grou	nd Water/I	Hydrology	Section _	Gera		. Gron	din					
SUBJE	CT:	Appli	cation G	17215				s Name edes rev	view of		N.A.	Date of Re	view(s)	
OAR 6 welfare, to determine the pres	90-310-1 safety as mine who umption	30 (1) nd head ether the	The Depart the as describe presumpt. This review.	ibed in ORS ion is estab ew is based	presume 537.525. lished. OA upon ava	that a properties that a prope	posed ent sta 0-14(ff review allows tion and	dwater use we we ground wathe proposed agency political agency political water was a second agency with the proposed agency was a second agency wa	ter apd use	pplications be modified in place at	under O ed or con the time	AR 690-: nditioned	310-140 to meet
A. <u>GE</u> I	NERAL	INFO	RMATIC	<u>)N</u> : A ₁	pplicant's	Name:	Jul	ie Moo	re (Count	ty: Ja	ckson		
A1.									the					_Basin,
A2. A3.	Propose	d use:	Irrigatio		orimary)	Sea		ity	d Map: 1 May to	31 O	ctober (18	34 days)	aid):	
Wel l	Well and aquifer data (attach and number logs for existing well Logid Applicant's Proposed Aquifer* Proposed Rate(cfs)				(T/	Location /R-S QQ-Q)		Location 2250' N	, metes a	and boun	Test Type N.A. Aximum aximum aximum Regue striction.			
1 2	Not dr	illed	1	Cla	aystone	0.02	5	35S/02	W-sec 13 A	BD	1040' S	, 1960' W	fr NE co	r S 13
3														
* Alluvii	um, CRB,	Bedroc	K								L			
	Well	First			W-11	C1			T in an	D	C	Wall	D	
Well	Elev ft msl	Water ft bls	r SWL	SWL Date	Well Depth (ft)	Seal Interval (ft)	Int	asing tervals (ft)	Liner Intervals (ft)		rforations r Screens (ft)	Well Yield (gpm)	Draw Down (ft)	
1	1380	70?	30?	N.A.	175?	0 to 20?	+1	to 20?	0 to 175?	100 to 175?		25?	N.A.	N.A.
Use data	from app	lication	for proposed	wells.									-	
A4.	Commo	ents: _												
				s 11 gpm () cfs per acı) maximui	m to	irrigate	4 acres, les	s tha	n the 22 g	gpm (0.0	5 cfs) ma	aximum
	Well co	nstruc	tion based	upon exam	ple water	well repo	rts sı	ubmitte	d with appli	catio	n.			
A5. 🗌	manage (Not all Comme River I	ment o basin t nts: Basin F	f ground w ules contain The properrogram a	ater hydraul n such provi osed use is i oplies (see	ically con sions.) In the Con OAR 690	nected to some constance C	surfacek (ce water drainag There a	ales relative are, or e within the re various of	⊠ a Upp classi	re not, act	ivated by River Ba for the u	this app	e Rogue
A6. 🗌	Well(s) Name o Comme	# f adminants:	nistrative ar	,ea:,	Not	Applicab	,	, tap	o(s) an aquife	er lim	nited by an	administ	rative res	striction.

1

B. GROUND WATER AVAILABILITY CONSIDERATIONS, OAR 690-310-130, 400-010, 410-0070

B1.	Bas	ed upon available data, I have determined that ground water* for the proposed use:
	a.	is over appropriated, is not over appropriated, or is cannot be determined to be over appropriated during any period of the proposed use. * This finding is limited to the ground water portion of the over-appropriation determination as prescribed in OAR 690-310-130;
	b.	☐ will not <i>or</i> ☐ will likely be available in the amounts requested without injury to prior water rights. * This finding is limited to the ground water portion of the injury determination as prescribed in OAR 690-310-130;
	c.	\square will not or \square will likely to be available within the capacity of the ground water resource; or
	d.	will, if properly conditioned, avoid injury to existing ground water rights or to the ground water resource: i. The permit should contain condition #(s)7B, 7N; ii. The permit should be conditioned as indicated in item 2 below. The permit should contain special condition(s) as indicated in item 3 below;
B2.	a.	Condition to allow ground water production from no deeper than ft. below land surface;
	b.	Condition to allow ground water production from no shallower than ft. below land surface;
	c.	Condition to allow ground water production only from the ground water reservoir between approximately ft. and ft. below land surface;
	d.	Well reconstruction is necessary to accomplish one or more of the above conditions. The problems that are likely to occur with this use and without reconstructing are cited below. Without reconstruction, I recommend withholding issuance of the permit until evidence of well reconstruction is filed with the Department and approved by the Ground Water Section. Describe injury —as related to water availability—that is likely to occur without well reconstruction (interference w/ senior water rights, not within the capacity of the resource, etc):
В3.	If a	permit is issued, condition with 7B, 7N, and a condition that requires the applicant to install and maintain a perly functioning, totalizing flow meter on the well, record monthly water use totals, and submitted the water use a annually to OWRD.
		Water Use Measurement, Recording And Reporting Conditions
	A	Before water use may begin under this permit, the permittee shall install a properly functioning totalizing flow meter. The permittee shall maintain the meter in good working order, shall keep a complete record of the amount of water used each month and shall submit a report which includes the recorded water use measurements to the Department annually or more frequently as may be required by the Director. Further, the Director may require the permittee to report general water use information, including the place and nature of use of water under the permit.
	В	. The permittee shall allow the watermaster access to the meter; provided however, where the meter is located within a private structure, the watermaster shall request access upon reasonable notice.
	the Wil mud	geologic map by Wiley and Hladky (1991) and Hladky (1992) and the water well reports (well log) for wells near proposed well indicate the proposed well site is located where the Payne Cliffs Formation (Tpcu) is exposed. ey and Hladky (1991) and Hladky (1992) note the formation is composed of conglomerate, sandstone, siltstone, alstone, and coal in non-marine fluvial deposits locally derived. The formation is likely fractured (secondary meability) with low storage and yield. The water well reports noted record various claystones and some sandstone

with well yields generally less than 50 gpm.

Application: G-17215

The proposed well may obtain the yield proposed (desired).

State observation well 1157 (JACK 34195) is about 4.3 miles southwest of the proposed well site in the same township (T35S/R2W) as the proposed well site, but in a different section (section 33). The water well report for JACK 34195 indicates the well obtains ground water from claystone. The ground water level measurement data is from 1975 to 2007. The hydrograph for the well shows seasonal fluctuations and annual (year to year) trends. The annual trend appears related to climate related with higher peak annual water levels during wet years and lower peak water levels during dry years. The difference between annual peaks during wet years versus dry years can exceed 10 feet. The

during dry years. The difference between annual peaks during wet years versus dry years can exceed 10 feet. The difference between the seasonal winter-spring ground water level high versus the summer-fall ground water level low in a given year ranges from less than 10 feet to more than 60 feet. This annual and seasonal variability is somewhat large and indicates low storage. Very limited ground water level measurement data for four wells (JACK 3466, JACK 55776, JACK 3509, and JACK 3427) less than 0.3 miles from the proposed well site were found. Graphs of the limited data do not indicate a ground water level decline.

3

C. GROUND WATER/SURFACE WATER CONSIDERATIONS, OAR 690-09-040

C1. **690-09-040 (1):** Evaluation of aguifer confinement:

Well	Aquifer or Proposed Aquifer	Confined	Unconfined
1	Payne Cliffs Formation (Tpcu)		\boxtimes

Basis for aquifer confinement evaluation: ___

Water well reports for wells near the proposed well site indicate a static water level above the first water bearing zone. This does not imply confined ground water given the ground water occurs in likely interconnected fractured rock. The depth where a well encounters fractures yielding water varies. Often, the various fractures are interconnected laterally and vertically.

C2. **690-09-040 (2) (3):** Evaluation of distance to, and hydraulic connection with, surface water sources. All wells located a horizontal distance less than ¼ mile from a surface water source that produce water from an unconfined aquifer shall be assumed to be hydraulically connected to the surface water source. Include in this table any streams located beyond one mile that are evaluated for PSI.

Well	SW #	Surface Water Name	GW Elev ft msl	SW Elev ft msl	Distance (ft)	Hydraulically Connected? YES NO ASSUMED	Potential Subst. Inte Assume YES	erfer.
1	1	Un-named creek	1365	1370	200			\boxtimes
1	2	Constance Creek	1365	1370	1200			\boxtimes
1	3	Snider Creek	1365	1370	9500			
1	4	Rogue River	1365	1260	10,400			\boxtimes

Basis for aquifer hydraulic connection evaluation:

The ground water level is based upon nearby well JACK 3466 less than 400 feet from the proposed well site, and the surface water elevations were based upon the Boswell Mountain and Shady Cove quadrangle maps (1:24,000 scale). The nearest reaches of the three creeks have approximately the same elevation.

No hydraulic connection with the un-named creek is noted in the table above given the creek is identified as intermittent or seasonal, dry during certain times of the year.

The proposed well site is in the same drainage as Constance Creek, less than 0.25 miles from the creek. One information source indicates the creek is perennial. However, OWRD staff surface water flow evaluation of Constance Creek during 2003-2004 observed the creek flow as intermittent rather than perennial, dominated by precipitation with very little, if any, ground water contribution (see attached Ivan Gall memo dated 28 June 2004 written for ground water right application files G-15794 and G-15943). Given that memo, a hydraulic connection can not be established at this time.

Snider Creek is in the next drainage west of Constance Creek. It is possible that a small ground water divide (mound) may exist between Constance Creek and Snider Creek. If present, a divide would make a hydraulic connection between the proposed well and Snider Creek indirect.

No potential for substantial interference can be assumed for the three creeks identified given there is no apparent hydraulic connection, and additionally for Snider reek the distance from the well to the creek is more than 0.25 miles.

The Rogue River is a regional ground water discharge area. The nearest river reach is near Dodge Bridge (Hwy 234) between river mile 138 and 139. However, no potential for substantial interference can be assumed given the distance from the well to the river is more than 0.25 miles. Additionally, establishing a hydraulic connection can not be established for the reach at this time given ground water – surface water observations by Young (1961) for the Dodge Bridge vicinity.

Water Availability Basin the well(s) are located within:

C3a.	690-09-040 (4): Evaluation of stream impacts for each well that has been determined or assumed to be hydraulically
	connected and less than 1 mile from a surface water source. Limit evaluation to instream rights and minimum stream flows
	that are pertinent to that surface water source, and not lower SW sources to which the stream under evaluation is tributary.
	Compare the requested rate against the 1% of 80% natural flow for the pertinent Water Availability Basin (WAB). If Q is not
	distributed by well, use full rate for each well. Any checked \(\subseteq box indicates the well is assumed to have the potential to cause
	PSI.

Well	SW #	Well < 1/4 mile?	Qw > 5 cfs?	Instream Water Right ID	Instream Water Right Q (cfs)	Qw > 1% ISWR?	80% Natural Flow (cfs)	Qw > 1% of 80% Natural Flow?	Interference @ 30 days (%)	Potential for Subst. Interfer. Assumed?

C3b. 690-09-040 (4): Evaluation of stream impacts by total appropriation for all wells determined or assumed to be hydraulically connected and less than 1 mile from a surface water source. Complete only if Q is distributed among wells. Otherwise same evaluation and limitations apply as in C3a above.

Saine eva	muuno	ii aiia iiiiit	ations ap	pry as in C3	i acove.					
	SW #		Qw > 5 cfs?	Instream Water Right ID	Instream Water Right Q (cfs)	Qw > 1% ISWR?	80% Natural Flow (cfs)	Qw > 1% of 80% Natural Flow?	Interference @ 30 days (%)	Potential for Subst. Interfer. Assumed?
							8			
							7			

Comments:	
The proposed well does not appear to be hydraulically connected with a stream less than one-	mile from the well site.
The un-named creek is less than one-mile from the proposed well site, but it is identified as in during certain times of the year.	termittent or seasonal, dry
The proposed well site is in the same drainage as Constance Creek located less than one-m site. However, OWRD staff surface water flow evaluation of Constance Creek during 200 flow as intermittent rather than perennial, dominated by precipitation with very litt contribution (see attached Ivan Gall memo dated 28 June 2004 written for ground water rigl and G-15943). Given that memo, a hydraulic connection can not be established at this time.	3-2004 observed the creek tle, if any, ground water
Snider Creek is more than one-mile from the proposed well site.	
The Rogue River is more than one-mile from the proposed well site.	

C4a. **690-09-040 (5):** Estimated impacts on **hydraulically connected surface water sources greater than one mile** as a percentage of the proposed pumping rate. Limit evaluation to the effects that will occur up to one year after pumping begins. This table encompasses the considerations required by 09-040 (5)(a), (b), (c) and (d), which are not included on this form. Use additional sheets if calculated flows from more than one WAB are required.

Non-D	istributed	Wells											
Well	SW#	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
		%	%	%	%	%	%	%	%	%	%	%	%
Well Q	as CFS												
Interfer	ence CFS												
Distril	outed Well	la											anders (A. de
Well	SW#	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
		%	%	%	%	%	%	%	%	%	%	%	%
Well Q	as CFS												
Interfer	ence CFS												
		%	%	%	%	%	%	%	%	%	%	%	%
Well Q	as CFS			,									8
Interfer	ence CFS												
		%	%	%	%	%	%	%	%	%	%	%	%
Well Q	as CFS												
Interfer	ence CFS												
		%	%	%	%	%	%	%	%	%	%	%	%
Well Q	as CFS												
Interfer	ence CFS												
(A) - T	otal Interf.				SOLEME ELLE		CHARLES AND A	ka .		CONTRACTORS			
	% Nat. Q												
(C) = 1	% Nat. Q												
(D) = (U > (C)												
$\mathbf{(D)} = \mathbf{(A)}$													
	/ B) x 100												

(A) = total interference as CFS; (B) = WAB calculated natural flow at 80% exceed. as CFS; (C) = 1% of calculated natural flow at 80% exceed. as CFS; (D) = highlight the checkmark for each month where (A) is greater than (C); (E) = total interference divided by 80% flow as percentage.

Basis for impact evaluation:	
There is no evaluation in this section for the un-named creek and Constance Creek given from the proposed well site and at this time both are identified as intermittent flow.	they are less than on-mile
from the proposed wen see and at this time both are identified as interimitent flow.	
There is no evaluation in this section for Snider Creek given the possibility that a small gro	
exists between Constance Creek and Snider Creek. A divide would make a hydraulic connec	
well and Snider Creek indirect. That makes interference calculations problematic with curre	nt tools for analysis.
The Rogue River is a regional ground water discharge area. However, there is no evaluate	ion in this section for the
Rogue River given the following. Treating the fractured rock as a porous media for the inte	
or may not be valid (see attached for range of transmissivity values derived from specific ca	
section 13, same section as the proposed well). Additionally, establishing with confidence a	hydraulic connection with
the nearby Rogue River reach (Dodge Bridge vicinity) is currently problematic given the gro	<u>und water – surface water</u>
observations by Young (1961) for the Dodge Bridge vicinity.	

C4b. 690-09-040 (5) (b) The potential to impair or detrimentally affect the public interest is to be determined by the Water Rights Section. C5. If properly conditioned, the surface water source(s) can be adequately protected from interference, and/or ground water use under this permit can be regulated if it is found to substantially interfere with surface water: i. The permit should contain condition #(s) ii. The permit should contain special condition(s) as indicated in "Remarks" below; C6. SW / GW Remarks and Conditions If a permit is issued, condition with 7B, 7N, 7J and a condition that requires the applicant to install and maintain a properly functioning, totalizing flow meter on the well, record monthly water use totals, and submitted the water use data annually to OWRD. Water Use Measurement, Recording And Reporting Conditions A. Before water use may begin under this permit, the permittee shall install a properly functioning totalizing flow meter. The permittee shall maintain the meter in good working order, shall keep a complete record of the amount of water used each month and shall submit a report which includes the recorded water use measurements to the Department annually or more frequently as may be required by the Director. Further, the Director may require the permittee to report general water use information, including the place and nature of use of water under the permit. B. The permittee shall allow the watermaster access to the meter; provided however, where the meter is located within a private structure, the watermaster shall request access upon reasonable notice.

Application: G-17215

Version: 08/15/2003

Date: 8 June 2009

Application: G-17215

References Used:
Gall, I. 2004. Observed Constance Creek Flows, Jackson, County, Oregon: OWRD memo from Ivan Gall to OWRD ground water application files G-15794 and G-15943 dated June 28, 2004, 2 p.
Hladky, F.R. 1992. Geology and mineral resources of the Shady Cove quadrangle, Jackson County, Oregon: Oregon Department of Geology and Mineral Industries Geologic Map Series map GMS-52, 1 plate.
McFarland, W.D. 1983. A description of aquifer units in western Oregon: U.S. Geological Survey Open File Report 82- 165, 35 p., 8 plates.
Theis, C.V. 1935. The relation between the lowering of the piezometric surface and the rate and duration of discharge of a well using ground water storage. American Geophysical Union Transactions, 16 annual meeting, vol. 16, pg. 519-524.
Vorhis, R.C. 1979. Transmissivity from pumped well data. Well Log, National Water Well Association newsletter, vol. 10, no. 11, Dec. 1979, pg. 50-52.
Wiley, T.J. and Hladky, F.R. 1991. Geology and mineral resources of the Boswell Mountain quadrangle, Jackson County, Oregon: Oregon Department of Geology and Mineral Industries Geologic Map Series map GMS-70, 1 plate.
Wells, F.G. and Peck, D.L. 1961. Geologic map of Oregon west of the 121 st meridian: U.S. Geological Survey Miscellaneous Geologic Investigations Map I-325.
Young, R.A. 1961. Hydrogeologic evaluation of streamflow records in the Rogue River basin, Oregon: U.S. Geological Survey Open File Report 61-176, 119 p., 2 plates.
Young, R.A. 1959. Ground-water resources of the Rogue River basin, Oregon: U.S. Geological Survey unpublished report, 158 p.
OWRD water availability analyses
Rogue Basin Program rules (OAR 690-515)
USGS Quadrangel Maps: Boswell Mtn and Shady Cove (1:24,000 scale)
Water well reports submitted as examples for the proposed well. Submitted were JACK 3456, JACK 55199, JACK 34626
Water well reports with specific capacity data for wells in T35S/R02W-sec 13
Wells with water level data: State observation well 1157 (JACK 34195), and nearby wells JACK 3466, JACK 55776, JACK 3509, and JACK 3427

D. <u>V</u>	VEI	LL CO	NSTRUC	TION, O	AR 690-	<u> 200</u>									
D1.		Well #:	1_		-	Logid:	proj	posed, n	ot yet c	construc	eted				
D2.		a.	review of field insp report of	s not meet f the well lo ection by _ CWRE pecify)	og;										
D3.		THE W a.	constitute comming permits the permits the	estruction des a health gles water fine loss of a he de-water pecify)	threat und from more artesian he ring of one	er Divisior than one g ad; e or more g	ground v	vater res	servoirs						
D4.		THE W	VELL cons	struction d	deficiency	is describ	ed as fo	ollows: _							
D5.			to the Enf	b.	original co I don't kno Section.		or most t standa and with	recent in recent	modifica e time o issuance	ation. of constr	uction. ((See we	ell casin	ng and s	seal) econstruction
		is filed	with the D	epartment	and appro	ved by the	Enforce	ement S	ection a	nd the C	round V	Vater Se	ection.		
TH	IS S	ECTIO	ON TO B	E COMP	LETED	BY ENFO	ORCE	MENT	PERSO	ONNE	Τ.				
D7.				deficiency											
Δ7.					nus ceen				, actions						
															, 200
			(Enforce	ment Section	on Signatu	ıre)			-						, 200
D8.		Route	to Water	Rights Sec	ction (atta	ich well re	econstru	etion lo	gs to th	is page).				



Water Resources Department

942 SW 6th Street Suite E Grants Pass, OR 97526 (541) 471-2886 FAX (541) 471-2876

TO:

File G-15794 Decker

File G-15943 Blandau

FROM:

Ivan Gall //

COPY:

Larry Menteer - Jackson County Watermaster

DATE:

June 28, 2004

SUBJECT:

Observed Constance Creek Flows, Jackson County, Oregon

This memo summarizes the results of several field visits that were conducted to observe Constance Creek stream flows. The purpose of the observations was to estimate the groundwater contribution to stream flow by looking for the presence or absence of flow following periods of time without precipitation. If groundwater was noticeably contributing to stream flow it would be necessary to consider Constance Creek hydraulically connected to the aquifer under a Division 9 review.

Constance Creek is a seasonal stream, generally going dry each year during the summer and fall months. Constance Creek flows generally south towards the Rogue River, and is composed of several small tributaries that flow across relatively gentle topography. Anecdotal information from staff and residents in the area indicates that Constance Creek generally flows following extended periods of precipitation. Following days or weeks of no rain, Constance Creek flows diminish significantly or stop.

The subject properties are located north and south of Beagle Road in Jackson County, Oregon, west of the Rogue River and southwest of Shady Cove. Topography slopes to the south towards Upper and Lower Table Rock. The bedrock in the area is composed of upper Eocene siltstone, mudstone, sandstone, conglomerate, and coal of the Payne Cliffs Formation. The original sediments were river deposited with the provenance believed to be local. The main stem of Constance Creek west of the site has deposited older quaternary alluvium. The subject well log notes "blue claystone" from 2 to 82 feet bgs. Overlying the bedrock are 2 feet of "black soil". Well logs in the vicinity of the subject site suggest that the depth to bedrock is approximately 2 to 10 feet. Ground water appears to be encountered in fractures ranging from 30 to 150 feet bgs.

Groundwater levels in area wells are generally shallow during the wet months, suggesting the potential for groundwater to discharge into the creek. The overlying soil has a high clay content and soil permeability is likely to be very low. This would minimize connection between the stream and underlying aquifer. However, at some locations in Constance Creek, bedrock is visible in the streambed.

Constance Creek flows were observed on the following dates, generally in several locations (three tributaries along Beagle Road, Dodge Road, and Glass Road). Stream flow measurements were not taken due to staff time limitations.

Date:	Observation:	Staff:
October 30, 2003	No flow	Stanford
December 10, 2003	No flow	Gall, Stanford, Haynes
January 2, 2004	Flowing	Chapman, Stanford
January 30, 2004	Flowing	Chapman, Stanford
March 17, 2004	Flowing	Chapman
April 4, 2004	Flowing	Chapman
April 13, 2004	Flowing, very limited	Gall

No visits were conducted after April 13, 2004, as precipitation was negligible, and the stream flow on April 13 was nearly zero.


A summary of monthly precipitation totals as measured at the Medford Airport is provided below. Daily precipitation values are available.

Month:	Precipitation* (inches):	Departure from Normal* (inches):
September 2003	0.86	0.08
October 2003	0.05	-1.26
November 2003	2.38	-0.55
December 2003	4.67	1.77
January 2004	2.98	0.51
February 2004	3.35	1.25
March 2004	1.27	-0.58
April 2004	0.75	-0.56
May 2004	1.27	0.06


^{*}Data Source Oregon Climate Service Web Page

Staff field observations between October 2003 and April 2004 suggest that stream flow in Constance Creek is dominated by precipitation. Any groundwater contribution to stream flow is minimal and of a short-term nature. No groundwater discharge occurs into Constance Creek near the applicants' properties during the dry months, as the stream is dry.

Limitations on staff resources did not allow location of wells and collection of water level elevation data to assess aquifer responses to precipitation, hydraulic gradients, and compare stream stage with aquifer levels. Quantitative stream flow measurements also were not collected due to staff limitations. These data would provide a more comprehensive evaluation of aquifer and stream interaction. However, I feel that the staff field observations are sufficient to remove Constance Creek from consideration in Division 9 reviews for groundwater rights in this area. If future data are gathered that change the conceptual model of the area, or indicate that surface and groundwater have a greater degree of interaction, then Constance Creek may need to be considered for a Division 9 review for future groundwater rights.



Ground Water Application G-17215 Julie Moore



0 0.5 1 2 Miles

Yellow = Proposed Well Red & Blue = Other Wells



Green = Surface Water Rights

Pump Rate Drawdown Total gpm feet	Total	Time Total hours	Specific_Capacity gpm/foot	Transmissivity ft2/day	Transmissivity gpd/ft	Method
33	П	-	1.52	302.26	2,261,04	Bailer
10	1	-	3.00	51.74	387.00	Bailer
88	1	- ,	98.0	66.53	497.67	Bailer
200		- 0	9.5	42.35	310.77	Baller
30	100	5.0	200	204.00	1 526 71	Bailer
74		1	0.26	43.61	326.19	Bailer
30		-	0.53	97.12	726.50	Bailer
73		-	0.27	46.83	350.30	Bailer
9		-	1.00	192.58	1,440.63	Bailer
95		-	0.53	95.72	716.07	Bailer
51		0.5	0.24	36.86	275.80	Bailer
13		2	7.69	1,828.30	13,676.64	Bailer
22		-	4.56	989.34	7,400.74	Bailer
36		-	0.42	74.15	554.69	Bailer
65		-	0.46	82.93	620.35	Bailer
52		-	1.45	289.18	2,163,23	Bailer
36		0.5	0.28	44.29	331.33	Bailer
28		-	0.36	62.64	468.54	Bailer
70		1.5	0.29	50.98	381.37	Bailer
61		1	0.21	35.52	265.74	Bailer
17		1.5	4.71	1,058.34	7,916.95	Bailer
120		1.5	0.21	36.07	269.82	Bailer
110		2	90:0	10.05	75.20	Bailer
27		0.5	0.56	95.09	711.30	Bailer
99		0.5	0.22	33.41	249.95	Bailer
75		0.5	0.23	36.52	273.16	Bailer
		Maximum	7.69	1,828.30	13,676.64	
		Minimum	0.06	10.05	75.20	
	-	Mean/Average	1.15	221.25	1,655.06	
	_	- Gninian Indian				