

## MITIGATION CONDITIONS

File # P- 83089

Date 11.7.97

DWF

### Oregon Department of Fish and Wildlife Conditions

- \_\_\_\_\_ In accordance with ORS 498.268 and ORS 509.605, install, maintain, and operate bypass devices as required by the Oregon Department of Fish and Wildlife that will provide adequate upstream passage for fish. (SMBS)
- \_\_\_\_\_ Install, maintain, and operate fish screening devices as required by the Oregon Department of Fish and Wildlife to prevent fish from entering the diversion. (SMSS)
- \_\_\_\_\_ The reservoir owner is required to by-pass flows from \_\_\_\_\_ through \_\_\_\_\_ (BPC)

### Water Right Related Conditions

- \_\_\_\_\_ The pond may be filled one time only per year. No diversion of water to storage can occur during times all water rights are not met on the John Day river System. (KR1)
- \_\_\_\_\_ If required by the Watermaster, the water user shall install and maintain a headgate, an in-line flow meter, weir, or other suitable device for measuring and recording the quantity of water diverted. The type and plans of the headgate and measuring device must be approved by the Watermaster (Department). (KR2)
- ✓ \_\_\_\_\_ Live stream flow must be passed when required to satisfy existing water rights. In order to substantiate live flow is being passed, measuring devices may be required. (J)
- \_\_\_\_\_ Live flow must be by-passed all year. (BSD)
- \_\_\_\_\_ Any secondary use of stored water is limited each year to the capacity of the reservoir. (BSD2)
- \_\_\_\_\_ The water user shall install and maintain a headgate, an in-line flow meter, weir, or other suitable device for measuring and recording the quantity of water diverted. The type and plans of the headgate and measuring device must be approved by the Department prior to beginning construction and shall be installed under the general supervision of the Department.