Groundwater Application Review Summary Form

Application # G- <u>18795</u> GW Reviewer Ben Scandella, Justin Iverson Date Review Completed: 3/31/2020 Summary of GW Availability and Injury Review: Groundwater for the proposed use is either over appropriated, will not likely be available in the amounts requested without injury to prior water rights, OR will not likely be available within the capacity of the groundwater resource per Section B of the attached review form. Summary of Potential for Substantial Interference Review: There is the potential for substantial interference per Section C of the attached review form. **Summary of Well Construction Assessment:** ☐ The well does not appear to meet current well construction standards per Section D of the attached review form. Route through Well Construction and Compliance Section. This is only a summary. Documentation is attached and should be read thoroughly to understand the basis for determinations and for conditions that may be necessary for a permit (if one is issued).

Version: 03/36/2020

WATER RESOURCES DEPARTMENT

MEM	0							_3	3/31/202	0_		
TO:		Applica	tion G-	18795								
FROM	И:	GW: Ben Scandella, Justin Iverson (Reviewer's Name)										
SUBJ	ECT: S	cenic Wa	aterway	Interf	erence l	Evaluat	ion					
	YES NO		source of		-	is hydr	aulically	y connec	cted to a	a State S	Scenic	
	 □ YES □ NO Use the Scenic Waterway Condition (Condition 7J) 											
	interfer	RS 390.8 rence with rence is d	h surfac	e water	that con							
	Per ORS 390.835, the Groundwater Section is unable to calculate ground water interference with surface water that contributes to a scenic waterway; therefore, the Department is unable to find that there is a preponderance of evidence that the proposed use will measurably reduce the surface water flows necessary to maintain the free-flowing character of a scenic waterway											
Calcule per crit the Dep Exerci	nte the per eria in 39 partment is ise of thi way by	ON OF Incentage of 0.835, do not be sunable to the following flow is re-	consump not fill in make a l is calcu wing an	tive use b the table Preponde lated to	y month of but check rance of reduce	k the "und Evidence monthly	ible" option finding. V flows	on above, in <u>[Ente</u>	thus info	orming W	ater Righ	its that
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	

Version: 03/36/2020

PUBLIC INTEREST REVIEW FOR GROUNDWATER APPLICATIONS

TO: FROM:								Date3/31/2020 candella, Justin Iverson								
SUBJE				8795		Reviev	ver's Nam	ie	ew of							
						1				.8	D	ate of Revi	ew(s)			
OAR 69 welfare, to deterr the presu	90-310-130 safety and mine wheth umption co	0 (1) The d health her the priteria. T	e Departm as describ presumption This review	oed in ORS 5 on is establis w is based u	esume that 37.525. De hed. OAR pon availa	a proposed epartment s 690-310-14 ble inforn	d ground taff rev 40 allov nation a	iew g vs the	er use will en groundwater e proposed us gency polici	applica se be m ies in p	tions und odified of lace at t	der OAR or conditi he time (690-310 oned to n	-140 neet tion.		
A. <u>GE</u> . A1.	Applicant(s) seek(s)															
A2. A3.			Irrig	ation of 10 a	cres	Seaso	nality:		ril 1 through			ıder logi	d):			
Well	Well#					Propo Rate(o	e(cfs) (T/R-S QQ-				Location, metes and bounds 2250' N, 1200' E fr NW cor 2598' N, 1442' E fr SW cor					
2 3 4 5																
* Alluviu	ım, CRB, B	Bedrock		•												
Well	Well Elev ft msl	First Water ft bls 20	SWL ft bls	SWL Date 9/5/2008	Well Depth (ft) 80	Seal Interval (ft) 0-19	Casi Interv (ft) 2-7.	als	Liner Intervals (ft) N/A	Or S	rations creens ft) 5-77.7	Well Yield (gpm) 200	Draw Down (ft) N/A	Test Type Air		
Use data	from applic	cation for	proposed	wells.												
A4.	Provisio managem (Not all b	ons of the nent of goasin rule	25 cfs (56 e North Croundwaters contain	gpm). For t	he remaind	ler of this r	eview, a Basin	a max n rule er [num allowed ximum rate of the series relative to are, or are,	of 0.125 the dev	elopmer , activat	assumed nt, classif ed by this	ication ar s applicat	nd/or ion.		
A6. 🗌	Name of	adminis ts:	trative are	a:					s) an aquifer							

Date: 3/31/2020

B. GROUNDWATER AVAILABILITY CONSIDERATIONS, OAR 690-310-130, 400-010, 410-0070

B1.	Bas	sed upon available data, I have determined that groundwater* for the proposed use:
	a.	is over appropriated, is not over appropriated, or ⊠ cannot be determined to be over appropriated during any period of the proposed use. * This finding is limited to the groundwater portion of the over-appropriation determination as prescribed in OAR 690-310-130;
	b.	will not or will likely be available in the amounts requested without injury to prior water rights. * This finding is limited to the groundwater portion of the injury determination as prescribed in OAR 690-310-130;
	c.	\square will not or \boxtimes will likely to be available within the capacity of the groundwater resource; or
	d.	will, if properly conditioned, avoid injury to existing groundwater rights or to the groundwater resource: i. The permit should contain condition #(s); ii. The permit should be conditioned as indicated in item 2 below. iii. The permit should contain special condition(s) as indicated in item 3 below;
B2.	a.	Condition to allow groundwater production from no deeper than ft. below land surface;
	b.	Condition to allow groundwater production from no shallower than ft. below land surface;
	c.	Condition to allow groundwater production only from the groundwater reservoir between approximately ft. and ft. below land surface;
	d.	■ Well reconstruction is necessary to accomplish one or more of the above conditions. The problems that are likely to occur with this use and without reconstructing are cited below. Without reconstruction, I recommend withholding issuance of the permit until evidence of well reconstruction is filed with the Department and approved by the Groundwater Section.
		Describe injury —as related to water availability— that is likely to occur without well reconstruction (interference w/ senior water rights, not within the capacity of the resource, etc):

B3. Groundwater availability remarks:

The proposed POA, COLU 53662, obtains groundwater from recent alluvium deposited by the Columbia River system. Water levels in many nearby well logs are reported to be within a few feet of ground surface, even during drier summer months, due to an extensive network of surface water features (canals and sloughs) located in this lowland area that are connected to the alluvial aquifer.

Furthermore, existing groundwater exploitation appears minimal in the area. The nearest groundwater right is Permit G-17247, for a shallow sump located about 3200 ft to the NE, and large tax lots suggest that neighboring domestic wells are also relatively distant. For this reason, there is minimal groundwater level data available; the next nearest well measurement in the OWRD database is from COLU 55222, about 6 miles to the east. The low allowed allocation, coupled with the surface-and groundwater rich environment and dearth of existing users, suggests that injury to any nearby users is highly unlikely.

C. GROUNDWATER/SURFACE WATER CONSIDERATIONS, OAR 690-09-040

C1. **690-09-040 (1):** Evaluation of aquifer confinement:

Well	Aquifer or Proposed Aquifer	Confined	Unconfined
1	Alluvium	\boxtimes	

Date: 3/31/2020

Basis for aquifer confinement evaluation: The water level reported in the well log for COLU 53662 is 8 feet above the top of the water-bearing zone, indicating confined conditions.

C2. **690-09-040** (2) (3): Evaluation of distance to, and hydraulic connection with, surface water sources. All wells located a horizontal distance less than ¼ mile from a surface water source that produce water from an unconfined aquifer shall be assumed to be hydraulically connected to the surface water source. Include in this table any streams located beyond one mile that are evaluated for PSI.

Well	SW #	Surface Water Name	GW Elev ft msl	SW Elev ft msl	Distance (ft)	Hydraulically Connected? YES NO ASSUMED	Potential for Subst. Interf Assumed? YES	er.
1	1	Westport Slough	-5	5	370			\boxtimes

Basis for aquifer hydraulic connection evaluation: Groundwater elevation is roughly coincident with surface water, indicating hydraulic connection. The shallow clay layer apparently creates confined or semi-confined conditions in the water-bearing zone accessed by this well, but there is no known geologic feature providing a barrier to hydraulic connection at this distance in the alluvial aquifer system.

There are several other surface water features located within 1 mile of the proposed POA that are hydraulically connected to the alluvial aquifer system. However, none of these are in a natural, free-flowing state; instead, all are part of an extensive network of excavated canals which both intersect and interconnect the sloughs. Consequently, PSI was not evaluated for any of these surface water features.

Water Availability Basin the well(s) are located within: This well is outside of any WAB, and the hydrogeologic setting suggests that significant impacts will not extend into the WABs in the Marine Sedimentary aquifer system to the south. Therefore, Columbia River Basin water availability will apply.

C3a. 690-09-040 (4): Evaluation of stream impacts for each well that has been determined or assumed to be hydraulically connected and less than 1 mile from a surface water source. Limit evaluation to instream rights and minimum stream flows that are pertinent to that surface water source, and not lower SW sources to which the stream under evaluation is tributary. Compare the requested rate against the 1% of 80% natural flow for the pertinent Water Availability Basin (WAB). If Q is not distributed by well, use full rate for each well. Any checked box indicates the well is assumed to have the potential to cause PSI.

Well	SW #	Well < 1/4 mile?	Qw > 5 cfs?	Instream Water Right ID	Instream Water Right Q (cfs)	Qw > 1% ISWR?	80% Natural Flow (cfs)	Qw > 1% of 80% Natural Flow?	Interference @ 30 days (%)	Potential for Subst. Interfer. Assumed?
1	1	\boxtimes		N/A	N/A		N/A		<25%	\boxtimes

Page

Date: 3/31/2020

C3b.	690-09-040 (4): Evaluation of stream impacts by total appropriation for all wells determined or assumed to be hydraulically
	connected and less than 1 mile from a surface water source. Complete only if Q is distributed among wells. Otherwise same
	evaluation and limitations apply as in C3a above.

	SW #	Qw > 5 cfs?	Instream Water Right ID	Instream Water Right Q (cfs)	Qw > 1% ISWR?	80% Natural Flow (cfs)	Qw > 1% of 80% Natural Flow?	Interference @ 30 days (%)	Potential for Subst. Interfer. Assumed?
-									

Comments: Using the Hunt, (2003) model and parameters appropriate for the hydrogeologic setting (Freeze and Cherry, 1979), streamflow depletion at 30 days is estimated to be likely less than 25% (see model parameters and results below).

C4a. **690-09-040 (5):** Estimated impacts on **hydraulically connected surface water sources greater than one mile** as a percentage of the proposed pumping rate. Limit evaluation to the effects that will occur up to one year after pumping begins. This table encompasses the considerations required by 09-040 (5)(a), (b), (c) and (d), which are not included on this form. Use additional sheets if calculated flows from more than one WAB are required.

	stributed												
Well	SW#	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
		%	%	%	%	%	%	%	%	%	%	%	9/6
Well Q	as CFS												
Interfere	ence CFS												
territoria de la composição de la compos													
	uted Wells	S											
Well	SW#	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
		%	%	%	%	%	%	%	%	%	%	%	9/0
Well Q	as CFS												
Interfere	ence CFS												
	al and property in the	ties the same the		trefferendigt of the			300000000000000000000000000000000000000	September 1990	ELIE-ELIPS ELICHE				
$(\mathbf{A}) = \mathbf{To}$	tal Interf.												
(B) = 80	% Nat. Q												
(C) = 1	% Nat. Q												1
		and the areas		174 1743		National Control	in all an officer						
$(\mathbf{D}) = (A$	A) > (C)	√	✓	√	√	√	√	√	√	✓	\checkmark	✓	/
$(\mathbf{E}) = (\mathbf{A} / \mathbf{E})$	B) x 100	%	%	%	%	%	%	%	%	%	%	%	%

(A) = total interference as CFS; (B) = WAB calculated natural flow at 80% exceed. as CFS; (C) = 1% of calculated natural flow at 80% exceed. as CFS; (D) = highlight the checkmark for each month where (A) is greater than (C); (E) = total interference divided by 80% flow as percentage.

Basis for impact evaluation: PSI was assumed because the well is hydraulically connected with Westport Slough and located less than ¼ mile away, as per OAR 690-009-040 (4) (a).

C4b. 690-09-040 (5) (b) The potential to impair or detrimentally affect the public interest is to be determined by the Water Rights Section.

5. If properly conditioned, the surface water source(s) can be adequately protected from interference, and/or groundwater use
under this permit can be regulated if it is found to substantially interfere with surface water:
i. The permit should contain condition #(s);
ii. The permit should contain special condition(s) as indicated in "Remarks" below;
6. SW / GW Remarks and Conditions:

References Used:

Application G-18795

OWRD Groundwater Information System and Well Log Databases, accessed 3/31/2020.

Freeze, R.A. and J.A. Cherry, 1979. Groundwater. Prentice-Hall, Englewood Cliffs, N.J.


Hunt, B., 2003. Unsteady Stream Depletion When Pumping from Semiconfined Aquifer. Journal of Hydrologic Engineering 8:12-19.

Version: 05/07/2018

D. WELL CONSTRUCTION, OAR 690-200


D1.	Well #:	Logid:	
D2.	a.	LL does not appear to meet current well constructions of the well log; all disspection by	action standards based upon:
	c. \square re	port of CWRE	/
D3.	· -		described as follows:
D4.	☐ Route to t	the Well Construction and Compliance Section	for a review of existing well construction.

Water-Level Measurements in Nearby Wells



Date: 3/31/2020

Application G-18795 (Reed): T7N / R5W S4



Stream Depletion Modeling Results:

Application type:
Application number:
Well number:
Stream Number:
Pumping rate (cfs):
Pumping duration (days):
Pumping start month number (3=March)


G	
18795	
1	
1	
0.125	
101	
3.0	

Date: 3/31/2020

Parameter	Symbol	Scenario 1	Scenario 2	Scenario 3	Units
Distance from well to stream	a	370	370	370	ft
Aquifer transmissivity	Т	1000	300	100	ft2/day
Aquifer storativity	S	0.001	0.005	0.01	-
Aquitard vertical hydraulic conductivity	Kva	0.01	0.05	0.1	ft/day
Aquitard saturated thickness	ba	20	15	10	ft
Aquitard thickness below stream	babs	15	10	5	ft
Aquitard specific yield	Sya	0.1	0.05	0.02	-
Stream width	ws	100	120	140	ft

Stream depletion for Scenario 2:

Days	10	330	360	30	60	90	120	150	180	210	240	270	300
Depletion (%)	10	6	6	17	25	31	22	17	14	11	10	8	7
Depletion (cfs)	0.01	0.01	0.01	0.02	0.03	0.04	0.03	0.02	0.02	0.01	0.01	0.01	0.01



Approved: The He

MEMO

To: Kristopher Byrd, Well Construction and Compliance Section Manager

From: Travis Kelly, Well Construction Program Coordinator

Subject: Review of Water Right Application G-18795

Date: April 8, 2020

The attached application was forwarded to the Well Construction and Compliance Section by the Ground Water Section. Ben Scandella and Justin Iverson reviewed the application. Please see Ben and Justin's Groundwater Review and the Well Log.

Applicant's Well #1 (COLU 53662): Based on a review of the Well Report, Applicant's Well #1 seems to protect the groundwater resource.

The construction of Applicant's Well #1 may not satisfy any hydraulic connection issues.



STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765 & OAR 690-205-0210)



WELL LABEL # L	88685
START CARD #	159614

(1) LAND OWNER Owner Well I.D.	(9) LOCATION OF WELL (legal description)
First Name David Last Name Rieben	County COLUMBI: Twp 7 N N/S Range 5 W E/W WM
Company	Sec 4 NE 1/4 of the SW 1/4 Tax Lot 01200
Address 12230 Marshland Road	Tax Map Number Lot
City Clatskanie State OR Zip 97016	Lat ° ' " or DMS or DD
(2) TYPE OF WORK New Well Deepening Conversion	Long OMS or DD
	Street address of well Nearest address
Alteration (repair/recondition) Abandonment	
(3) DRILL METHOD	12230 Marshland Road, Clatskanie, Oregon 97016
Rotary Air Rotary Mud Cable Auger Cable Mud	(10) STATIC WATER LEVEL Date SWL(psi) + SWL(ft)
Reverse Rotary Other	
(4) PROPOSED USE Domestic Irrigation Community	Existing Well / Predeepening Completed Well 19-05-2008 5.3 X 12.2
Industrial/Commericial Livestock Dewatering	Completed Well 09-05-2008 5.3 X 12.2 Flowing Artesian? Dry Hole?
Thermal Injection Other	
(5) BORE HOLE CONSTRUCTION Special Standard Attach copy)	WATER BEARING ZONES Depth water was first found 201
Depth of Completed Well 77.67 ft.	SWL Date From To Est Flow SWL(psi) + SWL(ft)
BORE HOLE SEAL sacks/	
Dia From To Material From To Amt Ibs	
10 0 19 Bentonite 0 19 12 S	
6 19 80	
	(11) WELL LOG Ground Elevation
How was seal placed: Method A B C D E	Material From To
XOther Poured	TOP SOIL 0 1
Backfill placed fromft. toft. Material	CLAY GRAY-BROWN I 10
Filter pack from ft. to ft. Material Size	SILTY SAND BLUE 10 51
Explosives used: Yes Type Amount	SILTY SAND W/WOOD 51 69
	SAND GRAY-BLUE MED-FINE 69 80
(6) CASING/LINER Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd	
	RECEIVED
Shoe Inside Outside Other Location of shoe(s) 73	HEGEIVED
Temp casing X Yes Dia 10 From 1 To 19	CFD 1 = 2000
(7) PERFORATIONS/SCREENS	2EP 1 3 2000
Perforations Method	WATER RESOURCES DEPT
Screens Type Telescoping Material S. Steel	SALEM, OREGON
Pert/S Casing/ Screen Scrn/slot Slot # of Tele/	Date Started 09-05-2008 Completed 09-05-2008
creen Liner Dia From To width length slots pipe size	Date Started 09-05-2008 Completed 09-05-2008
Screen 6 72.5 77.67 16	(unbonded) Water Well Constructor Certification
	I certify that the work I performed on the construction, deepening, alteration, or
	abandonment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to
	the best of my knowledge and belief.
(8) WELL TESTS: Minimum testing time is 1 hour	License Number Date
Pump Bailer Air Flowing Artesian	Password: (if filing electronically)
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)	Signed
200 72 1	(bonded) Water Well Constructor Certification
	I accept responsibility for the construction, deepening, alteration, or abandonment
	work performed on this well during the construction dates reported above. All work
Temperature 52 °F Lab analysis Yes By	performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best of my knowledge and belief.
Water quality concerns? Yes (describe bacceve) From To Describe Amount Units	
	License Number 1646 Date 09-12-2008 Password: (if filing electronically)
0CT 1 7 2008	Signed Chris McGhee Chrk MM
UCI 1 / PET	Contact Info (optional)