The original and first space of this report are to be filled with the

State Well No. 6/3w-13bde

STATE OF OREGON—
STATE ENGINEER, SALEMFOREGON PIONE NGINEER (Please type or print)
within 30 days from the date LEM OREGON(Do not write above this line)
of well completion, SALEM OREGON(Do not write above this line)

State Permit No.

of well completion.	<u>G 5089</u>
(1) OWNER:	(11) LOCATION OF WELL:
Name William Downer	County Marion Driller's well number 1297
Address 9700 River Road NE Salem, Oregon	14 % fleation 13 T. 65 R. 5W W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well II Deepening [Reconditioning [Abandon [
If abandonment, describe material and procedure in Item 12.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of well below casing
Rotary Driven Domastic Dindustrial Municipal	Depth drilled 340 st. Depth of completed well 340 st
Dug 🗓 Bored 🗋 Irrigation 🔁 Test Well 🗍 Other 🗌	Formation: Describe color, texture, grain size and structure of materials
CASING INSTALLED: Threaded Welded W	and show thickness and nature of each stratum and aquifer penchated with at least one entry for each change of formation. Report each change in position of Static Water Lovel as drilling proceeds. Note drilling rates
" Diam from ft. to ft. Gage	MATERIAL Prom To SWL
7 Diam. fromft. toft. Gage	Top Soil 0 2
PERFORATIONS: Perforated! Fr Yes O No.	Brown Clay 2 40
	Blue Clay 40 75
A 17 (a	Black sand & Gravel 75 85
Size of perforations 2 in by 5/8 in. 510 perforations from A5 in to 189 in.	Brown sand sisyx& gravel 85 100
perforations from ft to ft.	Brown sand clay & gravel 100 140 40
perforations from ft. to ft.	
perforations from	
perforations from	
(E) DONESNIC.	
(7) SCREENS: Well screen installed! Yes No	
Manufacturer's Name Model No.	The state of the s
Diam Blot size Set from # to #	RECEIVED
Diam. Slot size	ADD 0 0 0007
	APR 3 0 2007
(8) WATER LEVEL: Completed well.	WATER RESOURCES DEPT
Static level 40 ft. below land surface Date 4-1-68	- SALEM; OREGON
American pressure libs, per square inch Date	
(9) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a nump test made! El Yes No Myes, by whom! Drillar	
mold: 400 gal./min. with 43 ft. drawdown after 4 hrs.	Work started March 11,1968 Completed April 1, 1866
500 45 4 4	Date well drilling machine moved att of well April 1. 68 18
* * * * * * * * * * * * * * * * * * *	Drilling Machine Operator's Certification:
Bailor test gal./min. with ft, drawdown after hrs.	This well was constructed under my direct supervision. Materials used and information reported above are true to my bes
Artesian flow g.p.m. Date	knowledge and belief.
Temperature of water 55 Was a chemical analysis made? Yes No	[Signed] The Best Date 4-2-88, 19
	(Drilling Machine Operator)
(10) CONSTRUCTION:	Drilling Machine Operator's License No151
Well seal-Material useDrill cuttings Puddle clay	
M 4	Water Well Contractor's Cartification:
Abbuilture of here part to handle 44 hour human min	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Were any loose strata comented off (Yes 2 No Depth	NAME WILLAMETTE DETLLING COMPANY
Did any strata contain unusable water? Nes No	(Ferson, firm or corporation) (Type of print)
	Address 7641 35th Ave. NE Salem, Oregon
Type of water? depth of strata	(a) (b) (D)
Method of sealing strate off	[Signed]
Was well gravel packed? ☐ Yes 🏋 No Size of gravel:	(Water Well Contractor)
Gravel placed from	Contractor's License No. 2 Date 4-2-68

(USE ADDITIONAL SHEETS IF NECESSARY)