

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

FEB 19 1980

STATE OF OREGON

(Please type or print)

State Well No.

State Permit No.

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER RESOURCES DEPT

SALEM, OREGON

(1) OWNER:

Name Russell Hill
Address 13831 ADMIRALTY WAY
LYNNWOOD WASH. 98036

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Driven ☐
Jettied ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED:

Threaded ☐ Welded ☒
8 in. Diam. from 0 ft. to 60 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name

Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

Is a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

Per test 5 gal./min. with 20 ft. drawdown after 2 hrs.

Artesian flow g.p.m.

Temperature of water 54 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement (CEMENT)

Well sealed from land surface to 23 ft.

Diameter of well bore to bottom of seal 12 in.

Diameter of well bore below seal 8 in.

Number of sacks of cement used in well seal 17 sacks

Number of sacks of bentonite used in well seal NONE sacks

Brand name of bentonite placed Wagner pump

Number of pounds of bentonite per 100 gallons

of water lbs./100 gals.

Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Time of water depth of strata

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County DESCHUTES Driller's well number
SEKIN NEWS Section 5 T. 20 R. 16 W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 428 ft.
Static level 428 ft. below land surface. Date 10/4/79
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8
Depth drilled 145 ft. Depth of completed well 445 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
BROWN ROCK	0	90	
SANDSTONE	90	198	
CLAY	198	325	
SANDSTONE & CLAY	325	428	
GRAVEL AND SAND	428	445	

RECEIVED

NOV - 5 1979

WATER RESOURCES DEPT
SALEM, OREGON

RECEIVED
FEB 6 1980
WATER RESOURCES DEPT
SALEM, OREGON

Work started JULY 23 19 79 Completed SEPT 31 19 79

Date well drilling machine moved off of well OCT 15 19 79

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] Kenneth Mathers Date NOV 2, 1979
(Drilling Machine Operator)

Drilling Machine Operator's License No. 245

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name MATHERS & SON
(Person, firm or corporation) (Type or print)

Address 63469 OB RILEY RD

[Signed] BEN DOBSON Date NOV 2, 1979
(Water Well Contractor)

Contractor's License No. 245 Date NOV 2, 1979

WATER RESOURCES DEPT
SALEM OREGON

(USE ADDITIONAL SHEETS IF NECESSARY)

SP-45066-110