

# OWRD Stream Gaging Network Evaluation

for Water Distribution

Jonathan La Marche  
Hydrologist, PE



Photo: G. White



# Overall Gage Network Evaluation Project Review

## What?

Evaluation of the OWRD (and related) stream gaging network as it pertains to the defined agency goals.

## Why?

- Oregon specific gage network was last formally evaluated by USGS in 1970 (no management component).
- Changes to water science and management related needs have occurred since last formal Oregon evaluation.
- Does current gaging network meet OWRD goals?
- Find optimum network given constraints.



# Overall Project Review

**OWRD operates gages for two primary purposes**

- **Science**  
multiple agency goals
- **Water Management**  
multiple agency goals
  - **Water Distribution and Regulation**



# Stream Gaging Network Water Distribution Evaluation: Existing Stream Gaging


10 0 10 20 30 40 50  
Miles  
Oregon Lambert Coordinate Reference System  
(EPSG #4962)

**DISCLAIMER**  
This product is for informational purposes and may not have been prepared for, or be suitable for legal engineering, or surveying purposes. Users of this information should review or consult the primary data and information sources to ascertain the usability of the information.



**Legend**

- Other Gages
- OWRD Gages
- Streams
- City
- Basins



OWRD, 11/22/2010, J. LeMarche (A GIS (m)) / state 2010, GageNetworkEval\_V1.mxd

# Gage network evolution\*

\*related to water distribution needs

## Inherited regulation and monitoring scheme:

- **Complaint Driven**

High Competition >> Increased Monitoring

- **Resource constrained**

Cooperator Funding >> Increased Monitoring

- **Beneficial Use**

Put all waters to beneficial use. no ISWRs

- **GW/SW interactions**

Generally not considered. Unknown interactions or unknown implications for water distribution.



# Gage network evolution\*

\*related to water distribution needs

## Current regulation and monitoring pressures:

- **ISWRs**  
(including IS\_XFR common in Salmonid streams)
- **Increased water right complexity.**  
(e.g., permit conditions commonly related to limited supply)
- **GW/SW interactions.**  
(e.g., water management implications)
- **Increasing demand**  
(e.g., population pressures or climate change)
- **Increasing supply pressures**  
(e.g., ASR)





# Gage network evolution\*

\*related to water distribution needs

## Result of current monitoring pressures:

More real time monitoring needs for effective water distribution in the face of growing demand and finite supply.



# Current gage network heterogeneity due to:

## **Fish, Flows, and Funds: FFF(*w*)**

Explains most of variation in gage network for water distribution.

### **Fish:**

Salmonids? Typically related to IS\_XFR activity and outside interests in flow/diversions.

### **Flows:**

Supply relative to demand.

### **Funds:**

Cooperators enhance monitoring.

### ***Watermaster:***

Inherited gages and sets local monitoring priorities.






# Explanation

## Gage

### Operator

- USGS
- OWRD
- USACE
- Douglas County
- Idaho Power
- USBR/OWRD
- USGS/OWRD
- USBR
- USGS/USACE
- Other
- Unknown
- OWRD Administrative Basin
- City

# Existing Gage Network



DISCLAIMER & CONTACT INFO  
 This product is for informational purposes and may not have been prepared for or be suitable to help implement or improve operations. Users of this information should consult with the primary data and information sources to establish the usability of the information.  
 This map is produced by the Oregon Water Resources Department from digital data. Any errors or omissions in the data should be identified by the originating data provider. The Oregon Water Resources Department is not responsible for the use of this information for any purposes, or liability for the use of this information.  
 Mailing address:  
 700 Summer St. NE, Suite 4  
 Salem, OR 97301-1200  
 Web address:  
 www.oregon.gov/owrd



# Evaluating the network

This presentation covers OWRD gaging needs for water distribution only.

- All active gages (OWRD and non-OWRD).
- Monitoring alternatives to gaging.
- Gaging needs for water distribution related to
  - ISWRs and IS\_XFRs
  - Diversions on high regulation streams
  - Watersheds where  $CU > NF$
  - Large diversions and storage
  - GW/SW interactions



Photo: Gary White





# Methods



## Qualitative criteria: survey and interview based on:

- OWRD databases
- Areas of known or suspected GW/SW interactions.
- Field and technical staff knowledge, experience and analysis.
- Gaging needs considered without resource constraints.
- Monitoring alternatives to gaging also considered.



Photo: J. La Marche



# Stream Gaging Network Evaluation: Expected High Management Areas

10 0 10 20 30 40 50 Miles  
Oregon Lambert Coordinate Reference System  
(EPSG #2892)

**DISCLAIMER**  
This product is for informational purposes and may not have been prepared for, or be suitable for legal engineering, or surveying purposes. Users of this information should review or consult the primary data and information sources to ascertain the usability of the information.




**Number of regulatory actions (2002-2007)**

- 1 - 10
- 11 - 25
- 26 - 50
- 51 - 100
- 101 - 250
- 251 - 1000
- > 1000

Streams with instream transfer or lease activity (WY 2008)

Watersheds with zero expected summer flow (CU > NF)

Counties



—OWRD, 11/23/2010, J. LaMarche (& GIS (1)), state\_2010\_GageNetworkEval\_v1.mxd

126° 124° 123° 122° 121° 120° 119° 118° 117°

# Results

## Stream Gaging for Surface Water Distribution

- General hydrologic and regulatory setting narrative written for each watermaster district.
- Over 900 watersheds, stream reaches, storage facilities and diversions were examined.
- 225 gaging locations identified to meet OWRD surface water distribution goal. 155 of these locations currently have gages.
- 70 new stream gages needed. 31 of these were deemed high priority due to regulatory, environmental, and logistical setting.





# Stream Gaging Network Management Evaluation: Recommended Changes



**DISCLAIMER**  
This product is for informational purposes and may not have been prepared for, or be suitable for legal, engineering, or surveying purposes. Users of this information should review or consult the primary data and information sources to ascertain the usability of the information.




**Legend**

- Watermaster districts
- Counties
- Streams

**Recommended Gage Network Changes with Priority**

- low
- ▲ med
- high
- ✕ Not needed by OWRD for Management





# Results

## Stream Gaging for Conjunctive-Use Distribution

- Most locations needing stream gages for conjunctive use management are located in the Klamath and Deschutes basins. (Gannett et al., 2001 & 2007)
- Other conjunctive use related stream gaging locations are associated with direct tributaries to the Columbia River (CRBG related aquifers).
- Gage network is meeting current conjunctive use management needs (25 active stream gages).
- Near future conjunctive use needs will require 26 additional stream gages. Currently have gages at 19 of these sites.




# Stream Gaging Network Distribution Evaluation: Gage and Gage Locations Related to Conjunctive-Use Management

0 10 20 30 40 50 Miles  
Oregon Lambert Coordinate Reference System  
(EPSG #2992)



## Legend

- Groundwater Management Area
- ▲ Active Gage, Future Conjunctive Use
- ▼ New Gage, Future Conjunctive Use
- ▲ Existing Gage, Current Conjunctive-Use
- Watermaster districts
- Streams (1\_250k)
- Lakes



# Conclusions

- The OWRD water distribution goal entails timely and accurate flow monitoring, and moving away from complaint based flow distribution.
- The evaluation for water distribution provides a summary of how OWRD monitors water for regulation and distribution in each watermaster district.
- The evaluation identified 70 locations needing new stream gages to meet surface water distribution needs.
- Of these new sites, 31 were deemed high priority locations.





# Conclusions

- The existing gaging network is currently meeting conjunctive-use water distribution needs.
- 7 new stream gages will be required to meet projected future conjunctive-use data needs.
- OWRD's ability to expand the gaging network is limited by resource constraints.
- The stream gaging network evaluation for the other OWRD goals needs to be completed.



# Related Actions in the IWRS



**Recommended Action 1.B**  
**Improve Interagency Natural  
Resource Data Collection**

**Recommended Action 5.A**  
**Support Continued Basin-Scale  
Climate Change Research Efforts**

**Recommended Action 3.A**  
**Determine Flows Needed (Quality and  
Quantity) to Support Instream Needs**

**Recommended Action 5.B**  
**Assist with Climate Change Adaptation  
and Resiliency Strategies**

**Recommended Action 11.B**  
**Develop Additional Instream Protections**

**Recommended Action 10.B**  
**Improve Access to Built Storage**



Photo: R. Cooper

# Questions?





# Detailed results for surface water distribution monitoring needs

Type	High Priority Gages	Medium Priority Gages	Low Priority Gages	Total
New	31	25	14	70
Upgrade	4	6	2	12
Alternative	4	1	4	9
Total	39	32	20	91