RECEIVED

File Original and First Copy with the STATE ENGINEER, SALEM, OREGON

Bake 1035

9/40-8 R

STATE ENGWATER WELL REPORT SALEM, OREGITATE OF OREGON G 1005

State Permit No.

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water lowered below static level
Name CLYDE WARD	Was a pump test made? Yes No If yes, by whom? regular us
Address I 1500 H. St., Baker, Oregon.	Yield: 600 gal./min. with 15 ft. drawdown after hrs.
The state of the s	
(2) LOCATION OF WELL:	n n n
County Ba ker Owner's number, if any 10	Bailer test gal./min. with ft. drawdown after hrs.
SE 14 SE 14 Section 8 T. 9 S. R. 40 E. W.M.	Artesian flow g.p.m. Date
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis made? Yes No
1207 Ft. North and 563 Ft. East of the	(12) WELL LOG: Diameter of wellinches.
East 1/16th Sec. Corner of Sections	Depth drifter dug 40 ft. Depth of completed well 40 ft.
8 and 17, T. 9 S., R. 40 E., W. M., Oregon.	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each
	stratum penetrated, with at least one entry for each change of formation.
12 May 12	MATERIAL FROM TO
(3) TYPE OF WORK (check):	Earth Surface 81
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	Gravel 81 401
pandonment, describe material and procedure in Item 11.	
PROPOSED USE (check): (5) TYPE OF WELL:	
Domestic Industrial Municipal Rotary Driven	
Irrigation ☐ Test Well ☐ Other ☐ Dug ☐ Bored ☐	1 (4)
Corrugated galvanized Iron nine.	3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3
- · · ·	
24. "Diam. from 40 ft. to Top ft. Gage 16	
Connected by collars to ft. Gage ft. to ft. Gage	
It. Wage	NA.
(7) PERFORATIONS: Perforated? T Yes \(\square\) No	NAME OF THE PARTY
Type of perforator used Punched 3/8" holes.	
SIZE of perforations 3/8!! in. by round in.	
perforations from 40.1 ft. to 14.1 ft. perforations from ft. to ft.	
perforations fromft. toft.	
perforations from ft. to ft.	
perforations from ft. to ft.	A Chief
(8) SCREENS: Well screen installed ☐ Yes 17 No	
Manufacturar's Name	
Model No.	<u> </u>
Slot size ft. to ft.	A Section 1997
Such Slot size Set from ft. to ft.	Work started March 1956. Completed April 1956
(9) CONSTRUCTION:	
Was well gravel packed? Xyes No Size of gravel: 1" to 2"	(13) PUMP:
Gravel placed from40ft, to10ft.	Manufacturer's Name Fairbanks-Morse
Was a surface seal provided? XYes \(\subseteq \text{No To what depth?} \) ft.	Type: Turbine H.P. 15
Material used in seal— Topsoil dirt.	Well Driller's Statement: dug
Did any strata contain unusable water? Yes No	This well was the under my jurisdiction and this report is
Type of water? fresh Depth of strata 32	true to the best of my knowledge and belief.
Method of sealing strata off Topsoil	NAME (Glyde Wend)
(10) WATER LEVELS: to 40 ft. late summer.	NAME (Person, firm, or corporation) (Clyde Ward) (Type or print)
Static level 15 ft. June/it. below land surface Date	Address 1500 H St., Baker, Oregon.
Artesian pressure none lbs. per square inch Date	Driller's well number 10
Log Accepted by:	[Simust Kolydon (Man)
[Signed] Custo Marge July 7, 1952, 19	[Signed] (Well Driller) Owner
(Owner) 1958, 19	License No Date July 7,, 19.58.
(USE ADDITIONAL SH	