NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT:

STATE OF OREGON

(Please type or print) AFREO 1073 State Permit N

State Permit No.

	WINTER RESUURCES La va
(1) OWNER:	(10) LOCENON OF WELL:
Name Henry Steel	County Baker Driller's well number
Address Hoines, Oreom	JU 14 NE 1/4 Section 33 T. 75 R. 39 E W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 44 ft.
Rotary Driven Domestic Industrial Municipal	Static level /6 ft. below land surface. Date 4-13-78
Cable	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded □ Welded A O "Diam. from 1 ft. to 7 ft. Gage 250 2 "Diam. from 1 ft. to 300 ft. Gage 250 "Diam. from ft. to ft. Gage 1250 "Diam. from ft. to ft. Gage 1250 "Diam. from ft. to ft. Gage 1250 PERFORATIONS: Perforated? Yes □ No. pe of perforations 3/16 in. by 3 in. 69, 120 perforations from ft. to ft. perforations from ft. to ft. (7) SCREENS: Well screen installed? □ Yes No Manufacturer's Name Type Model No.	Depth drilled 330 ft. Depth of completed well 300 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. MATERIAL From To SWL TOO SOI C 21/2 Decomposed Claus Red. Bt Likit Small To Median Grave 2/4 /6 Clay Light Bt with Small Grave Decomposed Granie with 44 199 16
Diam. Slot size Set from ft. to ft.	Sand Fine with Layersof
Diam, Slot size Set from ft. to ft.	Hard Stroaks. 199 222
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Decomposed Granita with 122 1330 16
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	
Tanpressor (Thru Wier) "" "" "" "" ""	Gravelpack Hole with, 214ds of 34- Round
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water 49 Depth artesian flow encountered ft.	Work started 2-15 1978 Completed 4-13 1978
(9) CONSTRUCTION:	Date well drilling machine moved off of well 4-13 1978
Well seal—Material used Concent Count 1% Bentonite Well sealed from land surface to 36 ft. Diameter of well bore to bottom of seal 24 in. Diameter of well bore below seal in. Number of sacks of cement used in well seal 5 sacks How was cement grout placed? Pump Thou Pipe	Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief [Signed] (Drilling Machine Operator) Drilling Machine Operator's License No.
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? Yes No Plugs Size: location ft. Did any strata contain unusable water? Yes No	Name April (Person, firm or corporation) (Type or print)
	Address House City Orcord
Type of water? depth of strata	La de la
Method of sealing strata off	[Signed] (Water Well Contractor)
Was well gravel packed? Yes No Size of gravely Nound	1/25 1
Gravel placed from 36 ft. to 300 ft.	Contractor's License No. Date