NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

(10)	STATE OF OREGON UAN 1 1978 State Well No.
shaker	(Please type or print TER RESOURCES SOEPHermit No.
W 10'	(Do not write above this line SALEM, CREGON

(1) OWNER:	(10) LOCATION OF WELL:		_
Name Lad Fraset	County Baker Driller's well nu	imber F-7	<del>7</del>
Address / 320 N. Manzanita	5W 1/4 NE 1/4 Section 19 T. 75	R. 40E	W.M.
Arange, Calif	Bearing and distance from section or subdivision	on corner	
(2) TYPE OF WORK (check):			
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	-all	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	7 0	
Patron D	12	- 1	1 2c 7
Cable  Jetted	Static level 6 5 It. Delow lailu s		. 25-1
Dug   Bored   Irrigation Test Well   Other	Artesian pressure lbs. per squar	e inch. Date	
CASING INSTALLED: Threaded   Welded   W	(12) WELL LOG: Diameter of well be Depth drilled 240 ft. Depth of comple		8 32 n
	Formation: Describe color, texture, grain size a	and structure of	materials:
	and show thickness and nature of each stratuments with at least one entry for each change of format	m and aquifer pe	enetrated.
PERFORATIONS: Perforated? Yes   No.	position of Static Water Level and indicate prin	cipal water-beari	cnange in ng strata.
Type of perforator used Factory mill	MATERIAL	From To	SWL
Size of perforations 1/8 in. by 3 in.	TOO Soil	0 /	
28 80 perforations from 74 n to 232 n	D-composed Clays BL- Rod	1 56	
perforations from	4/10/10	. 33	
perforations from	Clauba Streeks & Branch	56 72	63
	med		
(7) SCREENS: Well screen installed?   Yes No	Gragela Sand Sine	72 76	
Manufacturer's Name	Dolcanic Kel Dark	76 /29	
Type Model No	Untrante Cindens Boken	129 151	
Diam. Slot size Set from ft. to ft.	COPCINIC LAVA Br	15/ 225	W/
Diam. Slot size Set from ft. to ft.	Golcanic Cincens	225 23/	63
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Basa/t	23/ 240	
Was a pump test made?  Yes No If yes, by whom?	0 + 17 / 2/10. 1		
Yield: 200 gal./min. with /20 ft. drawdown after 4 hrs.	Put 1 Juds 3/4 Round		
" " "	grave in more		
"Comphessor " "	/		
Bailer test gal./min. with ft. drawdown after hrs.			<del></del>
Artesian flow g.p.m.			
perature of water 4 Depth artesian flow encountered ft.	Work started //- 2 1977Complete	ed //-25	19 >
(9) CONSTRUCTION;	Date well drilling machine moved off of well	11.26	19 7
Well seal-Material used Cenen 7	Drilling Machine Operator's Certification:		
Well sealed from land surface to 22 ft.	This well was constructed under my	direct super	vision.
Diameter of well bore to bottom of sealin.	Materials used and information reported best knowledge and bares.	above are true	to my
Diameter of well bore below seal		Date 12-27	1077
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)	1041	<u> </u>
How was cement grout placed?  Pumped Thru Drill Pipe	Drilling Machine Operator's License No.	604	
	Water Well Contractor's Certification:		
	This well was drilled under my jurisdi true to the best of my knowledge and beli		eport is
Was a drive shoe used? ☐ Yes M No Plugs Size: location ft.  Did any strata contain unusable water? ☐ Yes No	Name Person, firm or copporation	Crope or pri	nt)
	10. (C+ 1)	Live -	110)
Type of water? depth of strata	Address Andrew Company Lofe, Lofe		•••••
Method of sealing strata off	[Signed]		••••••
Was well gravel packed? Yes No Size of gravel:	(Wafer Well Contr	actor)	ツレ
Gravel placed from 22 tt. to 232 ft.	Contractor's License No Date	1-10	, 19/./