NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

Market State Well No. 1/5 438-28 }
State Permit No.

(1) OWNER: Name Allen of Holding Zirkmun	(10) LOCATION OF WELL: County B All Driller's well no	ımber
Address Masse ( Capril	1/E 1/4 / 1/4 Section 28 T. //S	R. 43E W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivisi	on corner
New Well ( Deepening ☐ Reconditioning ☐ Abandon ☐		
If abandonment, describe material and procedure in Item 12.	(11) WATER I EVEL. Completed to	الم
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.  Depth at which water was first found 290 ft.	
	1001	
Domestic   Industrial   Municipal	Artesian pressure lbs. per square inch. Date	
(5) CASING INSTALLED: Threaded   Welded   Welded   Gage   House   Gage   Gage   House   Gage   G	(12) WELL LOG: Diameter of well below casing	
(6) PERFORATIONS: Perforated?  Yes No.	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.	
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	TOPSOIL	03
perforations from ft. to ft.	CLAY	3 20
perforations from ft. to ft.	GRAVELY BouldeRS	30 24
perforations from ft. to ft.	11 111 12/110	195 190
(7) SCREENS: Well screen installed?   Yes	SANGSTRIP	190 192 190
Manufacturer's Name	CLAVBLUC	192 304 190
Type Model No.	SANDSTRIP	204 205 190
Diam Slot size Set from ft. to ft.	CLAYBLUC.	205 326 190
Diam, Slot size Set from ft. to ft.	-SANA	326 327 190
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	DEAFILE	
as a pump test made? The Yes \( \subseteq \) No If yes, by whom? DRI 11eR.	WEGEIVED-	KECFIVEN
Yield: R gal./min. with // Oft. drawdown after 4 hrs.	OCT - 91070	No.
ried: gai./min. with // // urawdown arter - // mis.	WATE	NUV211979
	WATER RESOURCES DEVA	ER RESOURCES DE
	SALEM, OREGON	SALEM, OREGON
Bailer test gal./min. with ft. drawdown after hrs.	- Target	7 - 1,4 - 0014
Sian flow g.p.m.	0-71 20	. 0 - 2 7 1070
mperature of water 2 Depth artesian flow encountered ft.	Work started 9 - 2 / 19 9 Complete	ed 9-2 / 19/9
(9) CONSTRUCTION:	Date well drilling machine moved off of well	$9 - 27 \frac{19}{Y}$
Well seal-Material used CeMeNTGROUT	Drilling Machine Operator's Certification	
Well sealed from land surface toft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my	
Diameter of well bore to bottom of sealin.	best knowledge and belief.	
Diameter of well bore below seal	[Signed] M. (Outling Machine Operator) Date 9-50, 1979	
How was cement grout placed? WITH PRESSURE	Drilling Machine Operator's License No.	202
GROUTMACHINE	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction and this report is	
	true to the best of my knowledge and belief.	
Was a drive shoe used? Le Yes   No Plugs Size: location ft.  Did any strata contain unusable water?   Yes Le No	Name (Person, firm or comporation) (Type or print)	
	Address \( \int \mathcal{II} \tag{P} \int \( \tag{O} \)	DROGON!
Type of water? depth of strata	11	1 La .
Method of sealing strata off	[Signed] (Water Well Cont	ACUMUA J
Was well gravel packed?  Yes Ano Size of gravel:	11	2-21 50
Gravel placed from ft. to ft.	Contractor's License No Date	