NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report

are to be filed with the

WATER RESOURCES DEPARTMENT, (SALEM, OREGON 97310

within 30 days from the date

of well completion.

first copy of this report filed with the WATER WELL REPORT

STATE OF OREGON

(Please type or print)
(To not write above this line)

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name Okegay State Heway Division	County BAKER Driller's well number
Address Jaslen (1 Kg Jours	SE 14 NE 14 Section 30 T.125 R. 44 E W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well	
If abandonment, describe material and procedure in Item 12.	(11) WARRED I REVER Commission II
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well. Depth at which water was first found 40 ft.
Rotary V Driven D Domestic V Industrial Municipal	
Cable	Static level 4/ ft. below land surface. Date 1/-7-78 Artesian pressure lbs. per square inch. Date
GASING INSTALLED: Threaded Welded	77%
8 " Diam. from 0 ft. to 38 ft. Gage	Depth drilled 130 ft. Depth of completed well 130 ft.
ft. Gage ft. of the first fixed from ft. Gage ft. Ga	Formation: Describe color, texture, grain size and structure of materials;
	and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	5012
perforations from	BROKEN BASALT 5 20
perforations fromft. toft.	DINCH BROKE 25 1/A
perforations fromft. toft.	BLACK BASALT-GAAD STONE 40 43
(7) SCREENS: Well screen installed? Yes VNo	BLACK BASALT 43 130
Manufacturer's Name	DESIGNAL TO THE
Type Model No.	
Diam Slot size ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	SECEIVED
Was a fully test made? Leves I No If yes, by whom? DRILLER	- KEUEI VED
4	DEC 11978
gai./min. with 126 ft. drawdown after hrs.	WATER RESOURCES DEPT.
	WATER RESOURCE
	SALEM, OREGOT
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	1/10/20/20/20
perature of water Depth artesian flow encountered ft.	Work started //- 1978 Completed //-8 1978
(9) CONSTRUCTION,	Date well drilling machine moved off of well 1978
Well seal-Material used Farlland Cement	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of seal	best knowledge and belief.
Diameter of well bore below sealin.	[Signed] Jan Bun Date 11-8, 1975
Number of sacks of cement used in well seal Sacks How was cement grout placed?	Drilling Machine Operator's License No. 933
How was cement grout placed? TRPMY PIFF	
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? Yes [] No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water? 🛘 Yes 🏚 No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 3545 S.W. DOUGLAS DK. PENDLETON OL
Method of sealing strata off	[Signed] Lay Buy
Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 544 Date 11-8 1978