NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT SALEM, OREGON 97310 within 30 days from the date

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

tate	Well	No.	140/44E-13cb	
iale	AA CIT	140.		

State Permit No.

of well completion. (Do not write as	love tims fine)	
(1) OWNER:	(10) LOCATION OF WELL:	
Name (ty of Huntington	County 3 Rev Driller's well number 79£3/	/
Address Huntington, Orean	11.1 -11 12 16 1/1-	/.М.
(9) MVDE OF WORK (sheet):	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):		
New Well □ Deepening □ Reconditioning □ Abandon □		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	ft.
Rotary Driven Domestic Industrial Municipal	Static level 24 ft. below land surface. Date 7-26	7.7
Cable	Artesian pressure lbs. per square inch. Date	
CASING INSTALLED: Threaded Welded W	(0)	
2 "Diam. from 7.2 ft. to 3.3 ft. Gage 375	(12) WELL LOG: Diameter of well below casing	•••••
"Diam. fromft. toft. Gage	Depth drilled 550 ft. Depth of completed well 550	ft.
"Diam. from	Formation: Describe color, texture, grain size and structure of materi	
Diant Holl manager to to manager to the dage	and show thickness and nature of each stratum and aquifer penetra with at least one entry for each change of formation. Report each chang	
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing str	
Type of perforator used	MATERIAL From To SW	T.
Size of perforations in. by in.		
perforations fromft. toft.	Broght BK Some Stactured 448 480 2.	Z
perforations from ft. to ft.	Pasott Red Cap 480 493	<i>f</i>
perforations from ft. to ft.	Base 1481 493 510	
	Breather Fine grain Hard 510 5-50 2	4
(7) SCREENS: Well screen installed? Yes No		
Manufacturer's Name		
Type Model No	Set over 6" Test Hole	
Diam Slot size Set from ft. to ft.	open Hole To 16" To	
Diam. Slot size Set from ft. to ft.	331' Set 10" Pluge 334	
(8) WELL TESTS: Drawdown is amount water level is	Cemented 33/05/2"	
lowered below static level	Casing - Lound Cement	
Was a pump test made? Wes \(\sigma\) No If yes, by whom?	in Change 315 Dulled	
Yield: 320 gal./min. with /63 ft. drawdown after 5 hrs.	Hole 10" To 550 WATER WES	ne:
n n		
" " " "	Too Hale Consol To 1811 ORF CON	<u> </u>
Bailer test gal./min. with ft. drawdown after hrs.	To 19'	
Artesian flow g.p.m.	1/8/7	
perature of water 24 Depth artesian flow encountered ft.	Work started 6-27 1979 Completed 7-28 19	79
(9) CONSTRUCTION:	Date well drilling machine moved off of well 7-28	7 9
	Drilling Machine Operator's Certification:	
Well seal—Material used (emen) Stold Well sealed from land surface to 33 ft.	This well was constructed under my direct supervisi-	on.
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to best knowledge and belief.	my
Diameter of well bore below seal		79
Number of sacks of cement used in well seal	[Signed] DateO 0 , 19,	fZ
How was, cement grout placed?	Drilling Machine Operator's License No. 604	
Welled Capon Cosing & tumped	Window William Condensate Condens	
Thru Casing	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction and this report true to the best of my knowledge and belief.	t 1S
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Cobe Drilling, Inc	
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)	••
Type of water? depth of strata	Address Terre City, Crefort	
Method of sealing strata off	[Signed] Sand Jake	
Was well gravel packed? [] Yes No Size of gravel:	(Mater Well Contractor)	******
Gravel placed from ft. to ft.	Contractor's License No 382 Date 14/449 , 19	79