NOTICE TO WATER WELL ON RAFTE VE WATER WELL REPORT are to be filed with the

STATE OF OREGON

WATER RESOURCES DEPARTMENTN 1979 STATE OF OREGON SALEM, OREGON 97310 within 30 days from the TER RESOURCES DEPT-lease type or print) of well completion. SALEM, OREGON (Do not write above this line) State Well No. State Permit No.

Of the beautiful of the second	
(1) OWNER:	(10) LOCATION OF WELL:
Name (ity of Huntington	County / Daker Driller's well number
Address Hintington, Oregon	5w 145w14 Section / 3 T. /45 R. 44/E W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well	
If abandonment, describe material and procedure in Item 12.	
	(11) WATER LEVEL: Completed well,
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 244 - 12 gpm ft.
Rotary Driven Domestic Industrial Municipal Domestic Industrial Municipal Domestic D	Static level /2 ft. below land surface. Date/2-/3-78
Dug	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 6
"Diam from # 12 ft. to 26 ft. Gage 1250	Depth drilled 4/8 ft. Depth of completed well ft.
"Diam. from	Formation: Describe color, texture, grain size and structure of materials;
ft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
pe of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	211611011
perforations from ft. to ft.	Boulders Small to Medium O 4
perforations from ft. to ft.	Conglomerates 4 20
perforations from ft. to ft.	Chilly 20 EV
(7) SCREENS: Well screen installed? Yes Y No	Shale Light Rh 54248
Manufacturer's Name	Shale-By Broken 143 245 12
Type Model No.	Shale Dark Groy 245 335
Diam Slot size Set from ft. to ft.	Broken Besalt BK , Red 235 341
Diam Slot size Set from ft. to ft.	Basalt BK Some Startung 41 418 12
(8) WELL TESTS: Drawdown is amount water level is	
lowered below static level	This Hole Temporary
Was a pump test made? Yes No If yes, by whom?	Seal - 200 lbs of bentlyite
Yield: 200 gal./min. with 22 % ft. drawdown after hrs.	Chi Xes 4 Pumpes around
lompressor " "	Brian Mineta
n n	UNITERNITY OF THE
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water 3 Depth artesian flow encountered ft.	Work started //- 28 19 78 Completed /2 - 13 1978
(9) CONSTRUCTION:	Date well drilling machine moved off of well 12.13 1978
Well seal-Material used See Item # 12	Drilling Machine Operator's Certification:
Well sealed from land surface to 24 12 ft.	This well was constructed under my direct supervision.
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below sealin.	[Signed] Einest Johnson Dat 2-15, 19 8
Number of sacks of cement used in well seal sacks	(Drilling Michine Operator)
How was cement grout placed?	Drilling Machine Operator's License No. 60%
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? ☐ Yes M No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water? Yes No	Name (Refson, firm or corporation) (Type or print)
Type of water? depth of strata	Address BAINIE City, Orean
Method of sealing strata off	reigned (1. Sand We
Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 382 Date 12-19 198