

BAKELI

C.W. Hoffman Jr. ?

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM 10, OREGON within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON (Please type or print)

State Well No. 6/39-33A

State Permit No. G2662

SEP 8 1964

G286

(1) OWNER: R.O. RASMUSSEN
Name
Address 213 2ND. SAN MATEO CALIFORNIA

(2) LOCATION OF WELL:
County BAKER Driller's well number 122
NE 1/4 NE 1/4 Section 93 T. 6S R. 39E W.M.
Bearing and distance from section or subdivision corner

(3) TYPE OF WORK (check):
Well [ ] Deepening [ ] Reconditioning [ ] Abandon [ ]
abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):
Domestic [ ] Industrial [ ] Municipal [ ]
Irrigation [ ] Test Well [ ] Other [ ]
(5) TYPE OF WELL:
Rotary [ ] Driven [ ]
Cable [ ] Jetted [ ]
Dug [ ] Bored [ ]

(6) CASING INSTALLED:
Threaded [ ] Welded [ ]
14" Diam. from 0 ft. to 29.5 ft. Gage WALL

(7) PERFORATIONS:
Perforated? [ ] Yes [ ] No
Type of perforator used RASCAL MOSS HOVERED
Size of perforations 5/8 in. by 3 in.
2nd 160 perforations from 5.5 ft. to 22.3 ft.
7440 perforations from 2.23 ft. to 29.5 ft.

(8) SCREENS:
Well screen installed [ ] Yes [ ] No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(9) CONSTRUCTION:
Well seal—Material used in seal Cement
Depth of seal 40 ft. Was a packer used? No
Diameter of well bore to bottom of seal 26 in.
Were any loose strata cemented off? [ ] Yes [ ] No Depth 0-28'
Was a drive shoe used? [ ] Yes [ ] No
Was well gravel packed? [ ] Yes [ ] No Size of gravel: 3/8
Gravel placed from 40 ft. to 29.5 ft.
Did any strata contain unusable water? [ ] Yes [ ] No
Type of water Depth of strata
Method of sealing strata off

(10) WATER LEVELS:
Static level Flow ft. below land surface Date 8/12/64
Artesian pressure No. 12 lbs. per square inch Date

(11) WELL TESTS:
Drawdown is amount water level is lowered below static level.
Was a pump test made? [ ] Yes [ ] No If yes, by whom? B&M Equip. Co.
Yield: 2200 gal./min. with 90 ft. drawdown after 25 hrs.

Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow 30 g.p.m. Date 8/12/64
Temperature of water Was a chemical analysis made? [ ] Yes [ ] No

(12) WELL LOG:
Diameter of well below casing 9 7/8
Depth drilled 330 ft. Depth of completed well 295 ft.

Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.

Table with columns MATERIAL, FROM, TO. Rows include: Top soil DARK SANDY, SAND COARSE yellow, Boulders SMALL grey granite, CLAY BROWN SANDY, Boulders SMALL in yellow clay, CLAY yellow SANDY, SAND COARSE to med. white quartz, CLAY yellow SANDY, SAND STONE HARD white, GRAVEL SMALL white to black, CLAY blue (soft), GRAVEL SMALL to med., SAND COARSE to fine with STKS clay, SAND STONE HARD white + black, SAND med. grey with STKS clay, CONGLOMERATE HARD white, GRAVEL COARSE white, SAND COARSE to fine with STKS clay.

Work started 7/1 1964 Completed 8/3 1964
Date well drilling machine moved off of well 8/6/ 1964

(13) PUMP:
Manufacturer's Name
Type: H.P.

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME O.T. Ellsworth (Type or print)
Address 471 Island City OREGON
Drilling Machine Operator's License No. 282
[Signed] O.T. Ellsworth (Water Well Contractor)
Contractor's License No. 398 Date Aug 31, 1964