NOTICE TO WATER WELL CONTRACTOR: The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED JUL 12 1972 STATE ENGINEER SALEM, OR

NC

WATER WELL REPORT
STATE OF OREGON

(Please type or print) (Do not write above this line)

Baker 2e1

State Well No. 8S/38E-8dd

State Permit No. .....

(1) OWNER:
Name Mrs William McKolvson
Address Hamptich Oregon

(2) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☑ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☑ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED:
Threaded ☐ Welded ☑
6" Diam. from +1 ft. to 20 ft. Gage 1/4"
..." Diam. from ..... ft. to ..... ft. Gage .....
..." Diam. from ..... ft. to ..... ft. Gage .....

(6) PERFORATIONS:
Perforated? ☐ Yes ☑ No.
Type of perforator used
Size of perforations in. by in.
..... perforations from ..... ft. to ..... ft.
..... perforations from ..... ft. to ..... ft.
..... perforations from ..... ft. to ..... ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☑ No
Manufacturer's Name .....
Type ..... Model No. .....
Diam. ..... Slot size ..... Set from ..... ft. to ..... ft.
Diam. ..... Slot size ..... Set from ..... ft. to ..... ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☑ Yes ☐ No If yes, by whom? DRILLER
Yield: 20 gal./min. with 40 ft. drawdown after 4 hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 55° Depth artesian flow encountered ..... ft.

(9) CONSTRUCTION:
Well seal—Material used Cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 8" in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 1 sacks
Number of sacks of bentonite used in well seal ..... sacks
Brand name of bentonite .....
Number of pounds of bentonite per 100 gallons of water ..... lbs./100 gals.
Was a drive shoe used? ☑ Yes ☐ No Plugs ..... Size: location ..... ft.
Did any strata contain unusable water? ☐ Yes ☑ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☑ No Size of gravel: .....
Gravel placed from ..... ft. to ..... ft.

(10) LOCATION OF WELL:
County BAKER Driller's well number
SE 1/4 SE 1/4 Section 8 T. 8 R. 38E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 64' ft.
Static level 60 ft. below land surface. Date
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 6
Depth drilled 125' ft. Depth of completed well 125 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
GRAVELY CLAY	0	4	
LAVA Boulders	4	6	
LAVA ROCK	6'	60'	
LAVA BLACK Crevice	60	64	64
LAVA BLACK	64	119	64
LAVA CINDERS	119	125	60

Work started 6-1 1972 Completed 6-10 1972
Date well drilling machine moved off of well 6-10 1972

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Lee Mailloux (Drilling Machine Operator) Date 7-10, 1972
Drilling Machine Operator's License No. 101

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Holloway Drilling Co (Person, firm or corporation) (Type or print)
Address Ontario Oregon
[Signed] Max Holloway (Water Well Contractor)
Contractor's License No. 16 Date 7-10, 1972

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119