NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

(Do not write above this line)

(Do not write above this line)

	(10) TOCATION OF THEFE	
(1) OWNER:	(10) LOCATION OF WELL:	
Name MARION IMBIE	County BAILER Driller's well number	
Address RT / Box //2	5 4 3 5 14 Section / 8 T. 8 3 R. 37 E W.M.	
BALLADA -	Bearing and distance from section or subdivision	corner
(2) TYPE OF WORK (check):		
New Well (A Deepening Reconditioning Abandon		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 26 ft.	
Rotary Driven Domestic Industrial Municipal	Static level 2. 6 ft. below land sur	face. Date 6-15-76
Cable X Jetted	Artesian pressure lbs. per square i	inch. Date
CASING INSTALLED: Threaded Welded W	Depth drilled / 75 ft. Depth of completed well / 75 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.	
pe of perforator used CUTTINS TOBCH	MATERIAL	From To SWL
Size of perforations 1/4 in. by /2 in.	TOP 3011	0 /
50 perforations from 30 ft. to 130 ft.	Boulders	1 14
perforations from ft. to ft.	CIAX HABEL	14 20
perforations from ft. to ft.	STATE OF A	20 24
	· UAR A CONTRACTOR OF THE CONTR	26 27 W.B
(7) SCREENS: Well screen installed? Yes No	\(\frac{\sigma_1 \text{\tin}\text{\tin}\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\tinit}\\ \text{\text{\text{\text{\text{\text{\text{\text{\text{\tex{\tex	27 37
Manufacturer's Name	<u> </u>	37 50 25
Type	Clay yeilow sandy	50 175 20
Diam. Slot size Set from ft. to ft.		
Diam. Stot size		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? ☑ Yes ☐ No If yes, by whom? PRI//ci?		
Yield: 90 gal./min. with 37 ft. drawdown after 2 hrs.		
" " "		
, , , , , , , , , , , , , , , , , , , ,		
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		1 1
perature of water 5 2 Depth artesian flow encountered ft.	Work started 5-/2 197 (Completed	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	-15 1976
Well seal—Material used WZ M.T.M.J.T.	Drilling Machine Operator's Certification:	
Well sealed from land surface to	This well was constructed under my d Materials used and information reported al	
Diameter of well bore to bottom of seal	best knowledge and belief.	•
Diameter of well bore below seal in.	[Signed] (Drilling Machine Operator)	ate 7 13 , 19 8
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No	
Number of sacks of bentonite used in well seal		
Brand name of bentonite VOICIAY	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is	
of water	wide to the sest of my amovicage and sener.	
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location It. Did any strata contain unusable water? ☐ Yes 💆 No	Name /5 DCNN / S (Person, firm or corporation) (Type or print)	
	Address 54 MATCR STAGE BALLER DISC	
	-	
Method of sealing strata off	[Signed] 122 (Water Well Contractor)	
Was well gravel packed? ☐ Yes 💆 No Size of gravel:	Contractor's License No. 5.7.1 Date	
Gravel placed from ft. to ft.	Contractor's License No. 7 Date/	18. ر