NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED

JAN2 1981 State Well No. STATE OF OREGON 

(1) OWNER:	(10) LOCATION OF WELL:	An id	
Name Duid Hynderson #2	County Driller's well nu		/3
Address 3670 Coder	SW4 NE4 Section 19 T.	r. 39E	W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	n corner	
New Well Deepening Reconditioning Abandon I If abandonment, describe material and procedure in Item 12.			
	(11) WATER LEVEL: Completed we		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	44	tt.
Rotary Driven Domestic Industrial Municipal Domestic	Static level 32 ft. below land st	irface. Date	1/21/88
Bored   Irrigation   Test Well   Other	Artesian pressure lbs. per square	inch. Date	
CASING INSTALLED: Threaded Welded Welded Dig. Diam. from + 1/2 ft. to 272 ft. Gage 250	(12) WELL LOG: Diameter of well be the Depth drilled of the Depth of complete the Depth		<b>Z</b> ft.
	Formation: Describe color, texture, grain size a		
	and show thickness and nature of each stratum	n and aquifer p	enetrated,
) PERFORATIONS: Perforated? Mr. Yes   No.	with at least one entry for each change of format position of Static Water Level and indicate princ		
Type of perforator used Mill StoT	MATERIAL	From To	SWL
Size of perforations in. by in.	700 Soil .	01	
240 perforations from 552 ft. to 572 ft.	Medium Boulders + Smill		
perforations fromft. toft.	aravel	1 12	
perforations from ft. to ft.	Brun clay + Small grav.	12 44	32
	Broken Black Basalt	44 67	<del></del>
(7) SCREENS: Well screen installed?   Yes No	fine Sand	67 80	
Manufacturer's Name			<del>                                     </del>
Diam. Slot size Set from ft. to ft.			
Diam Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
a pump test made?  Yes No If yes, by whom?			
vield: 40 gal./min. with 35 ft. drawdown after hrs.			
Compresser " "			<del> </del>
" " "			<del></del>
Briler test gal./min. with ft. drawdown after hrs.			
sian flow g.p.m.			
mperature of water Depth artesian flow encountered ft.	Work started 11/10 19 40 Complete	d 11/2	1980
(a) CONSTRUCTION.	Date well drilling machine moved off of well	4/2	1 19 50
(9) CONSTRUCTION:  Well seal—Material used Cement GIOUT	Drilling Machine Operator's Certification:	<del></del>	
Well sealed from land surface to	This well was constructed under my		
Diameter of well bore to bottom of seal	Materials used and information reported best knowledge, and belief.	above are tru	e to my
Diameter of well bore below seal in.	64 11 784 A1A	Date	6180
Number of sacks of cement used in well seal sacks	(Drilling machine Operator)		
How was cement grout placed?PUMP	Drilling MacKine Operator's License No	1304	•••••
	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? Yes'□ No Plugs	Name Cake Intling for		
Did any strata contain unusable water?  Yes No	Merson, fight or corporation)	יות בייני (Type) או איני איני איני איני איני איני איני א	int)
Type of water? depth of strata	Address	r.c	A
Method of sealing strata off	[Signed]		••••••
Was well gravel packed?   Yes No Size of gravel:	(Water Well Contra	actor)	C
Gravel placed from ft. to ft.	Contractor's License No. Date	7-12-	, 18