| original bul File Original, and Duplicate with the STATE ENGINEER, SALEM, OREGON DEC 19 1962 STATE OF OR   | LERS REPORT Do Not State Well No. 7/38-27 G Fill In State Permit No.   |
|--|--|
|  | (10) WELL TESTS:   |
| (1) OWNER: Name () Acas Zel  |  |
| D - //-  | Was a pump test made? X Yes No If yes, by whom?  |
| Address Box 3205   | Yield:  gal./min. with  gt. draw down after  hrs.  |
| North founder, gregon  | <u> </u>   |
| (2) LOCATION OF WELL:  | Artesian flow g.p.m.   |
| County Baker Owner's number, if any-   | Shut-in pressurelbs, per square inch.  |
| R. F. D. or Street No.   | Bailer test g.p.m. with ft. drawdown   |
| Bearing and distance from section or subdivision corner  | Temperature of water Was a chemical analysis made? ☐ Yes 🛣 No  |
| The South East of the  | Was electric log made of well?  Yes No   |
| North East quarter of  |  |
| Lec 27 township 7 Range 38 Ew  | (11) WELLLOG:  |
|  | Diameter of well,  |
| (J) TYPE OF WORK (check):  | Total depth 60 ft. Depth of completed well 60 ft.  |
| New well Deepening Reconditioning Abandon  | Formation: Describe by color, character, size of material and structure, and   |
| If abandonment, describe material and procedure in Item 11.  | show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation. |
| ') PROPOSED USE (check): (5) EQUIPMENT:  | ft. to ft.   |
| mestic 🕱 Industrial 🗆 Municipal 🗆 Rotary   | O" 12" BROWN ChAY  |
| Cable Cable  | 12" 30" SANDE BROWN CLAY   |
| Irrigation   Test Well   Other   Dug Well  | 80" 28 " RROWN SAND  |
| (6) CASING INSTALLED: If gravel packed   | 28" 42 " SAND-BOULDERS BROWN   |
| Threaded   Welded  | 42" 54" SAND-CLAE BROWN  |
| Gage or Diameter from to   | 54" GO" SAND GREY  |
| FROM ft. to ft. Diam. Wall of Bore ft. ft. + 2" " (60" '8" .970 " " "  | "  |
| +2" "60" 8 270   | ))   |
| 11 11 11 11 11 11 11 11 11   | 19 99  |
| 1) 1) 1) 1) 1) 1) 1) 1) 1) 1) 1) 1) 1) 1   | 10 10  |
| 22 21 11 11 12 21 21 21  | D D  |
| Type and size of shoe or well ring & SHOE Size of gravel:  | 10 10  |
| Describe joint 20 TOINT WELDED TO SHOP SHOE  | n n  |
|  | n n  |
| (7) PERFORATIONS:  | 19 19  |
| Type of perforator used TORCH  | 11 11  |
| t of perforations S in., length, by 4 in.  S in., length, by 4 in.  F in., length, by 4 in.  F in., length, by 4 in.   | " "  |
|  | " "  |
| "28 " 32 " " " 4 " " 4 " " 2 " | n n  |
| "56 "61 "8 4 4<br>""""""""""""""""""""""""""""""""   | 1) 1)  |
| 1 21 11 11 11 11 11 11   | n n  |
| SCREENS:   | " "  |
| Give Manufacturer's Name, Model No. and Size   | n n  |
|  | " "  |
| (a) CONSUDICTION.  | " "  |
| (8) CONSTRUCTION: Was a surface sanitary seal provided? ★ Yes □ No To what depth ft.   | " "  |
| Were any strata sealed against pollution? ☐ Yes 🕱 No   | Ground elevation at well site feet above mean sea level.   |
| If yes, note depth of strata   | Work started OCT 35 1962, Completed OCT 27 1962  |
| FROM ft. to ft.  | Well Driller's Statement:  |
| 19 99  | This well was drilled under my jurisdiction and this report is   |
| METHOD OF SEALING RENTONITE  | true to the best of my knowledge and belief.   |
|  | NAME CHAS. JUNGMANN DRILLING CO.   |
| (9) WATER LEVELS:  Depth at which water was first found 28 ft.   | (Person firm or comparation) (Typed or suinted)  |
| Standing level before perforating 28 ft.   | WALLA WALLA, WASHINGTON Address  |
|  | Driller's weathnumber  |
| Standing level after perfections (2)   |  |
| X Log Accepted by:   | [Signed] (Fell Driller)  |
| [Signed Osen 2, Jacobson Dated Dorg 12, 1962   | License No. 236 Deted OCT. 30 19/2   |
| Overes   | ,, 10-475.   |
|  |  |