NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT.
SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT REGENT STATE OF OREGON STATE OF OREGON STATE OF OREGON STATE OF PERSON STATE OF PERSON STATE OF OREGON STATE OF OREGIN STATE OF OREGON STATE OF OREGIN STATE OF OREGON STATE OF OREGIN STATE

(Do not write above this line)WATER RESOURCES DEPT

	WATER RESOURCES DEPT.
(1) OWNER:	(10) LOCATION OF WEEE ON
1 Faran	County Baker Driller's well number
Address 1642 Valley	JE 1/4 SE 1/4 Section / 3 T. 7 S R. 39/5 W.M.
Baker Chrobon	
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	
	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found /8 ft.
Rotary Driven Domestic Industrial Municipal	Static level /5 ft. below land surface. Date /0-27-7
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded □ Welded ★ O " Diam from	(12) WELL LOG: Diameter of well below casing Depth drilled 250 ft. Depth of completed well 244 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated.
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used Shop Mill	MATERIAL From To SWL
Size of perforations 1/8 in. by 3 in.	Pulled 6" Casing 20
2880 perforations from 93 tt. to 244 tt.	Temporary sek/
perforations from ft. to ft.	
perforations from	Chaned Hole 10/5
(7) SCREENS: Well screen installed? Yes No	14h 477 85 10 (25/hg)
Manufacturer's Name	Put 6 uds 0 3 3/4 Round
Type Model No	Gravel 17 Hole
Diam Slot size	
Diam Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes W No If yes, by whom?	
Yield: 220 gal./min. with /49 ft. drawdown after 6 hrs.	
Compressor " "	
" " "	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 10-8 197/Completed 10-27 197/
(9) CONSTRUCTION:	Date well drilling machine moved off of well 10-27 197/
Well seal—Material used Cement Ground Well sealed from land surface to	Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin. Diameter of well bore below sealin.	[Signed]
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator) Drilling Machine Operator's License No
How was cement grout placed? Dullpipe	Drining Machine Operator's License No
- Secretary Control of the Control o	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? ☐ Yes No Plugs Size: location ft. Did any strata contain unusable water? ☐ Yes No	Name New Trust St. St. (Type or print)
Type of water? depth of strata	Address Adje Cotty Oregan
Method of sealing strata off	[Signed] Sand John
Was well gravel packed? Yes No Size of gravel 3/4 minus	(Water Well Contractor)
Gravel placed from 18 ft. to 214 ft.	Contractor's License No Date