#6-1/8" by 12" - per WWC 12/6/82 JCB

WATER WELL REPORT
STATE OF OREGON

RECEIVED
AUG 31 1982
WATER RESOURCES DEPT.
SALEM, OREGON

State Well No. 10S/4W-23 cb

State Permit No. .....

No. 3

(1) OWNER:
Name Gene Nygren
Address 3433 Countryman Circle NW
City Albany State OR

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary Air ☒ Driven ☐
Rotary Mud ☐ Dug ☐
Cable ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐
Thermal: Withdrawal ☐ Reinjection ☐

(5) CASING INSTALLED:
Steel ☒ Plastic ☐
Threaded ☐ Welded ☒
6" Diam. from +1 ft. to 99 ft. Gauge .250
" Diam. from ft. to ft. Gauge

LINER INSTALLED:
" Diam. from ft. to ft. Gauge

(6) PERFORATIONS:
Perforated? ☒ Yes ☐ No
Type of perforator used saw cut
Size of perforations in. by in.
80 perforations from 164 ft. to 204 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot Size Set from ft. to ft.
Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
Air test 35 gal./min. with drill stem at 204 ft. 1 hrs.
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 53 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Special standards: Yes ☐ No ☒
Well seal—Material used cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 8 sacks
How was cement grout placed? From bottom to top

Was pump installed? No Type HP Depth ft.
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of Water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Benton Driller's well number
NW ¼ SW ¼ Section 23 T. 10S R. 4W W.M.
Tax Lot # Lot Blk Subdivision
Address at well location: 34433 Countryman Circle NW, Albany, OR

(11) WATER LEVEL: Completed well.
Depth at which water was first found 172 ft.
Static level 3 ft. below land surface. Date 8/10/82
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 6
Depth drilled 204 ft. Depth of completed well 204 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top soil	0	3	
Brown clay (sticky)	3	13	
Redish brown clay (sticky)	13	21	
Yellowish Brown clay (sticky)	21	31	
Blue sandy clay	31	52	
Gray sandy clay	52	64	
Blue sandy clay	64	79	
Gray sandy clay	79	83	
Gray sandstone	83	204	

Work started 8/5 1982 Completed 8/10 1982
Date well drilling machine moved off of well 8/10 1982

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] George M. Simpson (Drilling Machine Operator) Date 8/26, 1982
Drilling Machine Operator's License No. 1072

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Schoen Electric, Inc. (Person, firm or corporation) (Type or print)
Address 626 W. Queen Ave., Albany, OR
[Signed] Larry L. Schoen (Water Well Contractor)
Contractor's License No. 513 Date 8/30, 1982

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

SP*12658-690