

OBSERVATION WELL

RECEIVED

10/18/88 - JSul

Bent 1557

10/3W-304

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

APR 8 1964 WATER WELL REPORT

STATE ENGINEER, SALEM 10, OREGON STATE ENGINEER STATE OF OREGON within 30 days from the date of well completion. (Please type or print)

State Well No. 6-2826 State Permit No.

(1) OWNER:

Name Springhill Golf and Country Club Address Rt. 4, Box 548F Albany, Oregon

(2) LOCATION OF WELL:

County Benton Driller's well number NE 1/4 SW 1/4 Section 30 T. 10S R. 3W W.M. Bearing and distance from section or subdivision corner

(11) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? Yes No If yes, by whom? Self Yield: 150 gal./min. with No ft. drawdown after hrs. 200 5 200 13

(12) WELL LOG:

Diameter of well below casing 10" Depth drilled 35 ft. Depth of completed well 35 ft. Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.

Table with columns: MATERIAL, FROM, TO. Rows: Top Soil (0-3), Sandy Loam (3-10), Sand & Gravel (10-14), Gravel (14-25), Sand & Gravel (25-31), Hard Sandstone (31-35)

(3) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon If abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):

Domestic Industrial Municipal Irrigation Test Well Other

(5) TYPE OF WELL:

Rotary Cable Dug Driven Jetted Bored

(6) CASING INSTALLED:

Threaded Welded 10" Diam. from 0 ft. to 30 ft. Gage 31#

(7) PERFORATIONS:

Perforated? Yes No Type of perforator used Acetylene Torch Size of perforations 1/2 in. by 12 in. 36 perforations from 18 ft. to 30 ft.

(8) SCREENS:

Well screen installed? Yes No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(9) CONSTRUCTION:

Well seal-Material used in seal Bentonite Depth of seal 18 ft. Was a packer used? Diameter of well bore to bottom of seal 12 in. Were any loose strata cemented off? No Depth Was a drive shoe used? Yes No Was well gravel packed? No Size of gravel: Gravel placed from ft. to ft. Did any strata contain unusable water? No Type of water? Depth of strata Method of sealing strata off

(10) WATER LEVELS:

Static level 12 ft. below land surface Date 3-15-64 Artesian pressure lbs. per square inch Date

(13) PUMP:

Manufacturer's Name Type: H.P.

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Merle Warren Well Drilling (Person, firm or corporation) (Type or print) Address Rt. 1, Box 85, Tangent, Oregon Drilling Machine Operator's License No. 313 [Signed] Merle Warren (Water Well Contractor) Contractor's License No. 182 Date 4/11 1964