File Original and First Copy with the STATE ENGINEER, SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON 61802

SALEM, OREGON	State Permit No.		
(1) OWNER:	(11) WELL TESTS: Drawdown is amount we lowered below static leve	iter level is	
Name Al Fortier	Was a pump test made? X Yes No If yes, by whom?		
Address 905 Spring Hill Rd.	Yield: 200 gal./min. with 24 ft. drawdown		ars.
Albany, Oregon	" " " "		**
(A) Y O CAMPONY OF THEY Y	27 23 37		72
(2) LOCATION OF WELL:	Bailer test gal./min. with ft. drawdown	after h	ırs.
County Benton Owner's number, if any—	Artesian flow g.p.m. Date	77.15	<u></u>
SW 4 SE 4 Section 30 T. /OS R. 3W W.M.	Temperature of water Was a chemical analysis mad	e? 🗆 Ves 🏋	No.
Bearing and distance from section or subdivision corner	response of water was a chemical analysis may	le? 🗌 Yes 🔯	
N.66° 35' E. 48.5 CHAINS FROM	(12) WELL LOG: Diameter of well	inch	es.
SW CORNER OF S. 30, t. 10 S.	Depth drilled 35 ft. Depth of completed well	ı 35	ft.
P. 3 W.	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of the	and structure, a	nd
	show thickness of aquifers and the kind and nature of the stratum penetrated, with at least one entry for each che	e material in ea inge of formatic	ich on.
	MATERIAL	FROM TO	
(9) MYDE OF WORK (-LL).			٠ خب
(3) TYPE OF WORK (check):	Top Soil	0 3	
New Well Deepening Reconditioning Abandon	Sandy Loam	3 12	
If abandonment, describe material and procedure in Item 11.	Dirty Gravel	12 24	
PROPOSED USE (check): (5) TYPE OF WELL:	Water Gravel	24 30	—
Domestic Industrial Municipal Rotary Driven	Blue Clay	30 35	
Cable Jetted			—
Irrigation Test Well Cher Dug Bored			
(6) CASING INSTALLED: Threaded □ Welded K			
12." Diam. from			<u></u>
"Diam. fromft. toft. Gage			_
"Diam. from			_
Diani. Hom			
(7) PERFORATIONS: Perforated? ♀ Yes □ No	· <u></u>		
Type of perforator used Acetylene Torch			
SIZE of perforations 3/8 in. by 12 in.			-
30 perforations from 17:10" ft. to 32:10" ft.			
perforations from ft. to ft.			
perforations from ft. to ft.			
perforations from ft. to ft.			
perforations from ft. to ft.	<u> </u>		
Y			:
(8) SCREENS: Well screen installed ☐ Yes ♣ No			_
Manufacturer's Name			
Type Model No.			
Slot size Set from ft. to ft.			
Slot size Set from	Work started 10-1 1958. Completed 10	<u>-2 195</u>	8
(9) CONSTRUCTION:	(19) DITAID.	-	
	(13) PUMP:		
Was well gravel packed? Yes No Size of gravel: Gravel placed fromft.	Manufacturer's Name		
to the state of th	Type:	.P	*****
Was a surface seal provided? ☐ Yes No To what depth? ft. Material used in seal—	XXII XXIII - A. Cl. I - A. Cl. I	•	
Did any strata contain unusable water? Yes No	Well Driller's Statement:		*_
Type of water? Depth of strata	This well was drilled under my jurisdiction as true to the best of my knowledge and belief.	id this report	18
Method of sealing strata off		• .	*-
ALCHOOK OF BEHALF BREACH OFF	NAME Merle E. Warren, Well Dr		· · · · ·
(10) WATER LEVELS:		pe or print)	
	Address1315W. 15th Ave., Albany, Oregon		
Artesian pressure lbs. per square inch Date	Driller's well number		
	Max la Han	• .1	
Log Accepted by:	[Signed] ///WW Merr	CVC.	
[Signed] all Jose Date 10-17: 1958	(Well Driller)	1,7	= C
(Owner)	License No. 182 Date	/, 19. <u>s</u>	<u>در</u> د