The original and first cooperators of this report are to the filed with the

Artesian pressure

of this report are to Hell JUN 16 1965

STATE ENGINEER, SALEM, OREGON 97310

STATE OF OREGON within 30 days from the date. TE ENGINEER Please type or print)

TER WELL REPORT

VVI	
0/0	State Well No. 10/3 W - 31
D v	

or well completion.			
(1) OWNER: SALEM OREGON	(11) WELL TESTS: Drawdown is amount v	vater leve	l is
Vame Tripp & Tripp	Was a pump test made? Yes \sum No If yes, by whom		
Address 206 W. 1st Ave.	Yield: 550 gal./min. with NO ft. drawdov		1 hrs.
Albany, Oregon	" " "	11 02001	"
(2) LOCATION OF WELL:	27 29 <sub></sub> 32		,,,
a) Hoofilion of Willia.	Bailer test gal./min. with ft. drawdo	wn after	hrs.
County Benton Driller's well number	Artesian flow g.p.m. Date	<u></u>	
14 14 Section 31 T. 10S R. 3W W.M.	Temperature of water Was a chemical analysis :	nade? []	Yes X No
Bearing and distance from section or subdivision corner		C	7 11
	(12) WELL LOG: Diameter of well below of	ising	
	Depth drilled 50 ft. Depth of completed w		0 ft.
	Formation: Describe by color, character, size of materia show thickness of aquifiers and the kind and nature of stratum penetrated, with at least one entry for each c	l and stru	icture, and
	stratum penetrated, with at least one entry for each c	hange of	formation.
	MATERIAL	FROM	то
(3) TYPE OF WORK (check):			
Well <b>Y</b> □ Deepening □ Reconditioning □ Abandon □	Top Soil	0	3
r abandonment, describe material and procedure in Item 12.	Clay	3	19 -
(A) TOP OF OCCUPANT TICKS (AL. 1.). (A) RESTRUCTE OF THE T.	Gravel		42
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Clay & Gravel	42	45
Domestic X Industrial   Municipal   Rotary   Driven	Clay———	45	50
rrigation Test Well Other Dug Bored			
			<del> </del>
(6) CASING INSTALLED: Threaded  Welded			<del>                                     </del>
8			<del> </del>
" Diam. fromft. toft. Gage		<u> </u>	<del>                                      </del>
" Diam, from ft. to ft. Gage		<del> </del>	
(7) PERFORATIONS: Perforated? M Yes   No			<del>                                     </del>
· ·			<u> </u>
Type of perforator used Acetylene Torch			
Size of perforations 3/8 in. by 12 in.			-
20 perforations from 29 ft. to 39 ft.	<u>.</u>		
perforations fromft. toft.			
perforations fromft. toft.			<del> </del>
perforations from			<u> </u>
perforations fromft. toft.			
(8) SCREENS: Well screen installed? ☐ Yes ☐ No			<u> </u>
Annufacturer's Name		<del> </del>	<del> </del>
Model No.			<del> </del>
Dram. Slot size Set from ft. to ft.	<u> </u>	<u> </u>	
Diam. Slot size Set from ft. to ft.		<u>-</u> 5	19 65
	Date well drilling machine moved off of well 6-	2	19 65
(9) CONSTRUCTION:	(13) PUMP:		
Vell seal—Material used in seal Bentonite	Manufacturer's Name		
Depth of seal18ft. Was a packer used?	Type:		
Diameter of well bore to bottom of seal	19pe	1.5	nne entriperronalis prize va dir
Were any loose strata cemented off? Tyes X No Depth	Water Well Contractor's Certification:		
Vas a drive shoe used? ▼ Yes □ No	This well was drilled under my jurisdiction	and this	ranort is
Was well gravel packed? ☐ Yes X No Size of gravel:	true to the best of my knowledge and belief.	*110 WIII	report is
Fravel placed fromft. toft.	NAMES - WILLIAM IN THE TAXABLE PARTY.	•	
Did any strata contain unusuable water? ☐ Yes 🕁 No	NAME Merle Warren Well Drill: (Person, firm or corporation) (Ty	ng pe or print	:)
Type of water? depth of strata	Address Rt. 1, Box 85, Tange		
Method of sealing strata off		go szanák II	
(10) WATER LEVELS:	Drilling Machine Operator's License No. 313		
AND THE EAST MAIN STEEDS	reimade ////hle / Mistra	m/	
static level 22 ft. below land surface Date 6-7-65	[Signed] (Water Well Contraptor)	<i></i>	******
Artesian pressure lbs. per square inch Date		9	, 1960.5
		7	, 1000