NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be
filed with the

## RECEI WATER WELL REPORT

STATE ENGINEER, SALEM, OREGON 97310 NOV 2 4 1975 (Please type or print) within 30 days from the date NOV 2 4 1975 (Please type or print) of well completion. WATER RESOURCES DEPT.

sent 1869

State Well No. 10s-4w-25

State Permit No. .....

(1) OWNER: SALEM, OREGON	(10) LOCATION OF WELL:
Name NW Intermountain Dev. Co. #2	County Benton Driller's well number 42575D
Address P. O. Box 550	NE NE NE Section 25 T. LOS R. 4W W.M.
Albany, Oregon 97321	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	Salary and anomalo Political Salary Store Corner
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐	10. p
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	D-9
Rotary Driven Domestic Industrial Municipal N	70 4 70 77
Cable K Jetted   Industrial   Municipal L	were point and political principle.
	Artesian pressure Ibs. per square inch. Date
CASING INSTALLED: Threaded □ Welded □	(12) WELL LOG: Diameter of well below casing 10"
10!!" Diam. from	Depth drilled 43 ft. Depth of completed well 43 ft.
ft. Gage	Formation: Describe color, texture, grain size and structure of materials;
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated?   Ves     No	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used Perforated? ☐ Yes ☑ No.	
	sand loam (brown) 0 12 13
	river gravel & sand   12   14
perforations fromft. toft.	sand 14 17
perforations fromft. toft.	gravel & sand - river   17   22
	brown sand & pea gravel 22 24
(7) SCREENS: Well screen installed? ☐ Yes ※☐ No	brown sand & river gravel 24 37
Manufacturer's Name	yellow clay with sand 37 39
Type Model No	green clay 39 43
Diam. Slot size Set from ft. to ft.  Diam. Slot size Set from ft. to ft.	
Diam. Stot size Set from It. to It.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes K No If yes, by whom?	
772-7-3	
Yield: gal./min. with ft. drawdown after hrs.	
" " "	- v v v v v v v v v v v v v v v v v v v
Bailer test 150 gal./min. with complete drawdown after 2 hrs.	
	(70 87 (70 87
aperature of water 53 Depth artesian flow encountered ft.	Work started 6-10 19 75 Completed 6-13 1975
(9) CONSTRUCTION:	Date well drilling machine moved off of well 6-13 19 75
Well seal—Material used	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.
Diameter of well bore below seal10. in.	[Signed] Late Letter Date 1/21, 1975
Number of sacks of cement used in well seal26sacks	Drilling Machine Operator's License No. 594
Number of sacks of bentonite used in well seal sacks	Drining Wachine Operator's License No. 12227
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of water	true to the best of my knowledge and belief.
Did any strata contain unusable water?  Yes 🖔 No	Name Schoen Electric & Pump (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 626 No Queen Avenue Albany, Or. 97321
Method of sealing strata off	Isigned Lamy & Schoe
Was well gravel packed? $\Box$ Yes $\Box$ No Size of gravel: $\Box$ $2^{17}$	[Signed] (Water Well Contractor)
was wen graver packed?   Tes   No Size of graver:	[//3/
Gravel placed from	Contractor's License No513 Date