NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

OCT 2 6 1973 state Well No. 105 4W-36

(Please type or print) STATE ENGINEER Permit No. ... (Do not write above this line SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name Parker-Oak Grove Water Dist./Russell Parker	
Address 910 Albany Road	NE 14 NE 14 Section 36 T. 10S R. 4W W.M.
Albany, Oregon 97321	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	Dearing and disease from section of submytsion corner
New Well ☐ Deepening ☑ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) WARRED FEVER CO. 1
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
Rotary D Driven D	Depth at which water was first found Previous
Cable	Static level 23 ft. below land surface. Date 9-26-73
Dug   Bored   Irrigation   Test Well   Other	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded   Welded	CASED TO THE BOTTEM
10 "Diam. from +5 ft. to 39.8 ft. Gage .250	(12) WELL LOG: Diameter of well below casing
"Diam. fromft. toft. Gage	Depth drilled 39.8 ft. Depth of completed well 39.8 ft.
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;
	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? XXYes \( \square\) No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used Torch	MATERIAL From To SWL
Size of perforations 1/4 in. by 8 in.	Previous drilling 0 31.6 23
144 perforations from 23 ft. to 38 ft.	71.0 27
perforations fromft. toft.	Gravel 31.6 36
perforations from ft. to ft.	Clay 36 39.8
	50 77.0
(7) SCREENS: Well screen installed? ☐ Yes 🔀 No	110
Manufacturer's Name	rame a
Type Model No	***
Diam Slot size Set from ft. to ft.	
Diam Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is	
lowered below static level	
Was a pump test made? 🔲 Yes 💆 No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	,
" " "	
" " " "	
Bailer test NO TEST gal./min. with XXX ft. drawdown after XXX hrs.	
A - L - L - M	2017 6817
Artesian flow g.p.m.	
perature of water 56 Depth artesian flow encountered ft.	Work started 9-24 1973 Completed 9-26 1973
(9) CONSTRUCTION:	Date well drilling machine moved off of well 9-26 1973
Well seal—Material used Previous	Drilling Machine Operator's Certification:
Well sealed from land surface to Previous	This well was constructed under my direct supervision
Diameter of well bore to bottom of seal XXXXXXXX in.	Materials used and information reported above are true to my
Diameter of well bore below seal XXXXXX in.	best knowledge and belief
Number of sacks of cement used in well seal XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	[Signed] Lale Stown Date 10/24, 1973
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No. 594
Brand name of bentonitesacks	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of water	This well was drilled under my jurisdiction and this report is
Was a drive shoe used?   Yes   No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water?  Yes XX No	Name Schoen Electric and Pump
	(Person, firm or corporation) (Type or print)  Address 626 W. Queen/Alban, Oregon 97321
Soport of Source	Address 200 10 400011 ALDAY, 04 68011 9/321
Method of sealing strata off	[Signed] James & Alexan
Was well gravel packed?   Yes XXNo Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 513 Date 10/24