NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT APR 2 4 1974 State Well No.

(Please type or print) STATE ENGINEER
(Do not write above this lineSALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name Kermit Beougher	County Benton Driller's well number
Address 1417 NW Highway 20, Albany, Ore. 9732	
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	Desired and anomico nom because of business Contra
New Well [X Deepening ☐ Reconditioning ☐ Abandon ☐	the state of the s
If abandonment, describe material and procedure in Item 12.	(11) WADED I EVEL Completed and
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
Determ C Determ C	Depth at which water was first found 28 ft.
Rotary Driven Domestic L Industrial Municipal Cable X Jetted D	Static level 16'06" ft. below land surface. Date 3-20-74
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded W	(12) WELL LOG: Diameter of well below easing 811 Depth drilled 42 ft. Depth of completed well 42 ft.
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
PO DEDEOD AMEONO.	with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used Acetylene Torch	MATERIAL From To SWL
Size of perforations ½ in. by 12 in.	Top Soil 0 3
45 perforations from 229 27 ft. to 37 ft.	Sandy Loam W/Some Grav. 3 8
perforations from ft. to ft.	Sandy Loam 8 26½
perforations from ft. to ft.	Brown Sand & Gravel 26½ 41½
(7) SCREENS: Well screen installed? Yes X No	Blue Clay 41½ 42
Manufacturer's Name	
Diam. Slot size Set from ft. to ft.	7 5 7
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Was a pump test made? Tyes Y No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
" " "	
The second of th	
Bailer test 100 gal./min. with 7 ft. drawdown after 7 hrs.	
Artesian flow g.p.m.	
mperature of water Depth artesian flow encountered ft.	Work started 3-19 19 74Completed 3-20 19 74
(9) CONSTRUCTION:	Date well drilling machine moved off of well 3-20 19 74
Well seal—Material used Bentonite	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal12in.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	[Signed] Martin Masses Date 3-26, 1974
Number of sacks of cement used in well seal sacks	[Signed] Machine Operator) Date 3 2 C., 19 14
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No436
Brand name of bentoniteOregon_Bentonite	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? 🕅 Yes 🗌 No Plugs Size: location ft.	Name Merle Warren Well Drilling
Did any strata contain unusable water? 🗌 Yes 🔏 No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address Rt./1, Box 84, Tangent, Ore. 97389
Method of sealing strata off	Mont The state of
Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's/License No. 182 Date 19/