NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF OREGON ATE ENGINEER

(Please type or print) TATE ENGINEER

(Do not write above this line)

(1) OWNER:	(10) LOCATION OF WELL:	
Name Kenneth Birch	County BENTON Driller's well number	
Address 1020 N.E. Granger	1/4 1/4 Section / T/10 R. 4(W W.M.	
Corvallis, Ore, 97330	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):	Searing and assessed from section of subdivision conten	
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL Completed as	_11
(3) TYPE OF WELL: (4) PROPOSED USE (check):	USE (check): Completed well.	
Rotary C Driven C	Depth at which water was first found	<u>55 ft.</u>
Cable Domestic Mindustrial Municipal	Static level 3.5 ft. below land s	surface. Date3/28/73
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per squar	e inch. Date
CASING INSTALLED: Threaded Welded 6 "Diam. from 0 ft. to 37 ft. Gage 250 ft. To ft. Gage 7 Diam. from ft. to ft. Gage 7 PERFORATIONS: Perforated? Yes XNo.	(12) WELL LOG: Diameter of well below casing	
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.		
	gravel dk. brown clay	0 2
perforations from ft. to ft.	yellow clay	6 18
perforations from ft. to ft.	It. grav clav	18 30
	lt. gray claystone	30
(7) SCREENS: Well screen installed? ☐ Yes 🙀 No	baring 7 gpm	60
Manufacturer's Name	broken dk. gray claystone	
Type Model No	1t. gray sandstone	88 90
Diam Slot size Set from ft. to ft.	baring 23 gpm	
Diam. Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is		
lowered below static level		-
Was a pump test made? Yes X No If yes, by whom?		
gal./min. with ft. drawdown after hrs.		
n n		
" " "		
Bailer test 30 gal./min. with 20 ft. drawdown after 2 hrs.		
Artesian flow g.p.m.		
perature of water 52Depth artesian flow encounteredft.	Work started 3/19/ 1973 Complete	d 2/28/ 1073
	Date well drilling machine moved off of well	8/28/ 1073
(9) CONSTRUCTION:		0/00/ 0/0
Well seal—Material used <u>Coment</u> Well sealed from land surface to <u>22</u> ft. Diameter of well bore to bottom of seal <u>10</u> in. Diameter of well bore below seal <u>6</u> in.	Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] (Drilling Machine Operator) Date	
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 503	
Number of sacks of bentonite used in well seal sacks Brand name of bentonite		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is	
Was a drive shoe used? ☐ Yes No Plugs Size: location ft.	true to the best of my knowledge and belief.	
Did any strata contain unusable water? Yes X No	NameRaymond C.Gellatly & Ronald S.Witham (Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address P.O. Box 1 Philon	- 12.5
Method of sealing strata off	B. M. D. H. M. Yall	
Was well gravel packed? ☐ Yes 'No Size of gravel:	[Signed] (Water Well Contra	actor)
Gravel placed fromft. toft.	Contractor's License No77 Date	1 / 2 2
	Date	Lite Jane Labor Laboration Literature