NOTICE TO WATER WELL CONTRACTOR The original and first copy

of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 O within 30 days from the date of well completion.

WATER WELL REPORT E VE
STATE OF OREGON NOV 2 9 1972

(Please type or print)

(Do not write above this line) E ENGINE State Permit No.

SALEM. OREGON Bender

(1) OWNER:	(10) LOCATION OF WELL:
Name Ken Birch	County Driller's well number
Address 1020 N. E. Granger	NE 1/4 CW 1/4 Section 7 T. // S R. / W.M.
Corvallis, Oregon 97330	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	Security of Subdivision Confer
New Well Deepening ☐ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found
Rotary Driven Domestic Industrial Municipal Domestic	1.2
Cable Jetted Domestic Industrial Municipal Dug Bored Irrigation Test Well Other	10/1
	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing
	Depth drilled ft. Depth of completed well ft.
"Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;
"Diam. fromft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated.
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perior used Tonch	
Size of perforations in. by in.	The state of the s
9.0 perforations from 3/ ft. to 4/ ft.	PLACE CIAN 1' 2'
perforations fromft. toft.	CREV CLAV 3'19'
perforations fromft. toft.	BROWN CLAV 121 171
	BLUE SANDY CLEAV 17/57
(7) SCREENS: Well screen installed? Yes No	CEMENT SAND 27.30
Manufacturer's Name	SAND + GRAVEL 30 39 13
Type Model No.	CEMENTED SAND + 39 411
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	CRAVEL
Det Holl It. to It.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes No If yes, by whom?	
gal./min. with ft. drawdown after hrs.	
" " "	
n n n n	
Bailer test 67 gal./min. with 8 ft. drawdown after 2 hrs.	
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 9/11/72_19 Completed 9/19/72_19
(9) CONSTRUCTION:	Date well drilling machine moved off of well
Well seal-Material used Coment + grout	Drilling Machine Operator's Certification:
Well sealed from land surface toft_	This well was constructed under my direct supervision.
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	[Signed Market 1] ellipse 19/12/7210
Number of sacks of cement used in well sealsacks	Drilling Macdine Operator)
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons of water	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? ☐ Yes No Plugs	true to the best of my knowledge and belief.
Did any strata contain unusable water? Yes No	Name Ray Gellatly & Ron Witham (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address EXX P. O. Box 1, Philomath, OR 97370
Method of sealing strata off	P. 1.0 4.00.TT.
Was well gravel packed? ☐ Yes (1) No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No