

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

STATE ENGINEER

G-4442

State Well No. 11/4w-19M

State Permit No.

(1) OWNER:

Name Oregon State University
Address 606 S. 15th St. Corvallis, Oregon

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon []
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven []
Cable [x] Jetted []
Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [x] Industrial [] Municipal []
Irrigation [] Test Well [] Other []

(5) CASING INSTALLED:

8" Diam. from 0 ft. to 57 ft. Gage .250
Threaded [] Welded [x]

(6) PERFORATIONS:

Perforated [x] Yes [] No []
Type of perforator used torch
Size of perforations 3/8 in. by 6 in.
312 perforations from 39 ft. to 55 ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 29 ft. below land surface Date 4/15/68
Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? [] Yes [x] No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
Baller test 30 gal./min. with 1 ft. drawdown after 1 hrs.
Artesian flow g.p.m. Date
Temperature of water 54 Was a chemical analysis made? [] Yes [x] No

(10) CONSTRUCTION:

Well seal—Material used Bentonite
Depth of seal 35 ft.
Diameter of well bore to bottom of seal 12 in.
Were any loose strata cemented off? [] Yes [x] No Depth
Was a drive shoe used? [] Yes [x] No
Did any strata contain unusable water? [] Yes [x] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [x] Yes [] No Size of gravel: 3/8"
Gravel placed from 50 ft. to 35 ft.

(11) LOCATION OF WELL:

County Benton Driller's well number N 7-68
SW 1/4 SW 1/4 Section 19 T. 11S R. 4W W.M.
Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 8
Depth drilled 60 ft. Depth of completed well 60 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with 4 columns: MATERIAL, From, To, SWL. Rows include Top soil, Willamette silt, Silt, sandy, Gravel, consolidated, Gravel, sandy, loose, Clay, blue.

Work started April 9 1968 Completed April 15 1968

Date well drilling machine moved off of well April 15 1968

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] C.V. Todd Date
(Drilling Machine Operator)

Drilling Machine Operator's License No. 450

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Todd's Drilling Service
(Person, firm or corporation) (Type or print)

Address Rt. 1, Box 144 Monmouth, Ore.

[Signed] C.V. Todd
(Water Well Contractor)

Contractor's License No. 450 Date Apr. 23, 1968