

NOTICE TO WATER WELL CONTRACTOR  
The original and first copy  
of this report are to be  
filed with the

**WATER WELL REPORT**

**RECEIVED**

STATE ENGINEER, SALEM, OREGON 97310  
within 30 days from the date  
of well completion.

STATE OF OREGON

JUL 13 1976

State Well No.

(Please type or print)

(Do not write above this line)

WATER RESOURCES DEPT.

SALEM, OREGON

State Permit No.

115/4W-20  
TRANS. 9883 (A.P.G-1603)

*Bent  
2765*

**(1) OWNER:**

Name Rosalie Hill

Address 1529 N.E. 94  
Seattle, Wn 98115

**(2) TYPE OF WORK (check):**

New Well  Deepening  Reconditioning  Abandon

If abandonment, describe material and procedure in Item 12.

**(3) TYPE OF WELL:**

Rotary  Driven   
Cable  Jetted   
Dug  Bored

**(4) PROPOSED USE (check):**

Domestic  Industrial  Municipal   
Irrigation  Test Well  Other

**(5) CASING INSTALLED:**

Threaded  Welded   
10" Diam. from 0 ft. to 33 ft. Gage .250  
" Diam. from ft. to ft. Gage  
" Diam. from ft. to ft. Gage

**(6) PERFORATIONS:**

Perforated?  Yes  No

Type of perforator used

acetylene

Size of perforations 28 in. by 6 in.  
28 perforations from 22 ft. to 30 ft.  
perforations from ft. to ft.  
perforations from ft. to ft.

**(7) SCREENS:**

Well screen installed?  Yes  No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from ft. to ft.

Diam. Slot size Set from ft. to ft.

**(8) WELL TESTS:**

Drawdown is amount water level is lowered below static level

Was a pump test made?  Yes  No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

" " " "

" " " "

Baller test 600 gal./min. with 1 ft. drawdown after 2 hrs.

Artesian flow g.p.m.

Temperature of water 51 Depth artesian flow encountered ft.

**(9) CONSTRUCTION:**

Well seal—Material used cement

Well sealed from land surface to 18 ft.

Diameter of well bore to bottom of seal 14 in.

Diameter of well bore below seal 10 in.

Number of sacks of cement used in well seal 2 sacks

Number of sacks of bentonite used in well seal - sacks

Brand name of bentonite -

Number of pounds of bentonite per 100 gallons of water - lbs./100 gals.

Was a drive shoe used?  Yes  No Plugs Size: location ft.

Did any strata contain unusable water?  Yes  No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed?  Yes  No Size of gravel:

Gravel placed from ft. to ft.

**(10) LOCATION OF WELL:**

County Benton

Driller's well number

¼ Section 20 T. 115 R. 4W W.M.

Bearing and distance from section or subdivision corner

**(11) WATER LEVEL: Completed well.**

Depth at which water was first found 22 ft.

Static level 15 ft. below land surface. Date 5/7/76

Artesian pressure lbs. per square inch. Date

**(12) WELL LOG:**

Diameter of well below casing 10"

Depth drilled 33 ft. Depth of completed well 33 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
topsoil	0	6	
brown sandy clay	6	18	
cemented gravel	1.8	22	
loose sand & gravel			
baring 600gpm	22	32	
yellow cly	32	33	

Work started 5/7/ 19 76 Completed 5/7/ 1976

Date well drilling machine moved off of well 5/7/ 1976

**Drilling Machine Operator's Certification:**

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Ronald S. Witham Date 5/28/1976  
(Drilling Machine Operator)

Drilling Machine Operator's License No. 503

**Water Well Contractor's Certification:**

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Raymond C. Gellatly & Ronald S. Witham  
(Person, firm or corporation) (Type or print)

Address P.O. Box 1, Philomath, Ore. 97370

[Signed] Raymond C. Gellatly  
(Water Well Contractor)

Contractor's License No. 77 Date 5/28/ 1976