NOTICE TO WATER WILL CONTRACTOR

The original and first copy of the report

are to be filed with the C C V WATER WELL REPORT

WATER RESOURCES DEPARTMENT.

SALEM, OREGON 97310 AUG 16 1977

within 30 days from the date
of well completion ATER RESOURCES

STATE OF OREGON

(Please type or print)

Be not write above this line)



State Well No. 115/6W-12 bd

State Permit No. .

OMLEM, OKEGON	(10) TOCATION OF WELL
(1) OWNER: Rudolph Sternberg	(10) LOCATION OF WELL: Benton 96877G
5120 N W HWY 99 W	County Driller's well number
Corvallis, Oregon 97330	SE 14 NW 14 Section 12 T. 11SR. 5W W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well X Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
	Depth at which water was first found 125 ft.
Cable  Jetted  Domestic  Industrial  Municipal	Static level 80 ft. below land surface. Date 8/10/77
Dug   Bored   Irrigation   Test Well   Other	Artesian pressure Ibs. per square inch. Date
CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well below casing 6
6 "Diam from 0 ft to 60 ft Gage 250	
5" Diam. from ft. to ft. Gage	Depth drilled 200 ft. Depth of completed well 200 ft.
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated.
DEDEODATIONS.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
PERFORATIONS: Perforated?   Yes XKNo.	
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Top Soil 0 1
perforations from ft. to ft.	Light Brown Clay 1 3
perforations fromft. toft.	Sticky Brown Clay 3 9
perforations fromft. toft.	Yellowish Brown Weathered
(7) SCREENS: Well screen installed?   Yes X No	sandy Clay 9 27
Manufacturer's Name	Sandyxxxxx Fine Greenish/Gray 27 54 Soft Sandstone
Type Model No	Fine Greenish Gray Sandstone 54 97 80
Diam. Slot size Set from ft. to ft.	Fine Green Sandstone 97 200
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is	
lowered below static level	
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
" " H "	
" " " " " " " " " " " " " " " " " " "	- 4-4-5
gal./min. with 100 ft. drawdown after 4 hrs.	
Artesian flow g.p.m.	
operature of water 53 Depth artesian flow encountered ft.	Work started 8/10 19 77 Completed 8/11 19 77
(9) CONSTRUCTION:	Date well drilling machine moved off of well 8/11 19 77
Well seal—Material used	Drilling Machine Operator's Certification:
Well sealed from land surface to18	This well was constructed under my direct supervision.
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal6 in.	
Number of sacks of cement used in well sealsacks	[Signed] Machine Operator) Date 8/12, 19.7.
How was cement grout placed?	Drilling Machine Operator's License No. 1072
The state of the s	Water Well Contractor's Certification:
hand mixed and hand placed	This well was drilled under my jurisdiction and this report is
T. C.	true to the best of my knowledge and belief.
Was a drive shoe used? 🗌 Yes 🔏 No Plugs Size: location ft.	Name Water Boy's Well Drilling
Did any strata contain unusable water?  Yes No	(Person, firm or corporation) (Type or print) Address 1416 East 32nd Albany, Oregon 97321
Type of water? depth of strata	Address 7
Method of sealing strata off	[Signed] Manny (Water Well Contractor)
Was well gravel packed? [ Yes XNo Size of gravel:	(Water Well Obudractor)
Gravel placed fromft. toft.	Contractor's License No. 572 Date 19/7