NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT STATE OF OREGON

(Please type or print)

MAR 84078ell No. L(S/SW-12

(Do not write above this line)

VIATER RESOURGE DOUBLE SALEM. OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name John BRY ANT	
Address 5925 N.W. DINE WOOD PL.	11 11 0 - 115 115
CORVALLIS DRE 973	1/4 1/4 Section / 2 T. // R. 5 W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WARRED LEAVES CO. 1. 1
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
Rotary Driven Domestic W Industrial Description	Depth at which water was first found ft.
Cable Z Jetted Domestic Industrial Municipal Dug Bored Irrigation Test Well Other	1. below land surface. Date 3/4/18
A CONTRACT OF CONT	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below cooling
6 " Diam. from 0 ft. to 49 ft. Gage ,250	Diameter of well below casing
" Diam. from ft. to ft. Gage	6/ 1
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated? [] Vog. [7] No.	with at least one entry for each change of formation. Report each change in
Type of perforator used	position of Static Water Level and indicate principal water-bearing strata.
	MATERIAL From To SWL
1 49	TopSail-CLAY BROWN 0' 3'
perforations from ft. to ft	SAULUCIA, Daniel De
perforations from ft. to ft.	SANdy CLAY-BROWN 3' 12'
	CLAY STONE-BROWN 12'59'
(7) SCREENS: Well screen installed? Yes No	- 1/ 210/1 DAOWN /2 D/
Manufacturer's Name	CLAYSTONE - BROKEN
Type Model No.	WATER BEARING - FRAY 59 63' 11'
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	<u> </u>
	CLAYSTONE - GRAY 6.3' 67 11'
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? Yes No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
" " "	
" " " "	
Bailer test / gal./min. with 46 ft. drawdown after / hrs.	
Ambarian Carry	A CONTRACT OF THE CONTRACT OF
perature of water Sk Bepth artesian flow encounteredft.	
Depth artesian flow encountered ft.	Work started 3/2 19/8 Completed 3/4 19/8
(9) CONSTRUCTION:	Date well drilling machine moved off of well 3/4 19>8
Well seal—Material used SENTONITE 4 Wks. Well sealed from land surface toft.	Drilling Machine Operator's Certification:
	This well was constructed under my direct supervision
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Rolling Machine Operator) Date 3/6, 1978
Number of sacks of cement used in well seal sacks	1
How was cement grout placed?	Drilling Machine Operator's License No. 25
the second secon	Water Well Contractor's Certification:
THE SECOND SECON	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? Yes No Plugs Size: location ft.	will to the best of my knowledge and helief
Did any strata contain unusable water? Yes No	Name Taylor Well Drill IN6 (Person, firm or corporation) (Type or print) 92
Type of water? depth of strata	Address 2715NEVAN BUREN CORVAILS
Method of sealing strata off	DIA-OI
	[Signed] Role & Sault
	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 6 1/2 Date 3/6 1928