NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

TATE ENGINEER Permit No. G-6854
SALEM OREGON

(1) OWNER:	(10) LOCATION OF WELL: County British Driller's well number			
Name Ridgewood Estates				
Address 7985 Bicqueel Dr. Corvallis	1/4 1/4 Section 30 T.115 R. 5 Cm W.M.			
Bregon	Bearing and distance from section or subdivision corner			
(2) TYPE OF WORK (check):				
New Well Deepening □ Reconditioning □ Abandon □				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 184 ft.			
Rotary Driven Domestic Industrial Municipal	Static level 44 ft. below land surface. Date 3/28/13			
Cable Jetted Irrigation Test Well Other	Artesian pressure lbs. per squar			41
248.	Artesian pressure ins. per squa.	e men.	Date	
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing			
8 " Diam. from #42ft. to 68 ft. Gage 450	Depth drilled 192 ft. Depth of completed well 192 ft.			
	Formation: Describe color, texture, grain size and structure of materials;			
"Diam. from	and show thickness and nature of each stratu	m and a	quifer pe	netrated,
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of forms position of Static Water Level and indicate prin			
Type of perforator used	MATERIAL	From	To	SWL
Size of perforations in. by in.	Sail	65	3	14
perforations fromft, toft.	CIAY, Yellow	3	10	
perforations fromft. toft.	SANGVOCK Drown	10	58	
perforations fromft. toft.	WOUART?			18
	SANdrOCK DIVE	58	92	
(7) SCREENS: Well screen installed? Yes No	HAVY WOVARTZ			77.
Manufacturer's Name	SANdrock, brown	92	184	
Type Model No.	WOVARTZ	1000	3 00 00	
Diam. Slot size Set from ft. to ft.	SANdrock, Drown	184	192	44
Diam, Slot size Set from ft. to ft.	broken waters	-		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	STICATOM.			-
Was a pump test made? Yes \(\subseteq No \) If yes, by whom?				
Yield: 60 gal./min. with/4 ft. drawdown after 24 hrs.				
ried: (b) gat./min. with/ 12. drawdown after 5 mis.				
" " " " " " "	8			

Bailer test gal./min. with ft. drawdown after hrs.	7			
Artesian flow g.p.m.		n3	1000	110
perature of water Depth artesian flow encountered ft.	Work started /-/0 19 73 Complet	ed///W	unde	5 19/0
(9) CONSTRUCTION:	Date well drilling machine moved off of well	Marci	1 28	19/3
Well seal-Material used Cemzat	Drilling Machine Operator's Certification			
Well sealed from land surface toft.	This well was constructed under my Materials ased, and information reported			
Diameter of well bore to bottom of sealin.	best knowledge and belief.		120	10
Diameter of well bore below seal	[Signed] (Drilling Machine Operator)	Date /	120	., 19/.2
Number of sacks of cement used in well sealSQ sacks	Drilling Machine Operator's License No			
Number of sacks of bentonite used in well seal sacks				
Brand name of bentonite	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons of waterlbs./190 gals.	This well was drilled under my jurisdiction and this report is			
of waterlbs./100 gals. Was a drive shoe used? Yes Plugs Size; location ft.	true to the best of my knowledge and belief.			
Did any strata contain unusable water? Yes No	Name (Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address 7555 Kyly OAK Creek	DR	CORT	005
Method of sealing strata off	Formelle Met	2160	30 3	
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	[Signed] (Water Well Con	ractor)		······································
Gravel placed from ft. to ft.	Contractor's License No.237 Date	Ru	30	19
		18		