NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

VATER WELL REPORT 29 1972

STATE OF OREGON OV 29 1972

(Please type Common TE ENGINEER

(Do not write above this Me) M. OREGON State Permit No.

(1) OWNER;	(10) LOCATION OF WELL:
Name Ill N. Illmali	County BENION Driller's well number
Address 2330 N E STRAW BENTY	1 1/2 1/4 / E 1/4 Section 25 T. // SR. 5 W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found
Rotary Driven Domestic Industrial Municipal Domestic Municipal Domestic	Static level 15 ft. below land surface. Date 5/1/72
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Through D. Welded D.	
Tiffeaded [] Weided []	(12) WELL LOG: Diameter of well below casing
Tit. toft. Gageft. toft. Gageft. toft. Gageft.	Depth drilled 34 ft. Depth of completed well 34 ft.
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;
To the state of th	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used / / C/	MATERIAL From To SWL
Size of perforations in. by in.	LOAM 0' 22'
4.2 perforations from 26 ft. to 34 ft.	CEMENTED SAND + 12'25.
perforations from ft. to ft.	GRAVEL
perforations from ft. to ft.	COAHSE GRAVEL + SAND 25 34 15
(7) SCREENS: Well screen installed?   Yes No	UP TO 34
Manufacturer's Name	
Type Model No.	
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made?  Yes No If yes, by whom?	
Yild: gal./min. with ft. drawdown after hrs.	
" - " " " " " " " " " " " " " " " " " "	
" " " "	
Bailer test 45 gal./min. with 1 ft. drawdown after 2 hrs.	
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started , 5/2 1972 Completed 55 1972
(9) CONSTRUCTION:	Date well drilling machine moved off of well 5 1972
Well seal-Material used Jon Gold	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision.  Materials used and information reported above/are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.
Diameter of well bore below seal	[Signed] (Drilling Machine Operator) Date , 1972
Number of sacks of cement used in well seal sacks  Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.
Brand name of bontonito	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of water	This well was drilled under my jurisdiction and this report is
Was a drive shoe used?   Yes No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water?   Yes Vo	Name (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address Por Box   PHILOMATH ORF
Method of sealing strata off	Des OD St DO TO
Was well gravel packed? [] Yes [ No Size of gravel:	[Signed (Water Well Contractor)
Gravel placed fromft. toft.	Contractor's License No. 77 Date 117/2 19
(USE ADDITIONAL SH	