NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT

STATE OF OREGON

WATER RESOURCES DEPARTMENT, ER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the dat
of well completion. or replease type or print) (Do dot write above this line)



State Well No	25/5W-22
---------------	----------

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name Western Pully A Products Company EPT.	County Benton Driller's well number C/56/A
Address P.O.Box 968 SALEM, CALLON	
Corvallis, Oregon 97330	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well K Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 38 ft.
Rotary 🔼 Driven 🗆 Domestic 🗆 Industrial 🛛 Municipal 🖸	
Cable	
	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing
10 "Diam. from 0 ft. to 42 ft. Gage .250	Depth drilled 160 ft. Depth of completed well 160 ft.
B"PVC	Formation: Describe color, texture, grain size and structure of materials;
3"PVC	and show thickness and nature of each stratum and aquifer penetrated
PERFORATIONS: Perforated? Yes Ft No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
(6) FERFORATIONS: Perforated? ☐ Yes ☐ No. Type of perforator used	
Size of perforations in. by in.	
perforations from ft. to ft.	Black clayred 3 5
perforations fromft. toft.	Blue clay 5 14
perforations from ft. to ft.	Brown clay 14 32
	Clay&gravel 32 38
(7) SCREENS: Well screen installed? TY Yes I No Ga tor	Small gravel&sand 38 57
Manufacturer's Name	Blue clay&gravel 57 63
Type PVC Diam. 8" Slot size 010 Set from 23 ft. to 53 ft. Diam. 8" Slot size 010 Set from 100 ft. to 140	Sticky blue clay 63 96
Diam. 8" Slot size 010 Set from 33 ft. to 53 ft. to 53 ft. to 53 ft. to 54 ft. to 55 f	Gray sand 96 137
	Sandy gray clay
(8) WELL TESTS: Drawdown is amount water level is lowered below static level Aquatic	Brue cray 140 160
Was a pump test made? The Yes I No If yes, by whom? Pump	bottom of well backfilled to 140' with
gal./min. with 110 ft. drawdown after 3 hrs.	apea gravel to support screen.
" " "	
" " "	
Bailer test XXXXXX XXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	7 Table 1 Tabl
Arresian flow g.p.m.	
	E/0/77 E/44/77
perature of water Depth artesian flow encountered ft.	Work started 2/7/11 19 Completed 2/11/11 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well 5/11/77 19
Well seal-Material usedCement	Drilling Machine Operator's Certification:
Well sealed from land surface to ft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of seal14 in.	best knowledge and belief.
Diameter of well bore below seal	[Signed] Lall Machine Operaty] Date 5/16/779
Number of sacks of cement used in well seal	Drilling Machine Operator's License No
How was cement grout placed?Mixed &poured from top.	Diffing Machine Operator's Literise No.
Pumped through tremie	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? Yex X No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water? Yes 15 No	Name Corvallis Drilling Co. Inc. (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 3440 SW 3rd St. Corvallis, Oregon 97330
Method of sealing strata off	11 110
Was well gravel packed? ☐ Yes 돈 No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed fromft. toft.	560 - 5/16/77
It,	Contractor's License No Date